



# Safety Data Sheet

Issue Date 24-Oct-2018

Revision Date 24-Oct-2018

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F151-1051A  
**Product Name** ELASTO-GRIP FC

### Other means of identification

**Common Name** SERIES 151, PART A  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

### **Hazard statements**

Causes serious eye irritation  
May cause an allergic skin reaction  
May cause genetic defects  
May cause cancer  
Suspected of damaging fertility or the unborn child  
Causes damage to organs through prolonged or repeated exposure

**Appearance** opaque**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation or rash occurs: Get medical advice/attention  
 Wash contaminated clothing before reuse

**Storage**

Store locked up  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Causes mild skin irritation  
 Toxic to aquatic life with long lasting effects  
 Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).  
 Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs  
 Contains ethylene glycol monobutyl ether which may cause blood damage based on animal data.  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 30.11817 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
EPOXY RESIN	-	10 - <30%
PROPRIETARY SOLVENT	-	1 - <10%
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	124-17-4	1 - <10%
BENZYL ALCOHOL	100-51-6	1 - <10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

<b>Notes to physician</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Ammonia.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.
-----------------------------	--

**Environmental Precautions**

<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
----------------------------------	---

**Methods and material for containment and cleaning up**

<b>Methods for containment</b>	Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.
--------------------------------	--

<b>Methods for cleaning up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
--------------------------------	---

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Acids. Alkaline. Amines. Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPRIETARY SOLVENT	TWA: 50 ppm STEL: 100 ppm	TWA: 100 ppm TWA: 360 mg/m <sup>3</sup> STEL: 150 ppm STEL: 540 mg/m <sup>3</sup>	

### Appropriate engineering controls

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<b>Property</b>	<b>Values</b>	<b>Remarks</b>
pH		No data available

Melting point / freezing point	No data available	No data available
Boiling point / boiling range	100 °C / 212.0 °F	
Flash point	No information available	
Evaporation rate		No data available
Flammability (solid, gas)	No data available	No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	1.1	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.03383	g/cm <sup>3</sup>
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	1000 centipoises	approx

**Other Information**

Density	8.62217 lbs/gal
Volatile organic compounds (VOC) content	1.50378 lbs/gal
Total volatiles weight percent	79.23 %
Total volatiles volume percent	82.26 %
Bulk density	No information available

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Acids, Alkaline, Amines, Strong oxidizing agents

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Ammonia. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Contact with eyes may cause irritation.
<b>Skin contact</b>	May cause irritation. May cause sensitization by skin contact.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PROPRIETARY SOLVENT	= 5000 mg/kg ( Rat )	= 13 g/kg ( Rabbit )	> 7559 ppm ( Rat ) 6 h
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	= 6500 mg/kg ( Rat )	= 14500 mg/kg ( Rabbit )	= 72500 mg/m <sup>3</sup> ( Rat ) 4 h
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity** Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Contains ethylene glycol monobutyl ether which may cause blood damage based on animal data. Skin sensitizer. Substances known to be mutagenic to man. Substances known to impair fertility.

**Sensitization** May cause sensitization of susceptible persons.

**Mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

**Reproductive effects** Suspected of damaging fertility or the unborn child.

**STOT - single exposure** No information available

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure

**Target organ effects** blood, Central nervous system, Central Vascular System (CVS), Eyes, hematopoietic system, kidney, liver, Lungs, respiratory system, Skin.

**Aspiration hazard** No information available.

**Acute Toxicity** 30.11817 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

69.83527 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
PROPRIETARY SOLVENT		20.8: 96 h Pimephales promelas g/L LC50 static 4600 - 10000: 96 h Leuciscus idus mg/L LC50 static	23300: 48 h Daphnia magna mg/L EC50
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4		50 - 70: 96 h Brachydanio rerio mg/L LC50 static 77: 96 h Pimephales promelas mg/L LC50 static	665: 48 h Daphnia magna mg/L LC50
BENZYL ALCOHOL 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	460: 96 h Pimephales promelas mg/L LC50 static 10: 96 h Lepomis macrochirus mg/L LC50 static	23: 48 h water flea mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Chemical name	log Pow
PROPRIETARY SOLVENT	-0.437
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	1.77

BENZYL ALCOHOL 100-51-6	1.1
----------------------------	-----

**Other Adverse Effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. TRANSPORT INFORMATION**

**DOT**  
**Proper Shipping Name** paint,water base freezable NOT REGULATED

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Does Not Comply
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Does Not Comply
<b>AICS</b>	Complies

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Chemical name</b>	<b>HAPS Data</b>
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE - 124-17-4	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**California Prop. 65**

None of the ingredients are listed with California Proposition 65.

Chemical name	California Prop. 65
AMORPHOUS SILICA - 7631-86-9	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
PROPRIETARY SOLVENT	X	X	X
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	X		X
BENZYL ALCOHOL 100-51-6		X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 0	Instability 0	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 0	Reactivity 0	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 24-Oct-2018

Revision Summary  
 4 5 7 10 8 9 11 14 15 1

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of SDS**





# Safety Data Sheet

Issue Date 05-Mar-2018

Revision Date 05-Mar-2018

Revision Number 5

## 1. IDENTIFICATION

### Product identifier

**Product Code** F151-1051B  
**Product Name** ELASTO-GRIP FC GREEN CONVERTER

### Other means of identification

**Common Name** SERIES 151-1051, PART B  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 1
-----------------------------------	------------

### Label elements

#### EMERGENCY OVERVIEW

**Danger**

#### **Hazard statements**

Causes serious eye damage



**Appearance** green

**Physical state** liquid

**Odor** Slight

#### **Precautionary Statements**

**Prevention**

Wear protective gloves/protective clothing/eye protection/face protection

**Response**

Get medical advice/attention if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

**Storage**

Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Causes mild skin irritation

Harmful to aquatic life with long lasting effects

Acute Toxicity 14.11162 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
EPOXY POLYMER	155240-10-1	10 - <30%
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	124-17-4	1 - <10%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Acids. Alkalis. Cleaning solutions such as Chromerge and Aqua Regia.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure guidelines**

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV).

Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

#### **Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.
<b>Skin and body protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Respiratory protection</b>	Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.
<b>General hygiene considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### **Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	green	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point	No data available	No data available
Boiling point / boiling range	100 °C / 212.0 °F	
Flash point	No information available	
Evaporation rate		No data available
Flammability (solid, gas)	No data available	No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	.8	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.00928	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

### **Other Information**

<b>Density</b>	8.41737 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	1.18846 lbs/gal
<b>Total volatiles weight percent</b>	85.14 %
<b>Total volatiles volume percent</b>	86.04 %
<b>Bulk density</b>	No information available

## 10. STABILITY AND REACTIVITY

### **Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Epoxy constituents.

**Incompatible materials**

Strong oxidizing agents, Acids, Alkalis, Cleaning solutions such as Chromerge and Aqua Regia

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Aldehydes. Carbon oxides. Hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	= 6500 mg/kg ( Rat )	= 14500 mg/kg ( Rabbit )	= 72500 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Chronic Toxicity</b>	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
<b>Sensitization</b>	No information available.
<b>Mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	There are no known carcinogenic chemicals in this product.
<b>Reproductive effects</b>	No information available.
<b>STOT - single exposure</b>	No information available
<b>STOT - repeated exposure</b>	No information available
<b>Aspiration hazard</b>	No information available.
<b>Acute Toxicity</b>	14.11162 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Harmful to aquatic life with long lasting effects

14.29022 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4		50 - 70: 96 h Brachydanio rerio mg/L LC50 static 77: 96 h Pimephales promelas mg/L LC50 static	665: 48 h Daphnia magna mg/L LC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Chemical name	log Pow
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	1.77

**Other Adverse Effects**

No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

**DOT****Proper Shipping Name**

paint,water base freezable Not regulated

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

**International Inventories**

TSCA	Complies
DSL/NDSL	Does Not Comply
EINECS/ELINCS	Does Not Comply
ENCS	Does Not Comply
IECSC	Does Not Comply
KECL	Does Not Comply
PICCS	Does Not Comply
AICS	Does Not Comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**Chemical name** **HAPS Data**  
 DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE - 124-17-4	1.0

**SARA 311/312 Hazardous**

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**California Prop. 65**

None of the ingredients are listed with California Proposition 65.

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Chemical name	New Jersey	Massachusetts	Pennsylvania
DIETHYLENE GLYCOL MONOBUTYL ETHER ACETATE 124-17-4	X		X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 3	Flammability 0	Instability 1	Physical hazard -
<b>HMIS (Hazardous Material Information System)</b>	Health 3	Flammability 0	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 05-Mar-2018  
 Revision Summary  
 9 4 5 7 10 8 11 14 15 1

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS