

Safety Data Sheet

Issue Date 14-Aug-2018

Revision Date 02-Mar-2018

Revision Number 5

1. IDENTIFICATION

Product identifier

Product Code F072-00WHA
Product Name ENDURA-SHIELD TNEMEC WHITE

Other means of identification

Common Name SERIES 72, PART A
UN/ID no. 1263
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 2

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 Highly flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor Strong aromatic

Precautionary Statements

Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

Acute Toxicity 61.28598 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
ACRYLIC COPOLYMER	-	10 - <30%

TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - <30%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - <30%
OH FUNCTIONAL POLYOL RESIN	8001-79-4	10 - <30%
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	108-65-6	10 - <30%
METHYL N-AMYL KETONE	110-43-0	1 - <10%
N-BUTYL ACETATE	123-86-4	1 - <10%
QUATERNARY AMMONIUM COMPOUNDS	68953-58-2	1 - <10%
METHYL ETHYL KETONE	78-93-3	1 - <10%
AMORPHOUS SILICA	7631-86-9	1 - <10%
CELLULOSE ACETATE BUTYRATE	9004-36-8	1 - <10%
XYLENE	1330-20-7	0.1 - <1%
ALUMINUM OXIDES	1344-28-1	0.1 - <1%
BIS (PENTAMETHYLPIPERIDYL) SEBACATE	41556-26-7	0.1 - <1%
ALUMINUM HYDROXIDE	21645-51-2	0.1 - <1%
PROPRIETARY	-	0.1 - <1%
DEFOAMER	63148-62-9	0.1 - <1%
ZIRCONIUM OXIDE	1314-23-4	0.1 - <1%
PROPRIETARY	-	0.1 - <1%
PROPRIETARY	82919-37-7	0.1 - <1%
POTASSIUM CARBOXYLATE	3164-85-0	0.1 - <1%
DISPERSING AGENT	-	0.1 - <1%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0 - <0.1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin contact	Wash affected area with soap and water. Remove contaminated clothing. Dispose of or launder accordingly. Consult a physician if skin irritation persists.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Chlorine. Fluorine.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Ensure adequate ventilation. Avoid contact with eyes, skin and clothing. Use personal protective equipment.

Environmental Precautions

Environmental precautions Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Keep away from heat, sparks and open flame. - No smoking.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children.

Incompatible products Acids. Bases. caustic. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m ³	-	250 mg/m ³
METHYL N-AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³	800 ppm
N-BUTYL ACETATE	TWA: 50 ppm	TWA: 150 ppm	1700 ppm

123-86-4	STEL: 150 ppm	TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³	
METHYL ETHYL KETONE 78-93-3	TWA: 200 ppm STEL: 300 ppm	TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³	3000 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m ³	3000 mg/m ³
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	
ALUMINUM OXIDES 1344-28-1	TWA: 1 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	
ALUMINUM HYDROXIDE 21645-51-2	TWA: 1 mg/m ³	-	
ZIRCONIUM OXIDE 1314-23-4	TWA: 5 mg/m ³	-	25 mg/m ³
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³ TWA: 50 µg/m ³	50 mg/m ³

Appropriate engineering controls

Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Strong aromatic
Appearance	opaque	Odor threshold	No information available
Color	No information available		
Property	Values	Remarks	
pH		No data available	
Melting point / freezing point	No data available	No data available	

Boiling point / boiling range	78 °C / 172.0 °F	
Flash point	37 °C / 99.0 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)	No data available	No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	1.1	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.34248	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	700 centipoises	approx

Other Information

Density	11.19627 lbs/gal
Volatile organic compounds (VOC) content	2.50385 lbs/gal
Total volatiles weight percent	32.72 %
Total volatiles volume percent	42.32 %
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Reacts with air to form peroxides.

Incompatible materials

Acids, Bases, caustic, Strong oxidizing agents

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Chlorine. Fluorine. Oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Causes serious eye irritation.
Skin contact	Irritating to skin. May cause sensitization by skin contact.
Ingestion	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg (Rat)	-	-
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6	= 8532 mg/kg (Rat)	> 5 g/kg (Rabbit)	-
METHYL N-AMYL KETONE 110-43-0	= 1600 mg/kg (Rat) = 1670 mg/kg (Rat)	= 12.6 mL/kg (Rabbit) = 12600 µL/kg (Rabbit)	2000 - 4000 ppm (Rat) 6 h
N-BUTYL ACETATE 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
QUATERNARY AMMONIUM COMPOUNDS 68953-58-2	> 5000 mg/kg (Rat)	-	> 12.6 mg/L (Rat) 4 h
METHYL ETHYL KETONE 78-93-3	= 2483 mg/kg (Rat) = 2737 mg/kg (Rat)	= 5000 mg/kg (Rabbit) = 6480 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
ALUMINUM OXIDES 1344-28-1	> 5000 mg/kg (Rat)	-	-
BIS (PENTAMETHYLPIPERIDYL) SEBACATE 41556-26-7	= 2615 mg/kg (Rat)	-	-
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg (Rat)	-	-
DEFOAMER 63148-62-9	> 17 g/kg (Rat) > 24 g/kg (Rat)	> 2 g/kg (Rabbit)	-

Information on toxicological effects

Symptoms

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Irritating to skin.

Eye damage/irritation

Irritating to eyes.

Chronic Toxicity

Substances known to impair fertility. Substances known to be mutagenic to man.

Substances known to be carcinogenic to man. Skin sensitizer. Avoid repeated exposure.

Sensitization

May cause sensitization of susceptible persons.

Mutagenicity

May cause genetic defects.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
AMORPHOUS SILICA 7631-86-9		Group 1 Group 3	Known	
XYLENE 1330-20-7		Group 3	-	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X

Reproductive effects

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Skin, Eyes, Central Nervous System (CNS)

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure

Target organ effects

Central nervous system, Eyes, Skin, Lungs, Peripheral Nervous System (PNS), respiratory system.

Aspiration hazard

No information available.

Acute Toxicity

61.28598 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6		161: 96 h Pimephales promelas mg/L LC50 static	500: 48 h Daphnia magna mg/L EC50
METHYL N-AMYL KETONE 110-43-0		126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	
N-BUTYL ACETATE 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static	72.8: 24 h Daphnia magna mg/L EC50
METHYL ETHYL KETONE 78-93-3		3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	5091: 48 h Daphnia magna mg/L EC50 520: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50 > 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
BIS (PENTAMETHYLPIPERIDYL) SEBACATE 41556-26-7		0.97: 96 h Lepomis macrochirus mg/L LC50 static	20: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6	0.43
METHYL N-AMYL KETONE 110-43-0	1.98
N-BUTYL ACETATE 123-86-4	1.81
METHYL ETHYL KETONE 78-93-3	0.29
XYLENE 1330-20-7	2.77
BIS (PENTAMETHYLPIPERIDYL) SEBACATE 41556-26-7	0.37

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ETHYL KETONE 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		
ISOBUTYL ALCOHOL 78-83-1	U140	Included in waste streams: F005, F039		U140
ETHYLBENZENE 100-41-4		Included in waste stream: F039		

Chemical name	CAWAST
N-BUTYL ACETATE 123-86-4	Toxic
METHYL ETHYL KETONE 78-93-3	Toxic Ignitable
XYLENE 1330-20-7	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no. 1263
 Proper Shipping Name PAINT
 Hazard Class 3
 Packing Group III
 Emergency Response Guide Number 128

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Does Not Comply
 ENCS Does Not Comply
 IECSC Complies
 KECL Does Not Comply
 PICCS Does Not Comply
 AICS Does Not Comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name HAPS Data
 XYLENE

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
METHYL ETHYL KETONE - 78-93-3	1.0
XYLENE - 1330-20-7	1.0
ALUMINUM OXIDES - 1344-28-1	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard Yes
 Chronic Health Hazard Yes
 Fire Hazard Yes
 Sudden Release of Pressure Hazard No
 Reactive Hazard No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
N-BUTYL ACETATE 123-86-4	5000 lb			X
XYLENE 1330-20-7	100 lb			X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
N-BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ETHYL KETONE 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
STYRENE - 100-42-5	Carcinogen
ETHYLBENZENE - 100-41-4	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		

METHYL N-AMYL KETONE 110-43-0	X	X	X
N-BUTYL ACETATE 123-86-4	X	X	X
METHYL ETHYL KETONE 78-93-3	X	X	X
AMORPHOUS SILICA 7631-86-9		X	X
XYLENE 1330-20-7	X	X	X
ALUMINUM OXIDES 1344-28-1	X	X	X
ZIRCONIUM OXIDE 1314-23-4		X	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X

16. OTHER INFORMATION


NFPA	Health 2	Flammability 3	Instability 1	Physical hazard *
HMIS (Hazardous Material Information System)	Health 2*	Flammability 3	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 02-Mar-2018
 Revision Summary
 5 7 10 8 9 11 14 1 15

Disclaimer
 For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date 18-Jul-2018

Revision Date 18-Jul-2018

Revision Number 14

1. IDENTIFICATION

Product identifier

Product Code F072-0072B
Product Name ENDURA-SHIELD CONVERTER

Other means of identification

Common Name SERIES 72, PART B
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Vapors)	Category 4
Serious eye damage/eye irritation	Category 2B
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Harmful if inhaled
Causes eye irritation
May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause an allergic skin reaction
May cause respiratory irritation. May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
Flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor Slight

Precautionary Statements

Prevention

- Use only outdoors or in a well-ventilated area
- Wash face, hands and any exposed skin thoroughly after handling
- In case of inadequate ventilation wear respiratory protection
- Contaminated work clothing should not be allowed out of the workplace
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Wear protective gloves/protective clothing/eye protection/face protection
- Keep cool

Response

- Get medical advice/attention if you feel unwell
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- If skin irritation or rash occurs: Get medical advice/attention
- Wash contaminated clothing before reuse
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician
- In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

- Store in a well-ventilated place. Keep container tightly closed
- Store locked up
- Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- Toxic to aquatic life with long lasting effects
- SEE SAFETY DATA SHEET
- Contains isocyanates. May produce an allergic reaction
- Acute Toxicity 2.1E-06 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
HEXAMETHYLENE DIISOCYANATE (HDI) POLYMER	28182-81-2	60 - 100%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - <30%
HEXAMETHYLENE DIISOCYANATE (HDI)	822-06-0	0.1 - <1%

MONOMER		
---------	--	--

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
Skin contact	Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Water.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Hydrogen cyanide. Chlorine. Fluorine.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate

ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling**Handling**

Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities**Storage**

Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products

Strong oxidizing agents. Water, alcohols, amines, strong bases, metal components, surface active materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m ³	-	250 mg/m ³
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	TWA: 0.005 ppm	-	

Appropriate engineering controls**Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Slight
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point	No data available	No data available
Boiling point / boiling range	139 °C / 282.0 °F	
Flash point	54 °C / 130.0 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)	No data available	Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.17633	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature	No data available	No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

Other Information

Density	9.81056 lbs/gal
Volatile organic compounds (VOC) content	0 lbs/gal
Total volatiles weight percent	20.88 %
Total volatiles volume percent	18.29 %
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Amines. Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Water, alcohols, amines, strong bases, metal components, surface active materials

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Nitrogen oxides (NOx). Hydrogen cyanide. Chlorine. Fluorine.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	Contains isocyanate monomer. If subject to spray application, engineering and administrative controls must be instituted to maintain an exposure level below .005ppm. If these controls are not adequate, the use of an air-supplied respirator is mandatory. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May cause sensitization of susceptible persons.
Eye contact	Causes serious eye irritation.
Skin contact	Irritating to skin. May cause sensitization of susceptible persons.
Ingestion	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
HEXAMETHYLENE DIISOCYANATE (HDI) POLYMER 28182-81-2	-	-	= 18500 mg/m ³ (Rat) 1 h
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	= 738 mg/kg (Rat)	= 593 mg/kg (Rabbit)	= 0.06 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Skin disorders. Respiratory disorders. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity	Avoid repeated exposure. Contains isocyanates. May produce an allergic reaction.
Sensitization	May cause sensitization of susceptible persons.
Mutagenicity	No information available.
Carcinogenicity	There are no known carcinogenic chemicals in this product.
Reproductive effects	No information available.
STOT - single exposure	Skin, Eyes, Central Nervous System (CNS)
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure
Target organ effects	Skin, Eyes, Central nervous system, kidney, liver.
Aspiration hazard	Not applicable.
Acute Toxicity	2.1E-06 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

78.56586 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0		26.1: 96 h Brachydanio rerio mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7

Other Adverse Effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name paint in oil

Additional information Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical

or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER - 822-06-0	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

California Prop. 65

None of the ingredients are listed with California Proposition 65.

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		
HEXAMETHYLENE DIISOCYANATE (HDI) MONOMER 822-06-0	X	X	

16. OTHER INFORMATION

NFPA	Health 2	Flammability 2	Instability 1	Physical hazard *
HMIS (Hazardous Material Information System)	Health 2*	Flammability 2	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 18-Jul-2018
 Revision Summary
 9 4 5 7 10 8 11 14 15 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS