



# Safety Data Sheet

Issue Date 26-Jun-2015

Revision Date 26-Jun-2015

Revision Number 7

## 1. IDENTIFICATION

### Product identifier

**Product Code** F094-0H20  
**Product Name** HYDRO-ZINC GREENISH GRAY

### Other means of identification

**Common Name** SERIES 94-H20  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address**  
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

### **Danger**

### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May cause cancer  
May cause damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 In case of inadequate ventilation wear respiratory protection  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing  
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).  
 Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs  
 Inhalation of metallic zinc dust may result in symptoms known as metal fume fever. Symptoms include chills, fever, muscular pain, nausea and vomiting  
 SEE SAFETY DATA SHEET  
 Acute Toxicity 15.94173 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
-----------	--------	----------

ZINC (TOTAL DUST)	7440-66-6	60 - 100%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - 30%
DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER	-	1 - 10%
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	101-68-8	1 - 10%
ZINC OXIDE (TOTAL DUST)	1314-13-2	1 - 10%
XYLENE	1330-20-7	1 - 10%
YELLOW IRON OXIDE	51274-00-1	1 - 10%
POLYMERIC MDI	9016-87-9	1 - 10%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.1 - 1%
ETHYL BENZENE	100-41-4	0.1 - 1%
P-TOLUENESULFONYL ISOCYANATE	4083-64-1	0.1 - 1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.
<b><u>Most important symptoms and effects, both acute and delayed</u></b>	
<b>Notes to physician</b>	Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### **Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### **Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Chlorine. Fluorine. Hydrogen cyanide. Sulfur oxides. Zinc oxide fume.

##### **Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

### Environmental Precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### Methods and material for containment and cleaning up

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** **Use only with adequate ventilation.** Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Strong oxidizing agents. Water, alcohols, amines, strong bases, metal components, surface active materials. Acids. Product may release hydrogen.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER 101-68-8	TWA: 0.005 ppm	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m <sup>3</sup>	75 mg/m <sup>3</sup>
ZINC OXIDE (TOTAL DUST) 1314-13-2	TWA: 2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	500 mg/m <sup>3</sup>
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 15 mg/m <sup>3</sup> TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	

CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	800 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Slight
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	138 °C / 280.0 °F		
<b>Flash point</b>	28 °C / 82.0 °F		
<b>Evaporation rate</b>		Pensky Martens - Closed Cup	
<b>Flammability (solid, gas)</b>		No data available	
<b>Flammability Limit in Air</b>		No information available	
<b>Upper flammability limit</b>	N/A	No data available	
<b>Lower flammability limit</b>	1.0		
<b>Vapor pressure</b>		No data available	

Vapor density		No data available
Specific gravity	2.98751	g/cm <sup>3</sup>
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	550 centipoises	approx

**Other Information**

Density	24.9158 lbs/gal
Volatile organic compounds (VOC) content	0.74392 lbs/gal
Total volatiles weight percent	15.75 %
Total volatiles volume percent	37.76 %

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Amines.

**Incompatible materials**

Strong oxidizing agents, Water, alcohols, amines, strong bases, metal components, surface active materials, Acids, Product may release hydrogen

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Oxides of nitrogen. Hydrogen cyanide. Sulfur oxides. Zinc oxide fume. Chlorine. Fluorine.

## 11. TOXICOLOGICAL INFORMATION

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Contains isocyanate monomer. If subject to spray application, engineering and administrative controls must be instituted to maintain an exposure level below .005ppm. If these controls are not adequate, the use of an air-supplied respirator is mandatory. May cause sensitization of susceptible persons. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
<b>Eye contact</b>	Severely irritating to eyes.
<b>Skin contact</b>	Irritating to skin. May cause sensitization by skin contact.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h

DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER			490 mg/m <sup>3</sup> , 4h (rat)
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER 101-68-8	= 31600 mg/kg ( Rat ) = 9200 mg/kg ( Rat )		= 369 mg/m <sup>3</sup> ( Rat ) 4 h
ZINC OXIDE (TOTAL DUST) 1314-13-2	> 5000 mg/kg ( Rat )		
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
POLYMERIC MDI 9016-87-9	= 49 g/kg ( Rat )	> 9400 mg/kg ( Rabbit )	= 490 mg/m <sup>3</sup> ( Rat ) 4 h
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg ( Rat )		
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
P-TOLUENESULFONYL ISOCYANATE 4083-64-1	= 2234 mg/kg ( Rat )		> 640 ppm ( Rat ) 1 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Respiratory disorders. Irritating to eyes and skin.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

**Sensitization** May cause sensitization of susceptible persons.

**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER 101-68-8		Group 3		
XYLENE 1330-20-7		Group 3		
POLYMERIC MDI 9016-87-9		Group 3		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
ETHYL BENZENE 100-41-4	A3	Group 2B		X

**Reproductive effects** No information available.  
**STOT - single exposure** No information available  
**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure  
**Target organ effects** Central nervous system, Gastrointestinal tract, Eyes, liver, Lungs, respiratory system, Skin, blood, kidney.

**Aspiration hazard** No information available.

**Acute Toxicity** 15.94173 % of the mixture consists of ingredient(s) of unknown toxicity.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

27.51052912 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
-----------	-------------------	------------------	---------------------

ZINC (TOTAL DUST) 7440-66-6	0.11 - 0.271: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 0.09 - 0.125: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	30: 96 h Cyprinus carpio mg/L LC50 7.8: 96 h Cyprinus carpio mg/L LC50 static 0.24: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.59: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 2.66: 96 h Pimephales promelas mg/L LC50 static 3.5: 96 h Lepomis macrochirus mg/L LC50 static 0.45: 96 h Cyprinus carpio mg/L LC50 semi-static 0.41: 96 h Oncorhynchus mykiss mg/L LC50 static 2.16 - 3.05: 96 h Pimephales promelas mg/L LC50 flow-through 0.211 - 0.269: 96 h Pimephales promelas mg/L LC50 semi-static	0.139 - 0.908: 48 h Daphnia magna mg/L EC50 Static
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
YELLOW IRON OXIDE 51274-00-1		EC50: > 1,000 mg/l (Golden orfe (Leuciscus idus), 48 h)	
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
XYLENE 1330-20-7	2.77
ETHYL BENZENE 100-41-4	3.118

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS**



**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
ZINC (TOTAL DUST) 7440-66-6	Ignitable Toxic
ZINC OXIDE (TOTAL DUST) 1314-13-2	Toxic
XYLENE 1330-20-7	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID no.** 1263  
**Proper Shipping Name** paint  
**Hazard Class** 3  
**Packing Group** III  
**Emergency Response Guide Number** 128

**IATA**

**UN/ID no.** 1263  
**Proper Shipping Name** paint  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 366

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Does not comply  
**ENCS** Does not comply  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Does not comply  
**AICS** Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	
XYLENE	
ETHYL BENZENE	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
ZINC (TOTAL DUST) - 7440-66-6	1.0
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER - 101-68-8	1.0
ZINC OXIDE (TOTAL DUST) - 1314-13-2	1.0
XYLENE - 1330-20-7	1.0
POLYMERIC MDI - 9016-87-9	1.0
ETHYL BENZENE - 100-41-4	0.1

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC (TOTAL DUST) 7440-66-6		X	X	
ZINC OXIDE (TOTAL DUST) 1314-13-2		X		
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
ZINC (TOTAL DUST) 7440-66-6	1000 lb		RQ 454 kg final RQ RQ 1000 lb final RQ
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER 101-68-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
ZINC (TOTAL DUST) 7440-66-6	X	X	X
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		X
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER 101-68-8	X	X	X
ZINC OXIDE (TOTAL DUST) 1314-13-2	X	X	X
XYLENE 1330-20-7	X	X	X
POLYMERIC MDI 9016-87-9	X		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 3 Flammability 3 Instability 2 Physical hazard \*  
**HMIS (Hazardous Material Information System)** Health 3\* Flammability 3 Reactivity 2

Prepared By Tnemec Regulatory Dept: 816-474-3400  
 Revision Date 26-Jun-2015

Revision Summary  
 9 4 5 7 10 8 11 14

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**