



Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code F090E0092A
Trade Name TNE ME-ZINC YELLOW
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

DANGER!

FLAMMABLE LIQUID AND VAPOR.
POISON, MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED
HARMFUL IF INHALED.
MAY BE HARMFUL IF ABSORBED THROUGH SKIN.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes Severe irritation.
Skin Irritating to skin.
Inhalation Irritating to respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Ingestion May be harmful if swallowed.

Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Gastrointestinal tract. Kidney disorders. Liver disorders. Skin disorders.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Blood, Central nervous system, Gastrointestinal tract, Eyes, Kidney, Liver, Lungs, Reproductive System, Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
ETHANOL	64-17-5	42.2907
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	16.3795
ETHYL SILICATE	78-10-4	5 - 10
MICA (RESPIRABLE DUST)	12001-26-2	5 - 10
IRON OXIDE FUME	1309-37-1	1 - 5
METHANOL (SKIN)	67-56-1	2.3893
ETHYL ACETATE	141-78-6	1.8363
TRIMETHYL BORATE	121-43-7	1 - 5

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Flammable.
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical

Hazardous Decomposition Products Oxides of carbon, hydrocarbons.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
ETHANOL	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³	TWA: 1000 ppm TWA: 1880 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³
ETHYL SILICATE	TWA: 10 ppm	TWA: 85 mg/m ³ TWA: 10 ppm TWA: 100 ppm TWA: 850 mg/m ³	TWA: 10 ppm TWA: 85 mg/m ³	TWA: 85 mg/m ³ TWA: 10 ppm	TWA: 10 ppm TWA: 85 mg/m ³ STEL: 30 ppm STEL: 255 mg/m ³
MICA (RESPIRABLE DUST)	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³
IRON OXIDE FUME	TWA: 1 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³	TWA: 1 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 1 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³ STEL: 2 mg/m ³
METHANOL (SKIN)	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm Skin	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 328 mg/m ³ STEL: 250 ppm Skin	TWA: 260 mg/m ³ TWA: 200 ppm STEL: 325 mg/m ³ STEL: 250 ppm Skin	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 310 mg/m ³ STEL: 250 ppm
ETHYL ACETATE	TWA: 400 ppm	TWA: 1400 mg/m ³ TWA: 400 ppm	TWA: 1440 mg/m ³ TWA: 400 ppm	TWA: 1440 mg/m ³ TWA: 400 ppm	TWA: 1400 mg/m ³ TWA: 400 ppm

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

If splashes are likely to occur, wear Goggles.

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point

12°C / 53.0°F

Method

Pensky Martens - Closed Cup

Boiling Point/Range

64 - 81°C / 147.0 - 178.0°F

Upper Exposure Limits

No information available

Lower Exposure Limits

No information available

Evaporation Rate

No information available

Vapour Pressure

No information available

Vapour Density

No information available

9. PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity	1.06388
Density	8.85311
VOC Content (lbs/gal)	5.063
% Volatile by Weight	58.0330
% Volatile by Volume	75.5451

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks. Contact with water liberates toxic gas (methanol).
Incompatible Products	Strong oxidizing agents. Acids. Alkalines. Amines. Nitrates. Hypochlorites. Boric Acid.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ETHANOL	7060 mg/kg (Rat)		
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg (Rat)		
ETHYL SILICATE	6270 mg/kg (Rat)	6300 µL/kg (Rabbit)	
IRON OXIDE FUME	10000 mg/kg (Rat)		
METHANOL (SKIN)	5628 mg/kg (Rat)	15800 mg/kg (Rabbit)	64000 ppm (Rat) 4 h 83.2 mg/L (Rat) 4 h
ETHYL ACETATE	5620 mg/kg (Rat)	20 mL/kg (Rabbit) 18000 mg/kg (Rabbit)	
TRIMETHYL BORATE	6140 mg/kg (Rat)	1980 µL/kg (Rabbit)	

Irritation	No information available
Corrosivity	No information available
Sensitization	No information available

Chronic Toxicity

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
ETHANOL	A3	Group 1		X	
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	

Mutagenic Effects	No information available
Reproductive Effects	No information available
Developmental Effects	No information available
Teratogenicity	No information available
Target Organ Effects	Blood, Central nervous system, Gastrointestinal tract, Eyes, Kidney, Liver, Lungs, Reproductive System, Respiratory system, Skin.
Endocrine Disruptor Information	No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
ETHANOL		LC50= 12900 mg/L Oncorhynchus mykiss 96 h LC50= 14.2 mg/L Pimephales promelas 96 h	EC50 = 35470 mg/L 5 min EC50 = 34634 mg/L 30 min	EC50 = 9268 mg/L 48 h EC50 = 10800 mg/L 24 h
METHANOL (SKIN)		LC50= 28100 mg/L Pimephales promelas 96 h LC50= 13200 mg/L Oncorhynchus mykiss 96 h	EC50 = 43000 mg/L 5 min EC50 = 40000 mg/L 15 min EC50 = 39000 mg/L 25 min	
ETHYL ACETATE	EC50 = 3300 mg/L 48 h	LC50= 230 mg/L Pimephales promelas 96 h LC50= 484 mg/L Oncorhynchus mykiss 96 h	EC50 = 1180 mg/L 5 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h EC50 = 1500 mg/L 15 min	EC50 = 717 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging

Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name UN1263,PAINT,3,PGIII,ERG 128

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Complies
ENCS	Does not Comply
KECL	Complies
PICCS	Complies
AICS	Complies

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Component
METHANOL (SKIN)

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
-----------	--------	----------	-----------------------------

METHANOL (SKIN)	67-56-1	2.3893	1.0
-----------------	---------	--------	-----

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	Yes
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
METHANOL (SKIN)	5000 lb	
ETHYL ACETATE	5000 lb	

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
ETHANOL	64-17-5	Carcinogen Developmental
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ETHANOL	X	X	X		X
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
ETHYL SILICATE	X	X	X		X
MICA (RESPIRABLE DUST)	X	X	X		X
IRON OXIDE FUME	X	X	X		X
METHANOL (SKIN)	X	X	X	X	X
ETHYL ACETATE	X	X	X		X
TRIMETHYL BORATE	X	X	X		

Other International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid
D2A Very toxic materials



Component	NPRI
ETHANOL	Part 5 Substance
METHANOL (SKIN)	Part 1, Group 1 Substance; Part 5 Substance
ETHYL ACETATE	Part 5 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 29-Dec-2009**Revision Summary** No information available**HMIS** **Health 2** **Flammability 3** **Reactivity 1****Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS



Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code	F090E0092B
Trade Name	TNEME-ZINC GRAY
Contact Manufacturer	TNEMEC Company, Inc. 123 West 23rd Avenue North Kansas City, MO 64116-3064 816-474-3400
Emergency Telephone Number	800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

HARMFUL BY INHALATION.
MAY CAUSE HEADACHE AND DIZZINESS.
MAY CAUSE FLU-LIKE SYMPTOMS.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Principle Routes of Exposure Inhalation

Acute Effects

Eyes

May cause slight irritation

Skin

Substance may cause slight skin irritation

Inhalation

May cause irritation of respiratory tract. Inhalation of metallic zinc dust may result in symptoms known as metal fume fever. Symptoms include chills, fever, muscular pain, nausea and vomiting.

Ingestion

Gastrointestinal discomfort.

Chronic Effects

Avoid repeated exposure

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions No information available

Interactions with Other Chemicals No information available

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Respiratory system

3. COMPOSITION/INFORMATION ON INGREDIENTS

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
ZINC (TOTAL DUST)	7440-66-6	60 - 100
ZINC OXIDE (TOTAL DUST)	1314-13-2	1 - 5

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	No information available
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Do NOT use water jet. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical

Hazardous Decomposition Products Zinc oxide fume.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	Shovel or sweep up.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Tightly fitting safety goggles. Wear protective gloves/clothing. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. Keep in a dry place. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)

ZINC OXIDE (TOTAL DUST)	TWA: 2 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³ STEL: 10 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 2 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³ STEL: 10 mg/m ³
-------------------------	---	---	---	---	---

Engineering Measures	Ensure adequate ventilation, especially in confined areas
Personal Protective Equipment	
Skin Protection	Lightweight protective clothing, Apron, Impervious gloves
Eye/face Protection	Tightly fitting safety goggles
Respiratory Protection	Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	Not applicable
Method	Pensky Martens - Closed Cup
Boiling Point/Range	No information available
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	7.06595
Density	58.79932
VOC Content (lbs/gal)	.000
% Volatile by Weight	.0000
% Volatile by Volume	.0000

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks.
Incompatible Products	Strong oxidizing agents. Bases. Acids. Water. Product may release hydrogen.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ZINC OXIDE (TOTAL DUST)	5000 mg/kg (Rat)		

Irritation	No information available
Corrosivity	No information available
Sensitization	No information available

Chronic Toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Mutagenic Effects No information available
Reproductive Effects No information available
Developmental Effects No information available
Teratogenicity No information available
Target Organ Effects Respiratory system.
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
ZINC (TOTAL DUST)	EC50 = 30 µg/L 96 h	LC50= 6.4 mg/L Pimephales promelas 96 h		EC50 = 5 µg/L 72 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name ZINC DUST

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
CHINA Complies
ENCS Does not Comply
KECL Complies
PICCS Complies
AICS Complies

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
ZINC (TOTAL DUST)	7440-66-6	60 - 100	1.0
ZINC OXIDE (TOTAL DUST)	1314-13-2	1 - 5	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard No
 Acute Health Hazard No
 Fire Hazard No
 Sudden Release of Pressure Hazard No
 Reactive Hazard No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC (TOTAL DUST)		X	X	
ZINC OXIDE (TOTAL DUST)		X		

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
ZINC (TOTAL DUST)	1000 lb	

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ZINC (TOTAL DUST)	X	X	X		X
ZINC OXIDE (TOTAL DUST)	X	X	X		X

Other International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B6 Reactive flammable material



Component	NPRI
ZINC (TOTAL DUST)	Part 1, Group 1 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 29-Dec-2009

Revision Summary: No information available

HMIS Health 2 Flammability 1 Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS