

Safety Data Sheet

Issue Date 29-Aug-2018

Revision Date 30-Mar-2015

Revision Number 5

1. IDENTIFICATION

Product identifier

Product Code FC20-00WHA
Product Name POTA-POX FC TNEMEC WHITE

Other means of identification

Common Name SERIES FC20, PART A
UN/ID no. 1263
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
Suspected of causing cancer

Suspected of damaging fertility or the unborn child
 May cause respiratory irritation. May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor aromatic

Precautionary Statements

Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool
 Use explosion-proof electrical/ventilating/lighting/equipment

Response

IF exposed or concerned: Get medical advice/attention
 specific treatment
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Rinse mouth
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

Harmful to aquatic life with long lasting effects
 SEE SAFETY DATA SHEET

Acute Toxicity

14.85471 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	10 - <30%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - <30%
TALC (RESPIRABLE DUST)	14807-96-6	10 - <30%
XYLENE	1330-20-7	1 - <10%
N-BUTANOL (SKIN)	71-36-3	1 - <10%
MODIFIED ALIPHATIC AMINE	90-72-2	1 - <10%
ETHYLBENZENE	100-41-4	1 - <10%
AMORPHOUS SILICA	7631-86-9	1 - <10%
ETHYL BENZENE	100-41-4	1 - <10%
TRIETHYLENE TETRAMINE	112-24-3	0.1 - <1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - <1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Nitrogen oxides (NOx). Aldehydes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep away from heat, sparks and flame. Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Epoxy constituents. Strong oxidizing agents. Acids. Cleaning solutions such as Chromerge and Aqua Regia. Water, alcohols, amines, strong bases, metal components, surface active materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	

N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m ³ TWA: 100 ppm TWA: 300 mg/m ³	1400 ppm
ETHYLBENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	800 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m ³	3000 mg/m ³
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	800 ppm
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

Appropriate engineering controls

Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Goggles If splashes are likely to occur, wear face-shield. Use chemical resistant splash type goggles.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	aromatic
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		
Melting point / freezing point	No data available	
Boiling point / boiling range	116 °C / 241.0 °F	
Flash point	28 °C / 82.0 °F	Pensky Martens - Closed Cup
Evaporation rate		
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit	N/A	

Lower flammability limit	1.0	
Vapor pressure		
Vapor density		
Specific gravity	1.65669	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		
Partition coefficient: n-octanol/water		
Autoignition temperature	No data available	
Decomposition temperature		
Kinematic viscosity		
Dynamic viscosity	1000 centipoises	approx

Other Information

Density	13.81681 lbs/gal
Volatile organic compounds (VOC) content	2.96371 lbs/gal
Total volatiles weight percent	21.45 %
Total volatiles volume percent	42.2 %
Bulk density	No information available

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Epoxy constituents.

Incompatible materials

Epoxy constituents, Strong oxidizing agents, Acids, Cleaning solutions such as Chromerge and Aqua Regia, Water, alcohols, amines, strong bases, metal components, surface active materials

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Nitrogen oxides (NOx). Hydrocarbons. Aldehydes.

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure**

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Corrosive to the eyes and may cause severe damage including blindness.
Skin contact	Irritating to skin.
Ingestion	Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
BARIUM SULFATE (TOTAL DUST) 7727-43-7	= 307000 mg/kg (Rat)	-	-
TITANIUM DIOXIDE (TOTAL DUST)	> 10000 mg/kg (Rat)	-	-

13463-67-7			
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg (Rat) = 790 mg/kg (Rat)	= 3400 mg/kg (Rabbit) = 3402 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
MODIFIED ALIPHATIC AMINE 90-72-2	= 1200 mg/kg (Rat)	= 1280 mg/kg (Rat)	-
ETHYLBENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
AMORPHOUS SILICA 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
TRIETHYLENE TETRAMINE 112-24-3	= 2500 mg/kg (Rat)	= 550 mg/kg (Rabbit)	-
BENZENE, 1,3-DIMETHYL 108-38-3	= 5 g/kg (Rat)	= 12.18 g/kg (Rabbit) = 14100 µL/kg (Rabbit)	= 5984 ppm (Rat) 6 h

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Corrosivity Corrosive to the eyes and may cause severe damage including blindness. May be corrosive to metals.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B	-	X
TALC (RESPIRABLE DUST) 14807-96-6		Group 2B Group 3	-	
XYLENE 1330-20-7		Group 3	-	
ETHYLBENZENE 100-41-4	A3	Group 2B	-	X
AMORPHOUS SILICA 7631-86-9		Group 1 Group 3	Known	
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3	-	

Reproductive effects Suspected of damaging fertility or the unborn child.
STOT - single exposure Skin, Eyes, Central Nervous System (CNS)
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Target organ effects Central nervous system, Central Vascular System (CVS), Eyes, Lungs, respiratory system, Skin, blood, Gastrointestinal tract, kidney, liver.

Aspiration hazard Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

Acute Toxicity 14.85471 % of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document .

12. ECOLOGICAL INFORMATION

Ecotoxicity

16.72980667 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST)		100: 96 h Brachydanio rerio g/L	

14807-96-6		LC50 semi-static	
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
N-BUTANOL (SKIN) 71-36-3	500: 72 h Desmodemus subspicatus mg/L EC50 500: 96 h Desmodemus subspicatus mg/L EC50	1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
ETHYLBENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
TRIETHYLENE TETRAMINE 112-24-3	2.5: 72 h Desmodemus subspicatus mg/L EC50 20: 72 h Pseudokirchneriella subcapitata mg/L EC50 3.7: 96 h Pseudokirchneriella subcapitata mg/L EC50	570: 96 h Poecilia reticulata mg/L LC50 semi-static 495: 96 h Pimephales promelas mg/L LC50	31.1: 48 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
XYLENE 1330-20-7	2.77

N-BUTANOL (SKIN) 71-36-3	0.785
MODIFIED ALIPHATIC AMINE 90-72-2	0.219
ETHYLBENZENE 100-41-4	3.2
ETHYL BENZENE 100-41-4	3.118
TRIETHYLENE TETRAMINE 112-24-3	-1.4
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

Other Adverse Effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
ETHYLBENZENE 100-41-4		Included in waste stream: F039		
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Chemical name	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
N-BUTANOL (SKIN) 71-36-3	Toxic
ETHYLBENZENE 100-41-4	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no. 1263
Proper Shipping Name PAINT
Hazard Class 3
Packing Group III
Emergency Response Guide Number 128

Additional information Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does Not Comply
ENCS	Does Not Comply
IECSC	Complies
KECL	Does Not Comply
PICCS	Does Not Comply
AICS	Does Not Comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
XYLENE	
ETHYLBENZENE	
ETHYL BENZENE	
BENZENE, 1,3-DIMETHYL	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0
XYLENE - 1330-20-7	1.0
N-BUTANOL (SKIN) - 71-36-3	1.0
ETHYLBENZENE - 100-41-4	0.1
ETHYL BENZENE - 100-41-4	0.1
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYLBENZENE 100-41-4	1000 lb	X	X	X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3				X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYLBENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical name	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
ETHYLBENZENE - 100-41-4	Carcinogen
AMORPHOUS SILICA - 7631-86-9	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen
BENZENE, 1,3-DIMETHYL - 108-38-3	*
BENZENE, 1,4-DIMETHYL - 106-42-3	*
BENZENE, 1,2-DIMETHYL - 95-47-6	*

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
XYLENE 1330-20-7	X	X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
ETHYLBENZENE 100-41-4	X	X	X
AMORPHOUS SILICA 7631-86-9		X	X
ETHYL BENZENE 100-41-4	X	X	X
TRIETHYLENE TETRAMINE 112-24-3	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

16. OTHER INFORMATION

NFPA Health 2 Flammability 3 Instability 1 Physical hazard *
HMIS (Hazardous Material Information System) Health 2* Flammability 3 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 30-Mar-2015
 Revision Summary 9 1 4 5 7 10 8 11 14


Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot

guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date 28-Aug-2018

Revision Date 09-Aug-2017

Revision Number 15

1. IDENTIFICATION

Product identifier

Product Code B020-0020B
Product Name F020/FC20 CONVERTER

Other means of identification

Common Name SERIES 20/FC20, PART B
UN/ID no. 1263
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372 816-474-3400
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203, Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
May damage fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure
Highly flammable liquid and vapor



Appearance opaque

Physical state liquid

Odor aromatic

Precautionary Statements

Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/mixing/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge

Response

- IF exposed or concerned: Get medical advice/attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- If skin irritation or rash occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

- Store locked up
- Store in a well-ventilated place. Keep cool
- Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

Toxic to aquatic life with long lasting effects
SEE SAFETY DATA SHEET

Acute Toxicity 0.6621 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
TALC (RESPIRABLE DUST)	14807-96-6	30 - <60%
SOLID EPOXY RESIN	-	10 - <30%
METHYL ISOBUTYL KETONE	108-10-1	10 - <30%
EPOXY RESIN (LER)	25085-99-8	10 - <30%
XYLENE	1330-20-7	1 - <10%
ETHYL BENZENE	100-41-4	1 - <10%
BENZENE, 1,4-DIMETHYL	106-42-3	0.1 - <1%

PROPRIETARY	-	0.1 - <1%
HYDROGENATED LIGHT DISTILLATE	64742-47-8	0.1 - <1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - <1%
MAGNESITE	546-93-0	0.1 - <1%
BENZENE, 1,2-DIMETHYL	95-47-6	0.1 - <1%
UREA RESIN	-	0.1 - <1%
CALCIUM MAGNESIUM CARBONATE	-	0.1 - <1%
CHLORITE	1318-59-8	0.1 - <1%
N-BUTANOL (SKIN)	71-36-3	0.1 - <1%
FORMALDEHYDE	50-00-0	0 - <0.1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Water.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all

sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep away from heat, sparks and flame. Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Amines. Strong oxidizing agents. Bases. Acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³ TWA: 100 ppm TWA: 410 mg/m ³	500 ppm
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	800 ppm
BENZENE, 1,4-DIMETHYL 106-42-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm
BENZENE, 1,3-DIMETHYL	TWA: 100 ppm	-	900 ppm

108-38-3	STEL: 150 ppm		
BENZENE, 1,2-DIMETHYL 95-47-6	TWA: 100 ppm STEL: 150 ppm	-	900 ppm
N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m ³ TWA: 100 ppm TWA: 300 mg/m ³	1400 ppm
FORMALDEHYDE 50-00-0	TWA: 0.1 ppm STEL: 0.3 ppm	TWA: 3 ppm STEL: 10 ppm Ceiling: 5 ppm TWA: 0.75 ppm STEL: 2 ppm	20 ppm

NIOSH IDLH: Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	aromatic
Appearance	opaque	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		
Melting point / freezing point	No data available	
Boiling point / boiling range	72 °C / 162 °F	
Flash point	18 °C / 64.0 °F	Pensky Martens - Closed Cup
Evaporation rate		
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit	N/A	
Lower flammability limit	1.0	
Vapor pressure		
Vapor density		
Specific gravity	1.28259	g/cm ³
Water solubility	Insoluble in cold water	
Solubility in other solvents		

Partition coefficient: n-octanol/water
Autoignition temperature No data available
Decomposition temperature
Kinematic viscosity
Dynamic viscosity 550 centipoises

Other Information

Density 10.67306 lbs/gal
Volatile organic compounds (VOC) content 2.895 lbs/gal
Total volatiles weight percent 27.1240 %
Total volatiles volume percent 42.0115 %
Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Amines.

Incompatible materials

Amines, Strong oxidizing agents, Bases, Acids

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact Severely irritating to eyes.
Skin contact Irritating to skin. May cause sensitization of susceptible persons.
Ingestion Harmful if swallowed.

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
BENZENE, 1,4-DIMETHYL 106-42-3	= 4029 mg/kg (Rat)	-	= 4550 ppm (Rat) 4 h = 4740 ppm (Rat) 4 h
HYDROGENATED LIGHT DISTILLATE 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
BENZENE, 1,3-DIMETHYL	= 5 g/kg (Rat)	= 12.18 g/kg (Rabbit) = 14100	= 5984 ppm (Rat) 6 h

108-38-3		$\mu\text{L/kg}$ (Rabbit)	
BENZENE, 1,2-DIMETHYL 95-47-6	= 3608 mg/kg (Rat)	= 14100 mg/kg (Rabbit)	= 4330 ppm (Rat) 6 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg (Rat) = 790 mg/kg (Rat)	= 3400 mg/kg (Rabbit) = 3402 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
FORMALDEHYDE 50-00-0	= 100 mg/kg (Rat)	= 270 mg/kg (Rabbit)	= 0.578 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TALC (RESPIRABLE DUST) 14807-96-6		Group 2B Group 3	-	
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	-	X
XYLENE 1330-20-7		Group 3	-	
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
BENZENE, 1,4-DIMETHYL 106-42-3		Group 3	-	
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3	-	
BENZENE, 1,2-DIMETHYL 95-47-6		Group 3	-	
FORMALDEHYDE 50-00-0	A1	Group 1	Known	X

Reproductive effects May damage fertility or the unborn child.

STOT - single exposure No information available

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Target organ effects Central nervous system, Central Vascular System (CVS), Eyes, kidney, liver, respiratory system, Skin, blood, Gastrointestinal tract.

Aspiration hazard Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

Acute Toxicity 0.6621 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

28.1846 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
EPOXY RESIN (LER) 25085-99-8	11 mg/L 72 hr	2 mg/L 96 hr Oncorhynchus mykiss	1.8 mg/L 48h
XYLENE		LC50= 13.4 mg/L Pimephales	EC50 = 3.82 mg/L 48 h LC50 = 0.6

1330-20-7		promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	mg/L 48 h
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
BENZENE, 1,4-DIMETHYL 106-42-3	105.1: 3 h Chlorella vulgaris mg/L EC50 3.2: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	7.2 - 9.9: 96 h Pimephales promelas mg/L LC50 static 2.6: 96 h Oncorhynchus mykiss mg/L LC50 8.8: 96 h Poecilia reticulata mg/L LC50 semi-static 2.6: 96 h Oncorhynchus mykiss mg/L LC50 static	3.55 - 6.31: 48 h Daphnia magna mg/L EC50 Static
HYDROGENATED LIGHT DISTILLATE 64742-47-8		2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through	4720: 96 h Den-dronereides heteropoda mg/L LC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static
BENZENE, 1,2-DIMETHYL 95-47-6	4.2: 192 h Pseudokirchneriella subcapitata mg/L EC50 4.7: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	11.6 - 22.4: 96 h Pimephales promelas mg/L LC50 flow-through 11.6 - 22.4: 96 h Lepomis macrochirus mg/L LC50 flow-through 5.59 - 11.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 12: 96 h Poecilia reticulata mg/L LC50	2.61 - 5.59: 48 h Daphnia magna mg/L EC50 Flow through 3.2: 48 h Daphnia magna mg/L EC50 0.78 - 2.51: 48 h Daphnia magna mg/L EC50 Static
N-BUTANOL (SKIN) 71-36-3	500: 72 h Desmodesmus subspicatus mg/L EC50 500: 96 h Desmodesmus subspicatus mg/L EC50	1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
FORMALDEHYDE 50-00-0		22.6 - 25.7: 96 h Pimephales promelas mg/L LC50 flow-through 23.2 - 29.7: 96 h Pimephales promelas mg/L LC50 static 41: 96 h Brachydanio rerio mg/L LC50 static 0.032 - 0.226: 96 h Oncorhynchus mykiss mL/L LC50 flow-through 1510: 96 h Lepomis macrochirus µg/L LC50 static 100 - 136: 96 h Oncorhynchus mykiss mg/L LC50 static	2: 48 h Daphnia magna mg/L LC50 11.3 - 18: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Chemical name	log Pow
METHYL ISOBUTYL KETONE 108-10-1	1.19
EPOXY RESIN (LER) 25085-99-8	3
XYLENE 1330-20-7	2.77
ETHYL BENZENE 100-41-4	3.118
BENZENE, 1,4-DIMETHYL 106-42-3	3.15
BENZENE, 1,3-DIMETHYL 108-38-3	3.2
BENZENE, 1,2-DIMETHYL 95-47-6	3.12
N-BUTANOL (SKIN) 71-36-3	0.785
FORMALDEHYDE 50-00-0	0.35

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ISOBUTYL KETONE 108-10-1		Included in waste stream: F039		U161
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
FORMALDEHYDE 50-00-0	U122	Included in waste streams: K009, K010, K038, K040, K156, K157		U122

California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical name	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable
N-BUTANOL (SKIN) 71-36-3	Toxic

FORMALDEHYDE 50-00-0	Toxic Ignitable
-------------------------	--------------------

14. TRANSPORT INFORMATION

DOT

UN/ID no. 1263
 Proper Shipping Name PAINT
 Hazard Class 3
 Packing Group II
 Emergency Response Guide Number 128

UN/ID no. 1263
 Proper Shipping Name PAINT
 Hazard Class 3
 Packing Group II
 ERG Code 366

Additional information

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Does Not Comply
 ENCS Does Not Comply
 IECSC Complies
 KECL Complies
 PICCS Complies
 AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Chemical name	HAPS Data
METHYL ISOBUTYL KETONE	
XYLENE	
ETHYL BENZENE	
BENZENE, 1,4-DIMETHYL	
BENZENE, 1,3-DIMETHYL	
BENZENE, 1,2-DIMETHYL	
FORMALDEHYDE	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values
METHYL ISOBUTYL KETONE - 108-10-1	1.0
XYLENE - 1330-20-7	1.0
ETHYL BENZENE - 100-41-4	0.1
BENZENE, 1,4-DIMETHYL - 106-42-3	1.0

BENZENE, 1,3-DIMETHYL - 108-38-3	1.0
BENZENE, 1,2-DIMETHYL - 95-47-6	1.0
N-BUTANOL (SKIN) - 71-36-3	1.0
FORMALDEHYDE - 50-00-0	0.1

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3				X
BENZENE, 1,3-DIMETHYL 108-38-3				X
BENZENE, 1,2-DIMETHYL 95-47-6				X
FORMALDEHYDE 50-00-0	100 lb			X

Chemical name	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,4-DIMETHYL 106-42-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,2-DIMETHYL 95-47-6	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
FORMALDEHYDE 50-00-0	100 lb	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ

California Prop. 65

WARNING: This product can expose you to the following chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical name	California Prop. 65
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental
ETHYL BENZENE - 100-41-4	Carcinogen
BENZENE, 1,3-DIMETHYL - 108-38-3	*
BENZENE, 1,2-DIMETHYL - 95-47-6	*
FORMALDEHYDE - 50-00-0	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Chemical name	New Jersey	Massachusetts	Pennsylvania
TALC (RESPIRABLE DUST)	X	X	X

14807-96-6			
METHYL ISOBUTYL KETONE 108-10-1	X	X	X
XYLENE 1330-20-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X
MAGNESITE 546-93-0	X	X	
BENZENE, 1,2-DIMETHYL 95-47-6	X	X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
FORMALDEHYDE 50-00-0	X	X	X

16. OTHER INFORMATION

NFPA Health 2 Flammability 3 Instability 1 Physical hazard *
HMIS (Hazardous Health 2* Flammability 3 Reactivity 1
Material Information
System)

Prepared By Tnemec Regulatory Dept: 816-474-3400
Revision Date 09-Aug-2017

Revision Summary
 9 1 4 5 7 10 8 11 14 15

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS