



# Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Code** G351-1232A  
**Trade Name** GLASS ARMOR 510 BLUE  
**Contact Manufacturer** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372  
**Emergency Telephone Number** 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

#### WARNING!

HARMFUL IF INHALED.  
HARMFUL OR FATAL IF SWALLOWED.  
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.  
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.  
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT.

#### Potential Health Effects

**Principle Routes of Exposure** Eye contact, Inhalation, Skin contact.

#### Acute Effects

**Eyes**

Irritating to eyes.

**Skin**

Irritating to skin. May cause sensitization by skin contact.

**Inhalation**

Irritating to respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.

**Ingestion**

May be harmful if swallowed.

#### Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** No information available

**Interactions with Other Chemicals** No information available

**Potential Environmental Effects** See Section 12 for additional Ecological information

**Target Organ Effects** Eyes, Lungs, Respiratory system

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous Components

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
BISPHENOL A TYPE EPOXY RESIN	25085-99-8	30 - 60
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	43.7759
d-LIMONENE	5989-27-5	1.0619
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	0.1 - 1

### 4. FIRST AID MEASURES

<b>Eye Contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Inhalation</b>	Move to fresh air. Oxygen or artificial respiration if needed.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Flammable.
<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO <sub>2</sub> ) - Foam - Dry chemical

**Hazardous Decomposition Products** Oxides of carbon, hydrocarbons. Aldehydes.

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

**Protective Equipment and Precautions for Firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
<b>Environmental Precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
<b>Methods for Cleaning Up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Other Information</b>	Not applicable

### 7. HANDLING AND STORAGE

**Handling**

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Storage**

Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
TITANIUM DIOXIDE (TOTAL DUST)	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas

**Personal Protective Equipment****Skin Protection**

Lightweight protective clothing, Apron, Impervious gloves

**Eye/face Protection**

If splashes are likely to occur, wear Goggles.

**Respiratory Protection**

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	Not applicable
Boiling Point/Range	171°C / 339.0°F
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	1.53023
Density	12.73380
VOC Content (lbs/gal)	.208
% Volatile by Weight	1.6290
% Volatile by Volume	2.9635

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable.	<b>Conditions to Avoid</b>	Heat, flames and sparks. Amines.
<b>Incompatible Products</b>	Strong oxidizing agents. Bases. Acids. Amines.	<b>Possibility of Hazardous Reactions</b>	None under normal processing

## 11. TOXICOLOGICAL INFORMATION

**Acute Toxicity**

## 11. TOXICOLOGICAL INFORMATION

### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg ( Rat )		
d-LIMONENE	4400 mg/kg ( Rat )	2000 mg/kg ( Rabbit )	
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg ( Rat )		

<b>Irritation</b>	No information available
<b>Corrosivity</b>	No information available
<b>Sensitization</b>	No information available

### Chronic Toxicity

#### Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	

<b>Mutagenic Effects</b>	No information available
<b>Reproductive Effects</b>	No information available
<b>Developmental Effects</b>	No information available
<b>Teratogenicity</b>	No information available
<b>Target Organ Effects</b>	Eyes, Lungs, Respiratory system.
<b>Endocrine Disruptor Information</b>	No information available

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
BISPHENOL A TYPE EPOXY RESIN	Group III Chemical		

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
d-LIMONENE		LC50= 0.702 mg/L Pimephales promelas 96 h		

## 13. DISPOSAL CONSIDERATIONS

<b>Waste Disposal Methods</b>	Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Contaminated Packaging</b>	Empty containers should be taken for local recycling, recovery or waste disposal

## 14. TRANSPORT INFORMATION

**DOT** Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.  
**Proper Shipping Name** PAINT IN OIL

## 15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Does not Comply
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Does not Comply
AICS	Does not Comply

U.S. Federal RegulationsSARA 313SARA 311/312 Hazardous Categorization

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLAU.S. State RegulationsCalifornia Proposition 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
TITANIUM DIOXIDE (TOTAL DUST)	X	X	X		X

Other International RegulationsCanada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials



Component	NPRI

---

d-LIMONENE	Part 5 Substance
------------	------------------

**Legend**

NPRI - National Pollutant Release Inventory

<b>16. OTHER INFORMATION</b>
------------------------------

**Revision Date:** 29-Dec-2009

**Revision Summary** No information available

**HMIS**                      **Health** 0                      **Flammability** 0                      **Reactivity** 1

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Code** G351-0351B  
**Trade Name** GLASS ARMOR 510 ACTIVATOR  
**Contact Manufacturer** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372  
**Emergency Telephone Number** 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

**DANGER!**

HARMFUL IF INHALED.  
CAUSES SKIN AND EYE BURNS.  
HARMFUL OR FATAL IF SWALLOWED.  
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.  
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.  
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT.

### Potential Health Effects

**Principle Routes of Exposure** Eye contact, Inhalation, Skin contact.

#### Acute Effects

**Eyes**

Causes burns.

**Skin**

Causes burns. May cause sensitization by skin contact.

**Inhalation**

Irritating to respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.

**Ingestion**

May be harmful if swallowed.

#### Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** Central nervous system. Gastrointestinal tract. Kidney disorders. Liver disorders. Skin disorders.

**Interactions with Other Chemicals** Use of alcoholic beverages may enhance toxic effects.

**Potential Environmental Effects** See Section 12 for additional Ecological information

**Target Organ Effects** Blood, Central nervous system, Gastrointestinal tract, Eyes, Kidney, Liver, Lungs, Respiratory system, Skin

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous Components

Component	CAS-No	Weight %
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	49.8522
MODIFIED ALIPHATIC AMINE	90-72-2	1 - 5
DIMETHYLAMINO(METHYL)PHENOL	25338-55-0	1 - 5
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	1 - 5
XYLENE	1330-20-7	1.5363
PHENOL (SKIN)	108-95-2	0.4721
ETHYL BENZENE	100-41-4	0.3787
ALUMINUM OXIDES	1344-28-1	0.1 - 1

### 4. FIRST AID MEASURES

<b>Eye Contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Inhalation</b>	Move to fresh air. Oxygen or artificial respiration if needed.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	No information available
<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO <sub>2</sub> ) - Foam - Dry chemical
<b>Hazardous Decomposition Products</b>	Oxides of carbon, hydrocarbons. Oxides of nitrogen. Aldehydes. Ammonia. Nitric acid, nitrosamine.
<b>Specific Hazards Arising from the Chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.
<b>Protective Equipment and Precautions for Firefighters</b>	Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
<b>Environmental Precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
<b>Methods for Cleaning Up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Other Information</b>	Not applicable

## 7. HANDLING AND STORAGE

### Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Storage

Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
TITANIUM DIOXIDE (TOTAL DUST)	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
XYLENE	TWA: 100 ppm STEL: 150 ppm	TWA: 435 mg/m <sup>3</sup> TWA: 100 ppm STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>	TWA: 434 mg/m <sup>3</sup> TWA: 100 ppm STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 650 mg/m <sup>3</sup>	TWA: 435 mg/m <sup>3</sup> TWA: 100 ppm STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>
PHENOL (SKIN)	TWA: 5 ppm Skin	TWA: 19 mg/m <sup>3</sup> TWA: 5 ppm Skin	TWA: 19 mg/m <sup>3</sup> TWA: 5 ppm Skin	TWA: 5 ppm TWA: 19 mg/m <sup>3</sup> Skin	TWA: 19 mg/m <sup>3</sup> TWA: 5 ppm STEL: 10 ppm STEL: 38 mg/m <sup>3</sup>
ETHYL BENZENE	TWA: 100 ppm STEL: 125 ppm	TWA: 435 mg/m <sup>3</sup> TWA: 100 ppm STEL: 545 mg/m <sup>3</sup> STEL: 125 ppm	TWA: 434 mg/m <sup>3</sup> TWA: 100 ppm STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 540 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
ALUMINUM OXIDES	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>

### Engineering Measures

Ensure adequate ventilation, especially in confined areas

### Personal Protective Equipment

#### Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

#### Eye/face Protection

Goggles. If splashes are likely to occur, wear face-shield.

#### Respiratory Protection

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

### General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Flash Point

Not applicable

### Method

Pensky Martens - Closed Cup

### Boiling Point/Range

138 - 142°C / 280.0 - 288.0°F

### Upper Exposure Limits

No information available

### Lower Exposure Limits

No information available

### Evaporation Rate

No information available

### Vapour Pressure

No information available

### Vapour Density

No information available

### Specific Gravity

1.69740

### Density

14.12491

### VOC Content (lbs/gal)

.322

### % Volatile by Weight

2.2810

## 9. PHYSICAL AND CHEMICAL PROPERTIES

% Volatile by Volume 4.4374

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable.	<b>Conditions to Avoid</b>	Heat, flames and sparks. Epoxy constituents.
<b>Incompatible Products</b>	Strong oxidizing agents. Bases. Acids. Metals . Hypochlorites. Peroxides.	<b>Possibility of Hazardous Reactions</b>	None under normal processing

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg ( Rat )		
MODIFIED ALIPHATIC AMINE	1000 mg/kg ( Rat )	1280 mg/kg ( Rat )	
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg ( Rat )		
XYLENE	4300 mg/kg ( Rat )	1700 mg/kg ( Rabbit )	47635 mg/L ( Rat ) 4 h 5000 ppm ( Rat ) 4 h
PHENOL (SKIN)	317 mg/kg ( Rat )	525 mg/kg ( Rat ) 630 mg/kg ( Rabbit )	316 mg/m <sup>3</sup> ( Rat ) 4 h
ETHYL BENZENE	3500 mg/kg ( Rat )	15354 mg/kg ( Rabbit )	17.2 mg/L ( Rat ) 4 h
ALUMINUM OXIDES	5000 mg/kg ( Rat )		

<b>Irritation</b>	No information available
<b>Corrosivity</b>	No information available
<b>Sensitization</b>	No information available

### Chronic Toxicity

#### Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	
ETHYL BENZENE	A3	Group 2B		X	

<b>Mutagenic Effects</b>	No information available
<b>Reproductive Effects</b>	No information available
<b>Developmental Effects</b>	No information available
<b>Teratogenicity</b>	No information available
<b>Target Organ Effects</b>	Blood, Central nervous system, Gastrointestinal tract, Eyes, Kidney, Liver, Lungs, Respiratory system, Skin.
<b>Endocrine Disruptor Information</b>	No information available

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
XYLENE		LC50= 13.4 mg/L Pimephales promelas 96 h LC50= 8.05 mg/L Oncorhynchus mykiss 96 h LC50= 16.1 mg/L Lepomis macrochirus 96 h LC50= 26.7 mg/L Pimephales promelas 96 h	EC50 = 0.0084 mg/L 24 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
PHENOL (SKIN)	EC50 = 150 mg/L 96 h	LC50= 24 mg/L Pimephales promelas 96 h LC50= 8.9 mg/L Oncorhynchus mykiss 96 h LC50= 23.88 mg/L Lepomis macrochirus 96 h LC50 5 - 12 mg/L Oncorhynchus mykiss 96 h LC50= 40 mg/L Poecilia reticulata 96 h LC50= 27.8 mg/L Brachydanio rerio 96 h	EC50 = 28.8 mg/L 5 min EC50 = 31.6 mg/L 15 min EC50 = 23.28 mg/L 5 min EC50 = 25.61 mg/L 15 min EC50 21 - 36 mg/L 30 min	EC50 = 23.0 mg/L 48 h LC50 = 13 mg/L 48 h
ETHYL BENZENE	EC50 = 4.6 mg/L 72 h EC50 > 438 mg/L 96 h	LC50= 14.0 mg/L Oncorhynchus mykiss 96 h LC50= 9.09 mg/L Pimephales promelas 96 h LC50= 150.0 mg/L Lepomis macrochirus 96 h LC50= 4.2 mg/L Oncorhynchus mykiss 96 h LC50= 32 mg/L Lepomis macrochirus 96 h LC50= 48.5 mg/L Pimephales promelas 96 h LC50= 9.6 mg/L Poecilia reticulata 96 h	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 1.8 - 2.4 mg/L 48 h

### 13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### Contaminated Packaging

Empty containers should be taken for local recycling, recovery or waste disposal

### 14. TRANSPORT INFORMATION

**DOT** Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.  
**Proper Shipping Name** UN3066, PAINT, 8, PGIII, ERG 153

### 15. REGULATORY INFORMATION

#### International Inventories

TSCA	Complies
DSL/NDL	Does not Comply
EINECS/ELINCS	Does not Comply
CHINA	Does not Comply
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Does not Comply
AICS	Does not Comply

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

**Component**XYLENE  
ETHYL BENZENE**U.S. Federal Regulations****SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values
XYLENE	1330-20-7	1.5363	1.0
PHENOL (SKIN)	108-95-2	0.4721	1.0
ETHYL BENZENE	100-41-4	0.3787	0.1

**SARA 311/312 Hazardous Categorization**

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE	100 lb			X
PHENOL (SKIN)	1000 lb	X	X	X
ETHYL BENZENE	1000 lb	X	X	X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs
XYLENE	100 lb	
PHENOL (SKIN)	1000 lb	1000 lb
ETHYL BENZENE	1000 lb	

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen
ETHYL BENZENE	100-41-4	Carcinogen

**State Right-to-Know**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
TITANIUM DIOXIDE (TOTAL DUST)	X	X	X		X
XYLENE	X	X	X	X	X
PHENOL (SKIN)	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X
ALUMINUM OXIDES	X	X	X		X

Other International Regulations**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class**

D2A Very toxic materials

E Corrosive material



Component	NPRI
XYLENE	Part 1, Group 1 Substance; Part 5 Substance
PHENOL (SKIN)	Part 1, Group 1 Substance
ETHYL BENZENE	Part 1, Group 1 Substance
ALUMINUM OXIDES	Part 1, Group 1 Substance (fibrous form)

**Legend**

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION
-----------------------

Revision Date: 29-Dec-2009

Revision Summary: No information available

HMIS                                      Health 3                                      Flammability 1                                      Reactivity 1

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**