



Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code S244-0244A
Trade Name ULTRA-TREAD S244/S246 CLEAR
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

HARMFUL IF INHALED.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
HARMFUL OR FATAL IF SWALLOWED.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes Irritating to eyes.
Skin Irritating to skin.
Inhalation Irritating to respiratory system.
Ingestion May be harmful if swallowed.

Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Kidney disorders. Skin disorders.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Eyes, Kidney, Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
BUTYL BENZYL PHTHALATE	85-68-7	10 - 30
VEGETABLE OIL MIST	M288	5 - 10

3. COMPOSITION/INFORMATION ON INGREDIENTS

SORBITAN MONOLAURATE	1338-39-2	5 - 10
ALKYL GLYCIDYL ETHER	68609-97-2	1 - 5
PINE OIL	8002-09-3	1 - 5

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	No information available
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous Decomposition Products	Oxides of carbon, hydrocarbons. Oxides of nitrogen. Hydrogen cyanide.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

Safety glasses with side-shields

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point

Not applicable

Boiling Point/Range

100°C / 212.0.0°F

Upper Exposure Limits

No information available

Lower Exposure Limits

No information available

Evaporation Rate

No information available

Vapour Pressure

No information available

Vapour Density

No information available

Specific Gravity

1.01880

Density

8.47797

VOC Content (lbs/gal)

.469

% Volatile by Weight

32.0530

% Volatile by Volume

32.8402

10. STABILITY AND REACTIVITY

Chemical stability

Stable.

Conditions to Avoid

Heat, flames and sparks. Reacts with air to form peroxides. Amines.

Incompatible Products

Strong oxidizing agents. Acids. Amines.

Possibility of Hazardous Reactions

None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
BUTYL BENZYL PHTHALATE	2330 mg/kg (Rat)	6700 mg/kg (Rat)	6.7 mg/L (Rat) 4 h
SORBITAN MONOLAURATE	33600 mg/kg (Rat)		
ALKYL GLYCIDYL ETHER	17100 mg/kg (Rat)		
PINE OIL	3200 mg/kg (Rat)	5 g/kg (Rabbit)	

Irritation

No information available

Corrosivity

No information available

Sensitization No information available

Chronic Toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Mutagenic Effects No information available
Reproductive Effects No information available
Developmental Effects Developmental Effects .
Teratogenicity No information available
Target Organ Effects Eyes, Kidney, Respiratory system, Skin.
Endocrine Disruptor Information No information available

Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
BUTYL BENZYL PHTHALATE	Group I Chemical Group III Chemical	High Exposure Concern	

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
BUTYL BENZYL PHTHALATE	EC50 = 0.1 mg/L 96 h	LC50 1 - 10 mg/L Oncorhynchus mykiss 96 h LC50= 1.7 mg/L Pimephales promelas 96 h LC50= 1.0 mg/L Lepomis macrochirus 96 h		EC50 = 3.0 mg/L 48 h EC50 = 0.97 mg/L 48 h
SORBITAN MONOLAURATE		LC50= 75 mg/L Salmo gairdneri 96 h		
PINE OIL				EC50 = 3.32 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper Shipping Name PAINT, WATER BASE FREEZABLE

Marine Pollutant: This product contains a chemical which is listed as a marine pollutant according to DOT.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDL Does not Comply
EINECS/ELINCS Does not Comply
CHINA Does not Comply

ENCS Does not Comply
 KECL Does not Comply
 PICCS Does not Comply
 AICS Does not Comply

U.S. Federal Regulations

SARA 313

SARA 311/312 Hazardous Categorization

Chronic Health Hazard No
 Acute Health Hazard Yes
 Fire Hazard Yes
 Sudden Release of Pressure Hazard No
 Reactive Hazard No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
BUTYL BENZYL PHTHALATE			X	

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
BUTYL BENZYL PHTHALATE	100 lb	

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
BUTYL BENZYL PHTHALATE	85-68-7	Developmental

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
BUTYL BENZYL PHTHALATE	X	X	X	X	
PINE OIL		X			

Other International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials



Component	NPRI
BUTYL BENZYL PHTHALATE	Part 1, Group 1 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 29-Dec-2009

Revision Summary No information available


HMIS **Health** 0 **Flammability** 0 **Reactivity** 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS



Material Safety Data Sheet

Print Date 12-Dec-2011

Revision Date 12-Dec-2011

Revision Number 2

1. PRODUCT AND COMPANY IDENTIFICATION

Common name	SERIES S244 PART B
Product code	S244-0244B
Trade name	ULTRA-TREAD S244/S246 CONVERTE
Product Class	ISOCYANATE
Manufacturer	Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency telephone	800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

DANGER!

HARMFUL OR FATAL IF SWALLOWED
HARMFUL IF INHALED
MAY CAUSE LUNG INJURY
MAY CAUSE ALLERGIC RESPIRATORY REACTION; EFFECTS MAY BE PERMANENT
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential health effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute effects

Eyes	Moderately irritating to the eyes. Risk of serious damage to eyes.
Skin	Irritating to skin. May cause sensitization by skin contact.
Inhalation	Irritating to respiratory system. May cause allergic respiratory reaction.
Ingestion	May be harmful if swallowed.

Chronic effects

Avoid repeated exposure.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Respiratory disorders.

Interactive effects Use of alcoholic beverages may enhance toxic effects.

Potential environmental effects See Section 12 for additional Ecological Information.

Target Organ Effects Eyes, Respiratory system

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
POLYMERIC MDI	9016-87-9	30 - 60
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	101-68-8	30 - 60
DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER	26447-40-5	10 - 30
DIPHENYLMETHANE DIISOCYANATE (VOLATILE MONOMER)	101-68-8	1 - 5

4. FIRST AID MEASURES

Eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin contact:	Wash off immediately with soap and plenty of water.
Ingestion:	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation:	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable properties	No information available.
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical

Hazardous decomposition products Oxides of carbon, hydrocarbons. Oxides of nitrogen. Hydrogen cyanide.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for cleaning up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other information	Not applicable

7. HANDLING AND STORAGE

Handling

Use only with adequate ventilation. Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Close container after each use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	TWA: 0.005 ppm	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m ³	TWA: 0.005 ppm TWA: 0.051 mg/m ³	TWA: 0.005 ppm CEV: 0.02 ppm	TWA: 0.02 ppm TWA: 0.2 mg/m ³ TWA: 0.005 ppm TWA: 0.051 mg/m ³
DIPHENYLMETHANE DIISOCYANATE (VOLATILE MONOMER)	TWA: 0.005 ppm	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m ³	TWA: 0.005 ppm TWA: 0.051 mg/m ³	TWA: 0.005 ppm CEV: 0.02 ppm	TWA: 0.02 ppm TWA: 0.2 mg/m ³ TWA: 0.005 ppm TWA: 0.051 mg/m ³

Engineering measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face protection

Safety glasses with side-shields

Respiratory protection

INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point	Not applicable
Boiling range	No information available
Upper explosion limit	No information available
Lower explosion limit	No information available
Evaporation rate	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	1.22094 g/cm ³
Density	10.16002 lbs/gal
Volatile organic compounds (VOC) content	.102 lbs/gal
Volatile by weight	1.0000 %
Volatile by volume	1.0261 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to avoid	Heat, flames and sparks. Amines.
Incompatible products	Water, alcohols, amines, strong bases, metal components, surface active materials.	Possibility of hazardous reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
POLYMERIC MDI	49 g/kg (Rat)	9400 mg/kg (Rabbit)	490 mg/m ³ (Rat) 4 h
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	9200 mg/kg (Rat)		
DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER	7400 mg/kg (Rat)	6200 mg/kg (Rabbit)	0.369 mg/L (Rat) 4 h
DIPHENYLMETHANE DIISOCYANATE (VOLATILE MONOMER)	9200 mg/kg (Rat)		

Irritation	No information available
Corrosivity	No information available.
Sensitization	No information available.

Chronic toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Mutagenicity	No information available.
Reproductive effects	No information available.
Developmental effects	No information available.
Teratogenicity	No information available.
Target Organ Effects	Eyes, Respiratory system.
Endocrine Disruptor Information	No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER	EC50 = 3230 mg/L 96 h			EC50 > 1000 mg/L 24 h

13. DISPOSAL CONSIDERATIONS

Waste disposal methods	Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Contaminated packaging	Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper shipping name PAINT,WATER BASE FREEZABLE

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
CHINA	Complies
ENCS	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component HAPS Data

DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER

DIPHENYLMETHANE DIISOCYANATE (VOLATILE MONOMER)

United States of America Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
POLYMERIC MDI	9016-87-9	30 - 60	1.0
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	101-68-8	30 - 60	1.0
DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER	26447-40-5	10 - 30	1.0
DIPHENYLMETHANE DIISOCYANATE (VOLATILE MONOMER)	101-68-8	1 - 5	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	yes
Acute Health Hazard	yes
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no


CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	5000 lb	
DIPHENYLMETHANE DIISOCYANATE (VOLATILE MONOMER)	5000 lb	

United States of America State Regulations

California Prop. 65

This product contains the following Proposition 65 chemicals:



Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code S244-0244C
Trade Name ULTRA-TREAD M AGGREGATE
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

MAY CAUSE EYE INJURY.
CAUSES SKIN AND EYE BURNS.
HARMFUL BY INHALATION.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes Causes burns. May cause eye injury. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible tissue (skin, eye, respiratory tract) damage due to chemical (caustic) burns, including third degree burns.

Skin Causes burns. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible tissue (skin, eye, respiratory tract) damage due to chemical (caustic) burns, including third degree burns.

Inhalation Irritating to respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible tissue (skin, eye, respiratory tract) damage due to chemical (caustic) burns, including third degree burns.

Ingestion May be harmful if swallowed.

Chronic Effects

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Skin disorders.

Interactions with Other Chemicals No information available.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Eyes, Respiratory system, Skin, Lungs

3. COMPOSITION/INFORMATION ON INGREDIENTS

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	66.5605
CRUSHED GRANITE, QUARTZ, AND MARBLES		10 - 30
CALCIUM SILICATES AND ALUMINATES	65997-15-1	10 - 30
CALCIUM HYDROXIDE	1305-62-0	1 - 5

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	No information available.
Suitable Extinguishing Media	Foam, carbon dioxide, and dry chemical.
Hazardous Decomposition Products	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	Shovel or sweep up.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Tightly fitting safety goggles. Wear protective gloves/clothing. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³
CALCIUM SILICATES AND ALUMINATES	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³
CALCIUM HYDROXIDE	TWA: 5 mg/m ³	TWA: 5 mg/m ³ TWA: 15 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

Tightly fitting safety goggles

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	Not applicable
Boiling Point/Range	No information available.0.0
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	2.68798
Density	22.36799
VOC Content (lbs/gal)	.000
% Volatile by Weight	.0000
% Volatile by Volume	.0000

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks
Incompatible Products	Acids. Strong oxidizing agents.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg (Rat)		

11. TOXICOLOGICAL INFORMATION

CALCIUM HYDROXIDE	7340 mg/kg (Rat)		
-------------------	--------------------	--	--

Irritation	No information available
Corrosivity	No information available
Sensitization	No information available

Chronic Toxicity

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	

Mutagenic Effects	No information available
Reproductive Effects	No information available
Developmental Effects	No information available
Teratogenicity	No information available
Target Organ Effects	Eyes, Respiratory system, Skin, Lungs.
Endocrine Disruptor Information	No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
CALCIUM HYDROXIDE		LC50= 160 mg/L Gambusia affinis 96 h		

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods	Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Contaminated Packaging	Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Does not Comply
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Does not Comply

AICS Does not Comply

U.S. Federal Regulations

SARA 313

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
CALCIUM SILICATES AND ALUMINATES	X	X	X		X
CALCIUM HYDROXIDE	X	X	X		X

Other International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2A Very toxic materials



Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 29-Dec-2009

Revision Summary: No information available

HMIS Health 1 Flammability 0 Reactivity 0

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS