



# Safety Data Sheet

Issue Date 28-Jul-2015

Revision Date 28-Jul-2015

Revision Number 10

## 1. IDENTIFICATION

### Product identifier

**Product Code** S215-1200A  
**Product Name** SURFACING EPOXY PRIMER WHITE

### Other means of identification

**Common Name** SERIES 215/215ML, PART A

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Corrosive to Metals	Category 1

### Label elements

## EMERGENCY OVERVIEW

Danger

**Hazard statements**

Harmful if swallowed  
 Harmful if inhaled  
 Causes severe skin burns and eye damage  
 May cause an allergic skin reaction  
 May cause genetic defects  
 May cause cancer  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 Causes damage to organs through prolonged or repeated exposure  
 May be corrosive to metals

**Appearance** opaque**Physical state** liquid**Odor** amine**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Keep only in original container

**Response**

Immediately call a POISON CENTER or doctor/physician  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 Immediately call a POISON CENTER or doctor/physician  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 Do NOT induce vomiting  
 Absorb spillage to prevent material damage

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Store in corrosive resistant/metal/plastic container with a resistant inner liner  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other information**

May be harmful in contact with skin

Harmful to aquatic life with long lasting effects

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs

SEE SAFETY DATA SHEET

Acute Toxicity

13.96486 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - 30%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	10 - 30%
COAL FIRED FLY ASH BI-PRODUCT	68131-74-8	10 - 30%
AMIDO AMINE	-	10 - 30%
BENZYL ALCOHOL	100-51-6	1 - 10%
4,7-METHANO-1H-INDENEDIMETHANAMINE, OCTAHYDRO-	68889-71-4	1 - 10%
PHENALKAMINE CURING AGENT	-	1 - 10%
AMORPHOUS SILICA	7631-86-9	1 - 10%
TETRAETHYLENEPENTAMINE	112-57-2	1 - 10%
ALUMINUM OXIDES	1344-28-1	0.1 - 1%
ALUMINUM HYDROXIDE	21645-51-2	0.1 - 1%
STODDARD SOLVENT (MINERAL SPIRITS)	8052-41-3	0.1 - 1%
ZIRCONIUM OXIDE	1314-23-4	0.1 - 1%
FATTY ACIDS	147900-93-4	0.1 - 1%
THIXATROPIC ADDITIVE	C389	0.1 - 1%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.1 - 1%
MODIFIED ALIPHATIC AMINE	1477-55-0	0.1 - 1%
FATTY ACIDS	85711-55-3	0 - 0.1%
PARAFFINIC SOLVENT	64742-47-8	0 - 0.1%
Trade secret	-	0 - 0.1%
POLYSILOXANE DEFOAMER	-	0 - 0.1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Flush immediately with large amounts of clean water under low pressure for at least 15 minutes. Consult a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

#### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

alcohol-resistant foam. Carbon dioxide. Dry chemical. Dry powder.

**Unsuitable extinguishing media** No information available.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Ammonia. Nitrogen oxides (NOx). Carbon dioxide. Hydrocarbons.

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Incompatible with oxidizing agents. Strong acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	TWA: 1 mg/m <sup>3</sup>	-	100 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m <sup>3</sup>	3000 mg/m <sup>3</sup>
ALUMINUM OXIDES 1344-28-1	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	
ALUMINUM HYDROXIDE 21645-51-2	TWA: 1 mg/m <sup>3</sup>	-	
STODDARD SOLVENT (MINERAL SPIRITS) 8052-41-3	TWA: 100 ppm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup>	20000 mg/m <sup>3</sup>
ZIRCONIUM OXIDE 1314-23-4	TWA: 5 mg/m <sup>3</sup>	-	25 mg/m <sup>3</sup>
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
MODIFIED ALIPHATIC AMINE 1477-55-0	Skin Ceiling: 0.1 mg/m <sup>3</sup>	Skin Ceiling: 0.1 mg/m <sup>3</sup>	
Trade secret	TWA: 20 ppm	TWA: 25 ppm TWA: 120 mg/m <sup>3</sup> Skin TWA: 50 ppm TWA: 240 mg/m <sup>3</sup>	700 ppm

**Appropriate engineering controls****Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties****Physical state**

liquid

<b>Appearance</b>	opaque	<b>Odor</b>	amine
<b>Color</b>	No information available	<b>Odor threshold</b>	No information available
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
pH		No data available	
Melting point / freezing point		No data available	
Boiling point / boiling range	72 °C / 162 °F		
Flash point	No information available		
Evaporation rate		No data available	
Flammability (solid, gas)		No information available	
Flammability Limit in Air		No data available	
Upper flammability limit	N/A		
Lower flammability limit	N/A		
Vapor pressure		No data available	
Vapor density		No data available	
Specific gravity	1.59846	g/cm3	
Water solubility	Insoluble in cold water		
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity	32000 centipoises		

**Other Information**

Density	13.30162 lbs/gal
Volatile organic compounds (VOC) content	.149 lbs/gal
Total volatiles weight percent	1.1238 %
Total volatiles volume percent	1.8374 %

**10. STABILITY AND REACTIVITY**

**Reactivity**  
No data available

**Chemical stability**  
Stable under recommended storage conditions.

**Possibility of hazardous reactions**  
None under normal processing.

**Conditions to avoid**  
Heat, flames and sparks.

**Incompatible materials**  
Incompatible with oxidizing agents, Strong acids

**Hazardous decomposition products**  
Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Ammonia. Oxides of nitrogen. Carbon dioxide. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION**

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Severely irritating to eyes. May cause burns.

**Skin contact** Contact causes severe skin irritation and possible burns.

**Ingestion** Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg ( Rat )		
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	> 2000 mg/kg ( Rat )		
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h
AMORPHOUS SILICA 7631-86-9	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h
TETRAETHYLENEPENTAMINE 112-57-2	= 2100 mg/kg ( Rat )	= 660 µL/kg ( Rabbit )	
ALUMINUM OXIDES 1344-28-1	> 5000 mg/kg ( Rat )		
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg ( Rat )		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg ( Rat )		
MODIFIED ALIPHATIC AMINE 1477-55-0	= 660 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 700 ppm ( Rat ) 1 h
PARAFFINIC SOLVENT 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Trade secret	= 470 mg/kg ( Rat )	= 99 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h

#### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Irritation** Severely irritating to eyes. Severe skin irritation.  
**Chronic Toxicity** NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

**Sensitization** May cause sensitization of susceptible persons.

**Mutagenicity** May cause genetic defects.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B		X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8		Group 1	Known	
AMORPHOUS SILICA 7631-86-9		Group 3		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
Trade secret	A3	Group 3		

**Reproductive effects** No information available.

**STOT - single exposure** Central Nervous System (CNS), Eyes, Skin  
**STOT - repeated exposure** No information available  
**Target organ effects** Eyes, Lungs, respiratory system, Skin, kidney, liver, Nasal Cavities.  
**Aspiration hazard** Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

**Acute Toxicity** 13.96486 % of the mixture consists of ingredient(s) of unknown toxicity. mg/kg mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects

46.17086 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8			140 - 2000: 24 h Daphnia magna mg/L EC50
BENZYL ALCOHOL 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static	23: 48 h water flea mg/L EC50
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
TETRAETHYLENEPENTAMINE 112-57-2	2.1: 72 h Pseudokirchneriella subcapitata mg/L EC50	420: 96 h Poecilia reticulata mg/L LC50 static	24.1: 48 h Daphnia magna mg/L EC50
PARAFFINIC SOLVENT 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static 2.2: 96 h Lepomis macrochirus mg/L LC50 static	4720: 96 h Den-dronereides heteropoda mg/L LC50
Trade secret		2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static	1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

### Mobility in Environmental Media

Component	log Pow
BENZYL ALCOHOL 100-51-6	1.1
TETRAETHYLENEPENTAMINE 112-57-2	.99
Trade secret	0.81

### Other Adverse Effects

No information available

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

#### **Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

#### **Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.



Component	CAWAST
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	Toxic Corrosive

#### 14. TRANSPORT INFORMATION

**DOT**

**Emergency Response Guide Number** 153

**IATA**

**UN/ID no.** 3066  
**Proper Shipping Name** paint  
**Hazard Class** 8  
**Packing Group** II  
**ERG Code** 855

**Additional information**

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

#### 15. REGULATORY INFORMATION

**International Inventories**

**TSCA** Complies  
**DSL/NDSL** Complies  
**EINECS/ELINCS** Does not comply  
**ENCS** Does not comply  
**IECSC** Does not comply  
**KECL** Does not comply  
**PICCS** Does not comply  
**AICS** Does not comply

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
COAL FIRED FLY ASH BI-PRODUCT	
Trade secret	

**United States of America****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
COAL FIRED FLY ASH BI-PRODUCT - 68131-74-8	1.0 0.1
ALUMINUM OXIDES - 1344-28-1	1.0
Trade secret -	1.0

**SARA 311/312 Hazardous**

**Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8		X		

**CERCLA**

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
COAL FIRED FLY ASH BI-PRODUCT - 68131-74-8	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
Trade secret -	*

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
COAL FIRED FLY ASH BI-PRODUCT 68131-74-8	X		X
BENZYL ALCOHOL 100-51-6		X	X
AMORPHOUS SILICA 7631-86-9	X	X	X
TETRAETHYLENAPENTAMINE 112-57-2	X	X	X
ALUMINUM OXIDES 1344-28-1	X	X	X
STODDARD SOLVENT (MINERAL SPIRITS) 8052-41-3	X	X	X
ZIRCONIUM OXIDE 1314-23-4		X	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
MODIFIED ALIPHATIC AMINE 1477-55-0	X	X	X
Trade secret	X	X	X

**16. OTHER INFORMATION**

<b>NFPA</b>	Health 3	Flammability 0	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 3*	Flammability 0	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
Revision Date 28-Jul-2015

**Revision Summary**


9 4 5 7 8 10 11 14

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 28-Jul-2015

Revision Date 28-Jul-2015

Revision Number 10

## 1. IDENTIFICATION

### Product identifier

**Product Code** S215-0215B  
**Product Name** SURFACING EPOXY CONVERTER

### Other means of identification

**Common Name** SERIES 215/215ML, PART B

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1A
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1


### Label elements

#### **EMERGENCY OVERVIEW**

#### **Danger**

#### **Hazard statements**

Harmful if swallowed  
Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
May cause cancer  
Causes damage to organs through prolonged or repeated exposure



**Appearance** opaque
**Physical state** liquid
**Odor** amine

**Precautionary Statements**

**Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Do not breathe dust/fume/gas/mist/vapors/spray

**Response**

- IF exposed or concerned: Get medical advice/attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN: Wash with plenty of soap and water
- Take off contaminated clothing and wash before reuse
- If skin irritation or rash occurs: Get medical advice/attention
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth

**Storage**

- Store locked up
- Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).
- Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs
- SEE SAFETY DATA SHEET
- Acute Toxicity 0.33775 % of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS-No	Weight-%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	30 - 60%
EPOXY RESIN (LER)	25085-99-8	30 - 60%
EPOXY RESIN	28064-14-4	10 - 30%
ALKYL GLYCIDYL ETHER	68609-97-2	1 - 10%
HYDROPHOBIC FUMED SILICA	67762-90-7	1 - 10%
BENZYL ALCOHOL	100-51-6	0.1 - 1%

GAMMA-GLYCIDOPROPYLTRIMETHOXYSILANE	2530-83-8	0.1 - 1%
PETROLEUM SOLVENT (NAPHTHA)	64742-95-6	0 - 0.1%
STODDARD SOLVENT (MINERAL SPIRITS)	8052-41-3	0 - 0.1%
FATTY ACIDS	147900-93-4	0 - 0.1%
FATTY ACIDS	85711-55-3	0 - 0.1%
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	108-65-6	0 - 0.1%
METHYL ALCOHOL	-	0 - 0.1%
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	0 - 0.1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

##### Most important symptoms and effects, both acute and delayed

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Water spray. Dry chemical. Foam. Carbon dioxide.

**Unsuitable extinguishing media** No information available.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Aldehydes. Phenolics.

##### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Incompatible with oxidizing agents. Strong acids. Bases. Amines. Alkalis.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
STODDARD SOLVENT (MINERAL SPIRITS) 8052-41-3	TWA: 100 ppm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup>	20000 mg/m <sup>3</sup>
METHYL ALCOHOL	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup> Skin	6000 ppm
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	TWA: 20 ppm	TWA: 25 ppm TWA: 120 mg/m <sup>3</sup> Skin TWA: 50 ppm TWA: 240 mg/m <sup>3</sup>	700 ppm

NIOSH IDLH: *Immediately Dangerous to Life or Health*

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

**Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	amine
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range		No information available
Flash point	No information available	
Evaporation rate		No data available
Flammability (solid, gas)		No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.59270	g/cm <sup>3</sup>
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	205000 centipoises	

**Other Information**

<b>Density</b>	13.25362 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	.021 lbs/gal
<b>Total volatiles weight percent</b>	.1570 %
<b>Total volatiles volume percent</b>	.2825 %

## 10. STABILITY AND REACTIVITY



**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Incompatible with oxidizing agents, Strong acids, Bases, Amines, Alkalis

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Aldehydes. Phenolics.

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Information on Likely Routes of Exposure**

<b>Inhalation</b>	Harmful if inhaled. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Severely irritating to eyes.
<b>Skin contact</b>	Irritating to skin. May cause sensitization of susceptible persons.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg ( Rat )		
ALKYL GLYCIDYL ETHER 68609-97-2	= 17100 mg/kg ( Rat )		
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h
GAMMA-GLYCIDOXYPROPYLTRI METHOXYSILANE 2530-83-8	= 22600 µL/kg ( Rat )	= 3970 µL/kg ( Rabbit )	
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	
METHYL ALCOHOL	= 6200 mg/kg ( Rat )	= 15800 mg/kg ( Rabbit )	= 22500 ppm ( Rat ) 8 h = 64000 ppm ( Rat ) 4 h
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h

**Information on toxicological effects**

<b>Symptoms</b>	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.
-----------------	---

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

**Sensitization**

May cause sensitization of susceptible persons.

**Mutagenicity**

No information available.

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
PETROLEUM SOLVENT (NAPTHA) 64742-95-6	.			
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	A3	Group 3		

**Reproductive effects**

No information available.

**STOT - single exposure**

No information available

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure

**Target organ effects**

Eyes, Lungs, respiratory system, Skin, kidney, liver.

**Aspiration hazard**

Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

**Acute Toxicity**

0.33775 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

48.94707 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
EPOXY RESIN (LER) 25085-99-8	11 mg/L 72 hr	2 mg/L 96 hr Oncorhynchus mykiss	1.8 mg/L 48h
BENZYL ALCOHOL 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static	23: 48 h water flea mg/L EC50
PETROLEUM SOLVENT (NAPTHA) 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6		161: 96 h Pimephales promelas mg/L LC50 static	500: 48 h Daphnia magna mg/L EC50
METHYL ALCOHOL		28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2		2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static	1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
BENZYL ALCOHOL 100-51-6	1.1
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE 108-65-6	0.43
METHYL ALCOHOL	-0.77
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	0.81

**Other Adverse Effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ALCOHOL		Included in waste stream: F039		U154

Component	CAWAST
METHYL ALCOHOL	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**  
Proper Shipping Name paint in oil Not regulated

**IATA**  
Proper Shipping Name Not regulated

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECL	Does not comply
PICCS	Does not comply
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECS** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):**

<b>Component</b>	<b>HAPS Data</b>
METHYL ALCOHOL	
ETHYLENE GLYCOL MONOBUTYL ETHER	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

Component	SARA 313 - Threshold Values
METHYL ALCOHOL -	1.0
ETHYLENE GLYCOL MONOBUTYL ETHER - 111-76-2	1.0

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ALCOHOL	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen
PETROLEUM SOLVENT (NAPHTHA) - 64742-95-6	.
METHYL ALCOHOL -	Developmental
ETHYLENE GLYCOL MONOBUTYL ETHER - 111-76-2	*

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
BENZYL ALCOHOL 100-51-6		X	X
STODDARD SOLVENT (MINERAL SPIRITS) 8052-41-3	X	X	X
METHYL ALCOHOL	X	X	X

ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	X	X	X
--	---	---	---

### 16. OTHER INFORMATION

<b>NFPA</b>	Health 2	Flammability 0	Instability 0	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 0	Reactivity 0	

Prepared By Tnemec Regulatory Dept: 816-474-3400  
Revision Date 28-Jul-2015

Revision Summary  
9 4 5 7 10 8 11 14 15

#### Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**