



Safety Data Sheet

Issue Date No data available

Revision Date 05-Mar-2015

Revision Number 9

1. IDENTIFICATION

Product identifier

Product Code F066-00WHA
Product Name H-B EPOXOLINE TNEMEC WHITE

Other means of identification

Common Name SERIES 66 PART A
UN/ID no. 1263

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2 Category 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Harmful if swallowed
 Harmful if inhaled
 Causes serious eye damage
 May cause an allergic skin reaction
 Suspected of causing cancer
 Suspected of damaging fertility or the unborn child
 May cause respiratory irritation. May cause drowsiness or dizziness
 Causes damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 May cause genetic defects
 May cause cancer
 Flammable liquid and vapor

**Appearance** viscous liquid opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Rinse mouth
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

May be harmful in contact with skin

Causes mild skin irritation

Harmful to aquatic life with long lasting effects

SEE SAFETY DATA SHEET

Acute Toxicity

30.42548 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	10 - 30%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - 30%
TALC (RESPIRABLE DUST)	14807-96-6	10 - 30%
XYLENE	1330-20-7	10 - 30%
N-BUTANOL (SKIN)	71-36-3	1 - 10%
ETHYL BENZENE	100-41-4	1 - 10%
AMORPHOUS SILICA	7631-86-9	1 - 10%
TRIETHYLENE TETRAMINE	112-24-3	0.1 - 1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - 1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures**General advice**

If symptoms persist, call a physician.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.

Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion

If swallowed, do not induce vomiting. Get medical attention immediately.

Self-protection of the first aider

Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed**Notes to physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Dry chemical.

Unsuitable extinguishing media Water.

Specific hazards arising from the chemical

Flammable liquid Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Nitrogen oxides (NOx). Aldehydes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Use personal protective equipment. Avoid contact with eyes, skin and clothing. Remove all sources of ignition. Ensure adequate ventilation.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE**Precautions for safe handling**

Handling Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Do not ingest. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Strong oxidizing agents. Acids. Cleaning solutions such as Chromerge and Aqua Regia. Water, alcohols, amines, strong bases, metal components, surface active materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters**

Exposure guidelines .

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	
N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m ³ TWA: 100 ppm TWA: 300 mg/m ³	1400 ppm
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	800 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m ³	3000 mg/m ³
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

Appropriate engineering controls

Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	aromatic
Appearance	viscous liquid opaque	Odor threshold	No information available
Color	opaque		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	116 °C / 241.0 °F	
Flash point	28 °C / 82.0 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)		No information available
Flammability Limit in Air		No data available
Upper flammability limit	NA	
Lower flammability limit	NA	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.71251	g/cm3
Water solubility	insoluble	
Solubility in other solvents		Petroleum distillates Hydrocarbons
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	900 centipoises	

Other Information

Density	14.28232 lbs/gal
Volatile organic compounds (VOC) content	3.14211 lbs/gal
Total volatiles weight percent	22 %
Total volatiles volume percent	44.57 %

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Epoxy constituents.

Incompatible materials

Strong oxidizing agents, Acids, Cleaning solutions such as Chromerge and Aqua Regia, Water, alcohols, amines, strong bases, metal components, surface active materials

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure**

Inhalation	Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Vapors may irritate throat and respiratory system.
Eye contact	Causes serious eye damage.
Skin contact	Irritating to skin. May cause sensitization by skin contact.

Ingestion

Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg (Rat)		
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg (Rat) = 790 mg/kg (Rat)	= 3402 mg/kg (Rabbit) = 3400 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
AMORPHOUS SILICA 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
TRIETHYLENE TETRAMINE 112-24-3	= 2500 mg/kg (Rat)	= 550 mg/kg (Rabbit)	
BENZENE, 1,3-DIMETHYL 108-38-3	= 5000 mg/kg (Rat)	= 14100 µL/kg (Rabbit)	

Information on toxicological effects

Symptoms

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

May cause sensitization of susceptible persons.

Mutagenicity

May cause genetic defects.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B		X
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		
XYLENE 1330-20-7		Group 3		
ETHYL BENZENE 100-41-4	A3	Group 2B		X
AMORPHOUS SILICA 7631-86-9		Group 3		
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3		

IARC: (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans

Reproductive effects

Suspected of damaging fertility or the unborn child.

STOT - single exposure

May cause disorder and damage to the, Eyes, Skin, Central Nervous System (CNS)

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, kidney, liver, respiratory system, Skin.

Target organ effects

Aspiration hazard

Risk of serious damage to the lungs (by aspiration).

Acute Toxicity

30.42548 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

16.02190988 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
-----------	-------------------	------------------	---------------------

TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
N-BUTANOL (SKIN) 71-36-3	500: 96 h Desmodemus subspicatus mg/L EC50 500: 72 h Desmodemus subspicatus mg/L EC50	1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
TRIETHYLENE TETRAMINE 112-24-3	2.5: 72 h Desmodemus subspicatus mg/L EC50 20: 72 h Pseudokirchneriella subcapitata mg/L EC50 3.7: 96 h Pseudokirchneriella subcapitata mg/L EC50	570: 96 h Poecilia reticulata mg/L LC50 semi-static 495: 96 h Pimephales promelas mg/L LC50	31.1: 48 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Component	log Pow
XYLENE 1330-20-7	2.77
N-BUTANOL (SKIN) 71-36-3	0.785
ETHYL BENZENE 100-41-4	3.118
TRIETHYLENE TETRAMINE 112-24-3	-1.4
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

Other Adverse Effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
BARIUM SULFATE (TOTAL DUST) 7727-43-7	Toxic
XYLENE 1330-20-7	Toxic Ignitable
N-BUTANOL (SKIN) 71-36-3	Toxic
ETHYL BENZENE 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no. 1263
Proper Shipping Name paint
Hazard Class 3
Packing Group III
Emergency Response Guide Number 128

IATA

UN/ID no. 1263
Proper Shipping Name paint
Hazard Class 3
Packing Group III
ERG Code 366

Additional information Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Does not comply
ENCS Does not comply
IECSC Complies

KECL Does not comply
 PICCS Does not comply
 AICS Does not comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
XYLENE	
ETHYL BENZENE	
BENZENE, 1,3-DIMETHYL	

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0
XYLENE - 1330-20-7	1.0
N-BUTANOL (SKIN) - 71-36-3	1.0
ETHYL BENZENE - 100-41-4	0.1
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3				X

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

United States of America

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
XYLENE 1330-20-7	X	X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
AMORPHOUS SILICA 7631-86-9	X	X	X
TRIETHYLENE TETRAMINE 112-24-3	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

16. OTHER INFORMATION

NFPA **Health** 2 **Flammability** 3 **Instability** 1 **Physical hazard** *
HMIS (Hazardous **Health** 2* **Flammability** 3 **Reactivity** 1
Material Information
System)


Prepared By Tnemec Regulatory Dept: 816-474-3400
Revision Date 05-Mar-2015
Revision Summary
 4 5 6 7 10 8 9 11 14

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS



Safety Data Sheet

Issue Date No data available

Revision Date 05-Mar-2015

Revision Number 9

1. IDENTIFICATION

Product identifier

Product Code B066-0066B
Product Name F65/66/160/161 CONVERTER

Other means of identification

Common Name SERIES 66/161, PART B
UN/ID no. 1263

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
May damage fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure
Highly flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** Strong aromatic Petroleum distillates**Precautionary Statements****Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Response

IF exposed or concerned: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep cool
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

May be harmful in contact with skin
 Causes mild skin irritation
 Toxic to aquatic life with long lasting effects
 SEE SAFETY DATA SHEET
 Acute Toxicity

0.662186 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
TALC (RESPIRABLE DUST)	14807-96-6	30 - 60%
SOLID EPOXY RESIN	-	10 - 30%
METHYL ISOBUTYL KETONE	108-10-1	10 - 30%
EPOXY RESIN (LER)	25085-99-8	10 - 30%
XYLENE	1330-20-7	1 - 10%
ETHYL BENZENE	100-41-4	1 - 10%

BENZENE, 1,4-DIMETHYL	106-42-3	0.1 - 1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - 1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
Skin contact	Wash affected area with soap and water. Remove contaminated clothing. Dispose of or launder accordingly. Consult a physician if skin irritation persists.
Inhalation	Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Most important symptoms and effects Breathing difficulties. Asthma-like and/ or skin allergy-like symptoms.

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂). Foam. Dry chemical.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Aldehydes. Hydrocarbons.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Store locked up. Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

Incompatible products Incompatible with oxidizing agents. Bases. Acids. Amines.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³ TWA: 100 ppm TWA: 410 mg/m ³	500 ppm
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	800 ppm
BENZENE, 1,4-DIMETHYL 106-42-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm
-----------------------------------	-------------------------------	---	---------

NIOSH IDLH: Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses with side-shields If splashes are likely to occur, wear Goggles

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Strong aromatic
Appearance	opaque		Petroleum distillates
Color	No information available	Odor threshold	No information available
Property	Values	Remarks	
pH		No data available	
Melting point / freezing point		No data available	
Boiling point / boiling range	114 °C / 237.0 °F		
Flash point	18 °C / 64.0 °F		Pensky Martens - Closed Cup
Evaporation rate		No data available	
Flammability (solid, gas)		No information available	
Flammability Limit in Air		No data available	
Upper flammability limit	N/A		
Lower flammability limit	1.0		
Vapor pressure		No data available	
Vapor density		No data available	
Specific gravity	1.28259		g/cm3
Water solubility	Insoluble in cold water		
Solubility in other solvents		No data available	
Partition coefficient: n-octanol/water		No data available	
Autoignition temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity	600 centipoises		

Other Information

Density	10.67307 lbs/gal
Volatile organic compounds (VOC) content	2.895 lbs/gal
Total volatiles weight percent	27.1240 %

Total volatiles volume percent 42.0119 %

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Incompatible with oxidizing agents, Bases, Acids, Amines

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Aldehydes. Hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	MAY CAUSE DROWSINESS AND DIZZINESS. Inhalation of vapors in high concentration may cause irritation of respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Causes serious eye irritation.
Skin contact	Irritating to skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Ingestion	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
BENZENE, 1,4-DIMETHYL 106-42-3	= 4029 mg/kg (Rat)		= 4740 ppm (Rat) 4 h = 4550 ppm (Rat) 4 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5000 mg/kg (Rat)	= 14100 µL/kg (Rabbit)	

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity May cause cancer. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B		X
XYLENE 1330-20-7		Group 3		
ETHYL BENZENE 100-41-4	A3	Group 2B		X
BENZENE, 1,4-DIMETHYL 106-42-3		Group 3		
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive effects

May damage fertility or the unborn child.

STOT - single exposure

No information available

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure

Target organ effects

Central nervous system, Central Vascular System (CVS), Eyes, kidney, liver, respiratory system, Skin, blood, Gastrointestinal tract.

Aspiration hazard

Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

Acute Toxicity

0.662186 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

28.18462 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
EPOXY RESIN (LER) 25085-99-8	11 mg/L 72 hr	2 mg/L 96 hr Oncorhynchus mykiss	1.8 mg/L 48h
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h

ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
BENZENE, 1,4-DIMETHYL 106-42-3	3.2: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 105.1: 3 h Chlorella vulgaris mg/L EC50	2.6: 96 h Oncorhynchus mykiss mg/L LC50 8.8: 96 h Poecilia reticulata mg/L LC50 semi-static 7.2 - 9.9: 96 h Pimephales promelas mg/L LC50 static 2.6: 96 h Oncorhynchus mykiss mg/L LC50 static	3.55 - 6.31: 48 h Daphnia magna mg/L EC50 Static
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Component	log Pow
METHYL ISOBUTYL KETONE 108-10-1	1.19
XYLENE 1330-20-7	2.77
ETHYL BENZENE 100-41-4	3.118
BENZENE, 1,4-DIMETHYL 106-42-3	3.15
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods

In accordance with local and national regulations. Should not be released into the environment.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ISOBUTYL KETONE 108-10-1		Included in waste stream: F039		U161
XYLENE 1330-20-7		Included in waste stream: F039		U239
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

California Hazardous Waste Status

This product contains one or more substances that are listed with the State of California as a hazardous waste

Component	CAWAST
XYLENE 1330-20-7	Toxic Ignitable
ETHYL BENZENE 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no. 1263
 Proper Shipping Name paint
 Hazard Class 3
 Packing Group III
 Emergency Response Guide Number 128

IATA

UN/ID no. 1263
 Proper Shipping Name paint
 Hazard Class 3
 Packing Group III
 ERG Code 366

IMDG/IMO

UN/ID no. 1263
 Proper Shipping Name paint, (Epoxy Resin)
 Hazard Class 3
 Packing Group III
 EmS No. F-E, S-E
 Marine Pollutant This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Does not comply
 ENCS Complies
 IECSC Complies
 KECL Complies
 PICCS Complies
 AICS Does not comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component	HAPS Data
METHYL ISOBUTYL KETONE	

XYLENE
 ETHYL BENZENE
 BENZENE, 1,4-DIMETHYL
 BENZENE, 1,3-DIMETHYL

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
METHYL ISOBUTYL KETONE - 108-10-1	1.0
XYLENE - 1330-20-7	1.0
ETHYL BENZENE - 100-41-4	0.1
BENZENE, 1,4-DIMETHYL - 106-42-3	1.0
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3				X
BENZENE, 1,3-DIMETHYL 108-38-3				X

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,4-DIMETHYL 106-42-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

United States of America

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental
ETHYL BENZENE - 100-41-4	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X
XYLENE 1330-20-7	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

16. OTHER INFORMATION

NFPA	Health 2	Flammability 3	Instability 1	Physical hazard *
HMIS (Hazardous Material Information System)	Health 2*	Flammability 3	Reactivity 1	

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 05-Mar-2015
 Revision Summary
 5 10 11 13 9

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS