



# Safety Data Sheet

Issue Date 24-Jul-2015

Revision Date 24-Jul-2015

Revision Number 5

## 1. IDENTIFICATION

### Product identifier

**Product Code** 0L69-00WHA  
**Product Name** HB EPOXOLINE II TNEMEC WHITE

### Other means of identification

**Common Name** SERIES L69 PART A

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

#### **Distributor**

Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

### Label elements

#### EMERGENCY OVERVIEW

**Appearance** No information available      **Physical state** No information available      **Odor** No information available

### **Precautionary Statements**

#### **Prevention**

Do not handle until all safety precautions have been read and understood

#### **Response**

Get medical advice/attention if you feel unwell

#### **Storage**

Keep away from children

#### **Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

**Other information**

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs  
SEE SAFETY DATA SHEET

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - 30%
TALC (RESPIRABLE DUST)	14807-96-6	10 - 30%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - 30%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	10 - 30%
MODIFIED CYCLOALIPHATIC POLYAMINE	68953-36-6	1 - 10%
BENZYL ALCOHOL	100-51-6	1 - 10%
N-BUTYL ALCOHOL	-	1 - 10%
ISOPHORONE DIAMINE	2855-13-2	1 - 10%
AMORPHOUS SILICA	7631-86-9	1 - 10%
AROMATIC HYDROCARBON MIXTURE	64742-95-6	0.1 - 1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - 1%
TETRAETHYLENEPENTAMINE	112-57-2	0.1 - 1%
P-P'-ISOPROPYLIDENEDIPHENOL	80-05-7	0.1 - 1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** No information available.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

**Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

**Incompatible products** No information available.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	5000 mg/m <sup>3</sup>
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>

N-BUTYL ALCOHOL	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup> TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	1400 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m <sup>3</sup>	3000 mg/m <sup>3</sup>
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

**Appropriate engineering controls**

**Engineering measures**

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

If splashes are likely to occur, wear Goggles

**Skin and body protection**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Respiratory protection**

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	No information available	<b>Odor</b>	No information available
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		Literary Reference	
<b>Boiling point / boiling range</b>	116 °C / 241.0 °F	No information available	
<b>Flash point</b>	41 °C / 105.0 °F	Pensky Martens - Closed Cup	
<b>Evaporation rate</b>		No data available	
<b>Flammability (solid, gas)</b>			
<b>Flammability Limit in Air</b>		No data available	
<b>Upper flammability limit</b>	N/A		
<b>Lower flammability limit</b>	1.4		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	1.75853	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	
<b>Kinematic viscosity</b>			
<b>Dynamic viscosity</b>		No data available	

**Other Information**

Density	14.63357 lbs/gal
Volatile organic compounds (VOC) content	1.254 lbs/gal
Total volatiles weight percent	24.3430 %
Total volatiles volume percent	36.8595 %

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

No information available

**Hazardous decomposition products**

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons.

**11. TOXICOLOGICAL INFORMATION****Information on Likely Routes of Exposure**

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg ( Rat )		
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg ( Rat )		
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h
N-BUTYL ALCOHOL	= 700 mg/kg ( Rat ) = 790 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit ) = 3400 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
ISOPHORONE DIAMINE 2855-13-2	= 1030 mg/kg ( Rat )		
AMORPHOUS SILICA 7631-86-9	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 2.2 mg/L ( Rat ) 1 h
AROMATIC HYDROCARBON MIXTURE 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5000 mg/kg ( Rat )	= 14100 µL/kg ( Rabbit )	

TETRAETHYLENEPENTAMINE 112-57-2	= 2100 mg/kg ( Rat )	= 660 µL/kg ( Rabbit )	
P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7	= 3300 mg/kg ( Rat )	= 3 mL/kg ( Rabbit )	> 0.17 mg/L ( Rat ) 6 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic Toxicity** Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

**Sensitization** No information available.

**Mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B		X
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
AMORPHOUS SILICA 7631-86-9		Group 3		
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3		

**Reproductive effects** No information available.

**STOT - single exposure** No information available

**STOT - repeated exposure** No information available

**Target organ effects** Central nervous system, Central Vascular System (CVS), Eyes, Lungs, respiratory system, Skin.

**Aspiration hazard** Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
BENZYL ALCOHOL 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static	23: 48 h water flea mg/L EC50
N-BUTYL ALCOHOL	500: 96 h Desmodesmus subspicatus mg/L EC50 500: 72 h Desmodesmus subspicatus mg/L EC50	1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
ISOPHORONE DIAMINE 2855-13-2	37: 72 h Desmodesmus subspicatus mg/L EC50	110: 96 h Leuciscus idus mg/L LC50 semi-static	42: 24 h Daphnia magna mg/L EC50 14.6 - 21.5: 48 h Daphnia magna mg/L EC50 semi-static
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50

AROMATIC HYDROCARBON MIXTURE 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static
TETRAETHYLENEPENTAMINE 112-57-2	2.1: 72 h Pseudokirchneriella subcapitata mg/L EC50	420: 96 h Poecilia reticulata mg/L LC50 static	24.1: 48 h Daphnia magna mg/L EC50
P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7	2.5: 96 h Pseudokirchneriella subcapitata mg/L EC50	4.0 - 5.5: 96 h Pimephales promelas mg/L LC50 static 3.6 - 5.4: 96 h Pimephales promelas mg/L LC50 flow-through 4: 96 h Oncorhynchus mykiss mg/L LC50 9.9: 96 h Brachydanio rerio mg/L LC50 static	3.9: 48 h Daphnia magna mg/L EC50 10.2: 48 h Daphnia magna mg/L EC50 9.2 - 11.4: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
BENZYL ALCOHOL 100-51-6	1.1
N-BUTYL ALCOHOL	0.785
ISOPHORONE DIAMINE 2855-13-2	0.79
BENZENE, 1,3-DIMETHYL 108-38-3	3.2
TETRAETHYLENEPENTAMINE 112-57-2	.99
P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7	2.2

**Other Adverse Effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal Methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
N-BUTYL ALCOHOL		Included in waste stream: F039		U031

Component	CAWAST
N-BUTYL ALCOHOL	Toxic

**14. TRANSPORT INFORMATION**

**DOT**

**IATA**

**Additional information**

Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Does not comply
<b>AICS</b>	Does not comply

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

<b>Component</b>	<b>HAPS Data</b>
BENZENE, 1,3-DIMETHYL	

**United States of America**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
N-BUTYL ALCOHOL -	1.0
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0
P-P'-ISOPROPYLDENEDIPHENOL - 80-05-7	1.0

**SARA 311/312 Hazardous**

**Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
BENZENE, 1,3-DIMETHYL 108-38-3				X

**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
N-BUTYL ALCOHOL	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ



BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
-----------------------------------	---------	--	---

**United States of America**

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen

**California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

**State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
BENZYL ALCOHOL 100-51-6		X	X
N-BUTYL ALCOHOL	X	X	X
ISOPHORONE DIAMINE 2855-13-2	X		
AMORPHOUS SILICA 7631-86-9	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X
TETRAETHYLENEPENTAMINE 112-57-2	X	X	X
P-P'-ISOPROPYLIDENEDIPHENOL 80-05-7	X	X	X

**16. OTHER INFORMATION**

**NFPA** Health 0 Flammability 0 Instability 0 Physical hazard -  
**HMIS (Hazardous Material Information System)** Health 2\* Flammability 2 Reactivity 1

**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 24-Jul-2015

**Revision Summary**  
 No information available

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Safety Data Sheet

Issue Date 07-Jul-2015

Revision Date 07-Jul-2015

Revision Number 5

## 1. IDENTIFICATION

### Product identifier

**Product Code** L-69-0069B  
**Product Name** HB EPOXOLINE II CONVERTER

### Other means of identification

**Common Name** SERIES L69/L69F, PART B  
**UN/ID no.** 1263

### Recommended use of the chemical and restrictions on use

**Recommended Use** industrial paint.  
**Uses advised against** Consumer use, For professional use only. Not for residential use.

### Details of the supplier of the safety data sheet

**Manufacturer Address** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372  
**Distributor** Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

### Emergency telephone number

**Company Phone Number** Tnemec Regulatory Dept: 816-474-3400  
**24 Hour Emergency Phone Number** 800-535-5053 (Infotrac)

## 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

### Label elements

## EMERGENCY OVERVIEW

Danger

**Hazard statements**

Causes skin irritation  
 Causes serious eye irritation  
 May cause an allergic skin reaction  
 May cause genetic defects  
 May cause cancer  
 Suspected of damaging fertility or the unborn child  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 Causes damage to organs through prolonged or repeated exposure  
 Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Use only outdoors or in a well-ventilated area  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

**Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Storage**

Store locked up  
 Store in a well-ventilated place. Keep container tightly closed  
 Keep away from children

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

**Other information**

Toxic to aquatic life with long lasting effects

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure).

Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs

SEE SAFETY DATA SHEET

Acute Toxicity

57.34295099 % of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
TALC (RESPIRABLE DUST)	14807-96-6	30 - 60%
EPOXY RESIN (LER)	25085-99-8	10 - 30%
P-CHLOROBENZOTRIFLUORIDE	98-56-6	10 - 30%
EPOXY RESIN	25036-25-3	10 - 30%
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	1 - 10%
tert-BUTYL ACETATE	540-88-5	1 - 10%
1,2,4-TRIMETHYLBENZENE	95-63-6	0.1 - 1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - 1%

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	If symptoms persist, call a physician.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. Oxygen or artificial respiration if needed.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

**Most important symptoms and effects, both acute and delayed**

**Notes to physician** Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Carbon dioxide. Foam. Dry chemical.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

**Hazardous combustion products** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons. Chlorine. Fluorine.

#### **Protective equipment and precautions for firefighters**

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

## **6. ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

### **Environmental Precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

### **Methods and material for containment and cleaning up**

**Methods for containment** Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

**Methods for cleaning up** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## **7. HANDLING AND STORAGE**

### **Precautions for safe handling**

**Handling** Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### **Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

**Incompatible products** Acids. Bases. Amines. Strong oxidizing agents.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Control parameters**

#### **Exposure guidelines**

<b>Component</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>	<b>NIOSH IDLH</b>
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	1000 mg/m <sup>3</sup>
P-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup>	-	
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>

tert-BUTYL ACETATE 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>	1500 ppm
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

**Appropriate engineering controls**

**Engineering measures** Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.
- Skin and body protection** Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
- Respiratory protection** Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	aromatic
<b>Appearance</b>	opaque	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	
<b>pH</b>		No data available	
<b>Melting point / freezing point</b>		No data available	
<b>Boiling point / boiling range</b>	98 °C / 208.0 °F		
<b>Flash point</b>	35 °C / 95.0 °F		
<b>Evaporation rate</b>		Pensky Martens - Closed Cup	
<b>Flammability (solid, gas)</b>		No data available	
<b>Flammability Limit in Air</b>		No information available	
<b>Upper flammability limit</b>	N/A	No data available	
<b>Lower flammability limit</b>	N/A		
<b>Vapor pressure</b>		No data available	
<b>Vapor density</b>		No data available	
<b>Specific gravity</b>	1.46987	g/cm <sup>3</sup>	
<b>Water solubility</b>	Insoluble in cold water		
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	
<b>Kinematic viscosity</b>		No data available	
<b>Dynamic viscosity</b>	1700 centipoises	approx	

**Other Information**

Density	12.25872 lbs/gal
Volatile organic compounds (VOC) content	0.28741 lbs/gal
Total volatiles weight percent	25.9 %
Total volatiles volume percent	31.65 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to avoid

Heat, flames and sparks. Amines.

### Incompatible materials

Acids, Bases, Amines, Strong oxidizing agents

### Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes. Chlorine. Fluorine.

## 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

<b>Inhalation</b>	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin. May cause sensitization by skin contact.
<b>Ingestion</b>	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
P-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	= 500 mg/kg ( Rat )		
tert-BUTYL ACETATE 540-88-5	= 4100 mg/kg ( Rat )	> 2 g/kg ( Rabbit )	> 2230 mg/m <sup>3</sup> ( Rat ) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5000 mg/kg ( Rat )	= 14100 µL/kg ( Rabbit )	

### Information on toxicological effects

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to eyes and skin. Skin disorders.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Chronic Toxicity**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure). Substances known to impair fertility. Substances known to be mutagenic to man. Skin sensitizer.

**Sensitization**

May cause sensitization of susceptible persons.

**Mutagenicity**

May cause genetic defects.

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	A2	Group 1	Known	X
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3		

**Reproductive effects**

Suspected of damaging fertility or the unborn child.

**STOT - single exposure**

Skin, Central Nervous System (CNS), Eyes

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure

**Target organ effects**

Central nervous system, Central Vascular System (CVS), Eyes, Lungs, respiratory system, Skin.

**Aspiration hazard**

No information available.

**Acute Toxicity**

57.34295099 % of the mixture consists of ingredient(s) of unknown toxicity.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

38.64743 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
EPOXY RESIN (LER) 25085-99-8	11 mg/L 72 hr	2 mg/L 96 hr Oncorhynchus mykiss	1.8 mg/L 48h
P-CHLOROBENZOTRIFLUORIDE 98-56-6		11.5 - 15.8: 48 h Lepomis macrochirus mg/L LC50 static	3.68: 48 h Daphnia magna mg/L EC50
tert-BUTYL ACETATE 540-88-5		296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility in Environmental Media**

Component	log Pow
P-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
tert-BUTYL ACETATE 540-88-5	1.38
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63



BENZENE, 1,3-DIMETHYL 108-38-3	3.2
-----------------------------------	-----

**Other Adverse Effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal Methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. TRANSPORT INFORMATION

#### DOT

UN/ID no.	1263
Proper Shipping Name	paint
Hazard Class	3
Packing Group	III
Emergency Response Guide Number	128

#### IATA

UN/ID no.	1263
Proper Shipping Name	paint
Hazard Class	3
Packing Group	III
ERG Code	366

**Additional information** Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

### 15. REGULATORY INFORMATION

#### International Inventories

TSCA	Complies
DSL/NDSL	Does not comply
EINECS/ELINCS	Does not comply
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Does not comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

**Component**  
BENZENE, 1,3-DIMETHYL

**HAPS Data**

### United States of America

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

#### **SARA 311/312 Hazardous**

##### **Categorization**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
tert-BUTYL ACETATE 540-88-5				X
BENZENE, 1,3-DIMETHYL 108-38-3				X

#### **CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
tert-BUTYL ACETATE 540-88-5	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

### United States of America

#### **California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
CRYSTALLINE SILICA (QUARTZ) - 14808-60-7	Carcinogen

#### **California SCAQMD Rule 443**

Contains Photochemically Reactive Solvent

#### **State Right-to-Know**

Component	New Jersey	Massachusetts	Pennsylvania
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
P-CHLOROBENZOTRIFLUORIDE 98-56-6	X		X
CRYSTALLINE SILICA (QUARTZ) 14808-60-7	X	X	X
tert-BUTYL ACETATE 540-88-5	X	X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X

### **16. OTHER INFORMATION**

<b>NFPA</b>	Health 2	Flammability 3	Instability 1	Physical hazard *
<b>HMIS (Hazardous Material Information System)</b>	Health 2*	Flammability 3	Reactivity 1	

**Prepared By** Tnemec Regulatory Dept: 816-474-3400  
**Revision Date** 07-Jul-2015  
**Revision Summary**  
9 4 5 7 10 8 11 14

**Disclaimer**  
For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**