

Safety Data Sheet

Issue Date 04-Aug-2015

Revision Date 04-Aug-2015

Revision Number 9

1. IDENTIFICATION

Product identifier

Product Code N69F-00WHA
Product Name HB EPOXOLINE II TNEMEC WHITE

Other means of identification

Common Name SERIES N69F/V69F, PART A
UN/ID no. 1263

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Distributor Tnemec Company, Inc. 86 Boul, des Entreprises, Ste. 203 Boisbriand, Quebec Canada J7G 2T3

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Harmful if swallowed
Harmful if inhaled
Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause genetic defects
May cause cancer
Suspected of damaging fertility or the unborn child
May cause respiratory irritation. May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure
Flammable liquid and vapor
May be corrosive to metals

**Appearance** opaque**Physical state** liquid**Odor** aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. — No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/mixing/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Response

IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician
If skin irritation or rash occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth
In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

SEE SAFETY DATA SHEET

Acute Toxicity

32.68167 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	10 - 30%
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - 30%
TALC (RESPIRABLE DUST)	14807-96-6	10 - 30%
XYLENE	1330-20-7	1 - 10%
MODIFIED CYCLOALIPHATIC POLYAMINE	68953-36-6	1 - 10%
BENZYL ALCOHOL	100-51-6	1 - 10%
N-BUTANOL (SKIN)	71-36-3	1 - 10%
ETHYL BENZENE	100-41-4	1 - 10%
ISOPHORONE DIAMINE	2855-13-2	1 - 10%
MODIFIED ALIPHATIC AMINE	90-72-2	1 - 10%
AMORPHOUS SILICA	7631-86-9	1 - 10%
ALUMINUM HYDROXIDE	21645-51-2	0.1 - 1%
ZIRCONIUM OXIDE	1314-23-4	0.1 - 1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - 1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
Skin contact	Wash off immediately with soap and plenty of water. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide. Foam. Dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons. Oxides of nitrogen.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Strong oxidizing agents. Acids. Bases. Cleaning solutions such as Chromerge and Aqua Regia.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	

TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	5000 mg/m ³
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	
N-BUTANOL (SKIN) 71-36-3	TWA: 20 ppm	Skin Ceiling: 50 ppm Ceiling: 150 mg/m ³ TWA: 100 ppm TWA: 300 mg/m ³	1400 ppm
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	800 ppm
AMORPHOUS SILICA 7631-86-9	-	TWA: 6 mg/m ³	3000 mg/m ³
ALUMINUM HYDROXIDE 21645-51-2	TWA: 1 mg/m ³	-	
ZIRCONIUM OXIDE 1314-23-4	TWA: 5 mg/m ³	-	25 mg/m ³
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm

Appropriate engineering controls

Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	aromatic
Appearance	opaque	Odor threshold	No information available
Color	No information available		

Property	Values	Remarks
-----------------	---------------	----------------

pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	116 °C / 241.0 °F	
Flash point	26 °C / 78.0 °F	
Evaporation rate		Pensky Martens - Closed Cup
Flammability (solid, gas)		No data available
Flammability Limit in Air		Not applicable
Upper flammability limit	N/A	No data available
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.81849	g/cm ³
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	1100 centipoises	approx

Other Information

Density	15.13253 lbs/gal
Volatile organic compounds (VOC) content	2.507 lbs/gal
Total volatiles weight percent	16.5680 %
Total volatiles volume percent	35.0326 %

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Epoxy constituents.

Incompatible materials

Strong oxidizing agents, Acids, Bases, Cleaning solutions such as Chromerge and Aqua Regia

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Oxides of nitrogen. Aldehydes. Hydrocarbons. Carbon oxides.

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure**

Inhalation	Vapors may irritate throat and respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	Causes serious eye damage.
Skin contact	Irritating to skin. May cause sensitization by skin contact.
Ingestion	Harmful if swallowed.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	> 10000 mg/kg (Rat)		
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg (Rat)	= 2 g/kg (Rabbit)	= 8.8 mg/L (Rat) 4 h
N-BUTANOL (SKIN) 71-36-3	= 700 mg/kg (Rat) = 790 mg/kg (Rat)	= 3402 mg/kg (Rabbit) = 3400 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
ISOPHORONE DIAMINE 2855-13-2	= 1030 mg/kg (Rat)		
MODIFIED ALIPHATIC AMINE 90-72-2	= 1000 mg/kg (Rat)	= 1280 mg/kg (Rat)	
AMORPHOUS SILICA 7631-86-9	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
ALUMINUM HYDROXIDE 21645-51-2	> 5000 mg/kg (Rat)		
BENZENE, 1,3-DIMETHYL 108-38-3	= 5000 mg/kg (Rat)	= 14100 µL/kg (Rabbit)	

Information on toxicological effects

Symptoms

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity

Skin sensitizer. Substances known to be mutagenic to man. Substances known to impair fertility. May cause cancer. Avoid repeated exposure.

Sensitization

May cause sensitization of susceptible persons.

Mutagenicity

May cause genetic defects.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7		Group 2B		X
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		
XYLENE 1330-20-7		Group 3		
ETHYL BENZENE 100-41-4	A3	Group 2B		X
AMORPHOUS SILICA 7631-86-9		Group 3		
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3		

Reproductive effects

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Eyes, Central Nervous System (CNS), Skin

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure

Target organ effects

blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, kidney, liver, Lungs, respiratory system, Skin.

Aspiration hazard

No information available.

Acute Toxicity

32.68167 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

11.11656 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
-----------	-------------------	------------------	---------------------

TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
BENZYL ALCOHOL 100-51-6	35: 3 h Anabaena variabilis mg/L EC50	10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static	23: 48 h water flea mg/L EC50
N-BUTANOL (SKIN) 71-36-3	500: 96 h Desmodesmus subspicatus mg/L EC50 500: 72 h Desmodesmus subspicatus mg/L EC50	1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
ISOPHORONE DIAMINE 2855-13-2	37: 72 h Desmodesmus subspicatus mg/L EC50	110: 96 h Leuciscus idus mg/L LC50 semi-static	42: 24 h Daphnia magna mg/L EC50 14.6 - 21.5: 48 h Daphnia magna mg/L EC50 semi-static
AMORPHOUS SILICA 7631-86-9	440: 72 h Pseudokirchneriella subcapitata mg/L EC50	5000: 96 h Brachydanio rerio mg/L LC50 static	7600: 48 h Ceriodaphnia dubia mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Component	log Pow
XYLENE 1330-20-7	2.77
BENZYL ALCOHOL 100-51-6	1.1
N-BUTANOL (SKIN) 71-36-3	0.785
ETHYL BENZENE 100-41-4	3.118
ISOPHORONE DIAMINE 2855-13-2	0.79

MODIFIED ALIPHATIC AMINE 90-72-2	0.219
BENZENE, 1,3-DIMETHYL 108-38-3	3.2

Other Adverse Effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
N-BUTANOL (SKIN) 71-36-3		Included in waste stream: F039		U031
ETHYL BENZENE 100-41-4		Included in waste stream: F039		

Component	CAWAST
BARIUM SULFATE (TOTAL DUST) 7727-43-7	Toxic
XYLENE 1330-20-7	Toxic Ignitable
N-BUTANOL (SKIN) 71-36-3	Toxic
ETHYL BENZENE 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no. 1263
 Proper Shipping Name paint
 Hazard Class 3
 Packing Group III
 Emergency Response Guide Number 128

IATA

UN/ID no. 1263
 Proper Shipping Name paint
 Hazard Class 3
 Subsidiary Hazard Class III
 ERG Code 366

Additional information Call TNEMEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDL Complies

EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Does not comply
PICCS	Does not comply
AICS	Does not comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):
Component **HAPS Data**

XYLENE
 ETHYL BENZENE
 BENZENE, 1,3-DIMETHYL

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0
XYLENE - 1330-20-7	1.0
N-BUTANOL (SKIN) - 71-36-3	1.0
ETHYL BENZENE - 100-41-4	0.1
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,3-DIMETHYL 108-38-3				X

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
N-BUTANOL (SKIN) 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

United States of America

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
TITANIUM DIOXIDE (TOTAL DUST) - 13463-67-7	Carcinogen
ETHYL BENZENE - 100-41-4	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X
TITANIUM DIOXIDE (TOTAL DUST) 13463-67-7	X	X	X
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
XYLENE 1330-20-7	X	X	X
BENZYL ALCOHOL 100-51-6		X	X
N-BUTANOL (SKIN) 71-36-3	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
ISOPHORONE DIAMINE 2855-13-2	X		
AMORPHOUS SILICA 7631-86-9	X	X	X
ZIRCONIUM OXIDE 1314-23-4		X	
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X


16. OTHER INFORMATION

NFPA Health 2 Flammability 3 Instability 1 Physical hazard *
HMIS (Hazardous Material Information System) Health 2* Flammability 3 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 04-Aug-2015
 Revision Summary 9 4 5 7 10 8 2 11 14 1

Disclaimer
 For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.
 To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of SDS



Safety Data Sheet

Issue Date 26-Jun-2015

Revision Date 26-Jun-2015

Revision Number 9

1. IDENTIFICATION

Product identifier

Product Code N-69-0069B
Product Name H-B EPOXOLINE II CONVERTER

Other means of identification

Common Name SERIES N69/N69F, PART B
UN/ID no. 1263

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address
Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)
Emergency Telephone United States: 800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT:
816-474-3400

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
 Causes serious eye irritation
 May cause an allergic skin reaction
 May cause genetic defects
 May cause cancer
 May damage fertility or the unborn child
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Flammable liquid and vapor

**Appearance** opaque**Physical state** liquid**Odor** Slight**Precautionary Statements****Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Response

IF exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 If skin irritation or rash occurs: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep cool
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

Toxic to aquatic life with long lasting effects
 SEE SAFETY DATA SHEET

Acute Toxicity

26.1844305 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
TALC (RESPIRABLE DUST)	14807-96-6	30 - 60%
EPOXY RESIN (LER)	25085-99-8	10 - 30%
SOLID EPOXY RESIN	-	10 - 30%
BARIUM SULFATE (TOTAL DUST)	7727-43-7	1 - 10%
XYLENE	1330-20-7	1 - 10%
METHYL ISOBUTYL KETONE	108-10-1	1 - 10%
AROMATIC HYDROCARBON MIXTURE	64742-95-6	1 - 10%
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - 10%
ETHYL BENZENE	100-41-4	1 - 10%
BENZENE, 1,4-DIMETHYL	106-42-3	0.1 - 1%
1,3,5-TRIMETHYLBENZENE	108-67-8	0.1 - 1%
BENZENE, 1,3-DIMETHYL	108-38-3	0.1 - 1%
BENZENE, 1,2-DIMETHYL	95-47-6	0.1 - 1%
(1-METHYLETHYL)BENZENE	-	0.1 - 1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Most important symptoms and effects Breathing difficulties.

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam, carbon dioxide, and dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon oxides. Hydrocarbons. Aldehydes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Acids. Bases. Amines. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC (RESPIRABLE DUST) 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	1000 mg/m ³
BARIUM SULFATE (TOTAL DUST) 7727-43-7	TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	

XYLENE 1330-20-7	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³	
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³ TWA: 100 ppm TWA: 410 mg/m ³	500 ppm
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	800 ppm
BENZENE, 1,4-DIMETHYL 106-42-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm
BENZENE, 1,3-DIMETHYL 108-38-3	TWA: 100 ppm STEL: 150 ppm	-	900 ppm
BENZENE, 1,2-DIMETHYL 95-47-6	TWA: 100 ppm STEL: 150 ppm	-	900 ppm
(1-METHYLETHYL)BENZENE	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ Skin	900 ppm

Appropriate engineering controls

Engineering measures

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use chemical resistant splash type goggles. If splashes are likely to occur, wear face-shield.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Slight
Appearance	opaque	Odor threshold	No information available
Color	No information available		
Property	Values	Remarks	
pH		No data available	

Melting point / freezing point		No data available
Boiling point / boiling range	114 °C / 237.0 °F	
Flash point	27 °C / 80.0 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)		No information available
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	1.0	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	1.44716	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	1100 centipoises	approx

Other Information

Density	12.06934 lbs/gal
Volatile organic compounds (VOC) content	2.11938 lbs/gal
Total volatiles weight percent	17.56 %
Total volatiles volume percent	29.86 %

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Amines.

Incompatible materials

Acids, Bases, Amines, Strong oxidizing agents

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Aldehydes. Carbon oxides. Hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	HARMFUL BY INHALATION.
Eye contact	Causes serious eye irritation.
Skin contact	Irritating to skin. May cause sensitization by skin contact.
Ingestion	Harmful if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
-----------	-----------	-------------	-----------------

XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
AROMATIC HYDROCARBON MIXTURE 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
BENZENE, 1,4-DIMETHYL 106-42-3	= 4029 mg/kg (Rat)		= 4740 ppm (Rat) 4 h = 4550 ppm (Rat) 4 h
1,3,5-TRIMETHYLBENZENE 108-67-8	= 5000 mg/kg (Rat)		= 24 g/m ³ (Rat) 4 h
BENZENE, 1,3-DIMETHYL 108-38-3	= 5000 mg/kg (Rat)	= 14100 µL/kg (Rabbit)	
BENZENE, 1,2-DIMETHYL 95-47-6	= 3608 mg/kg (Rat)	= 14100 mg/kg (Rabbit)	= 4330 ppm (Rat) 6 h
(1-METHYLETHYL)BENZENE	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h = 39000 mg/m ³ (Rat) 4 h

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Substances known to impair fertility. Substances known to be mutagenic to man. Skin sensitizer. May cause cancer.

Sensitization May cause sensitization of susceptible persons.

Mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
TALC (RESPIRABLE DUST) 14807-96-6		Group 3		
XYLENE 1330-20-7		Group 3		
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B		X
ETHYL BENZENE 100-41-4	A3	Group 2B		X
BENZENE, 1,4-DIMETHYL 106-42-3		Group 3		
BENZENE, 1,3-DIMETHYL 108-38-3		Group 3		
BENZENE, 1,2-DIMETHYL 95-47-6		Group 3		
(1-METHYLETHYL)BENZENE		Group 2B	Reasonably Anticipated	X

Reproductive effects May damage fertility or the unborn child.

STOT - single exposure No information available

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure
Target organ effects blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, kidney, liver, respiratory system, Skin.

Aspiration hazard Risk of serious damage to the lungs (by aspiration).

Acute Toxicity 26.1844305 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

18.01842 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
TALC (RESPIRABLE DUST) 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
EPOXY RESIN (LER) 25085-99-8	11 mg/L 72 hr	2 mg/L 96 hr Oncorhynchus mykiss	1.8 mg/L 48h
XYLENE 1330-20-7		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96 h LC50 23.53 - 29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50 > 780 mg/L Cyprinus carpio 96 h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
AROMATIC HYDROCARBON MIXTURE 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-TRIMETHYLBENZENE 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
ETHYL BENZENE 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
BENZENE, 1,4-DIMETHYL 106-42-3	3.2: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 105.1: 3 h Chlorella vulgaris mg/L EC50	2.6: 96 h Oncorhynchus mykiss mg/L LC50 8.8: 96 h Poecilia reticulata mg/L LC50 semi-static 7.2 - 9.9: 96 h Pimephales promelas mg/L LC50 static 2.6: 96 h Oncorhynchus mykiss mg/L LC50 static	3.55 - 6.31: 48 h Daphnia magna mg/L EC50 Static
1,3,5-TRIMETHYLBENZENE 108-67-8		3.48: 96 h Pimephales promelas mg/L LC50	50: 24 h Daphnia magna mg/L EC50
BENZENE, 1,3-DIMETHYL 108-38-3	4.9: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	8.4: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 14.3 - 18: 96 h Pimephales promelas mg/L LC50 flow-through 12.9: 96 h Poecilia reticulata mg/L LC50 semi-static	2.81 - 5.0: 48 h Daphnia magna mg/L EC50 Static
BENZENE, 1,2-DIMETHYL 95-47-6	4.2: 192 h Pseudokirchneriella subcapitata mg/L EC50 4.7: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	11.6 - 22.4: 96 h Pimephales promelas mg/L LC50 flow-through 12: 96 h Poecilia reticulata mg/L LC50 11.6 - 22.4: 96 h Lepomis macrochirus mg/L LC50 flow-through 5.59 - 11.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	3.2: 48 h Daphnia magna mg/L EC50 0.78 - 2.51: 48 h Daphnia magna mg/L EC50 Static 2.61 - 5.59: 48 h Daphnia magna mg/L EC50 Flow through

(1-METHYLETHYL)BENZENE	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static
------------------------	---	---	---

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Component	log Pow
XYLENE 1330-20-7	2.77
METHYL ISOBUTYL KETONE 108-10-1	1.19
1,2,4-TRIMETHYLBENZENE 95-63-6	3.63
ETHYL BENZENE 100-41-4	3.118
BENZENE, 1,4-DIMETHYL 106-42-3	3.15
BENZENE, 1,3-DIMETHYL 108-38-3	3.2
BENZENE, 1,2-DIMETHYL 95-47-6	3.12
(1-METHYLETHYL)BENZENE	3.55

Other Adverse Effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE 1330-20-7		Included in waste stream: F039		U239
METHYL ISOBUTYL KETONE 108-10-1		Included in waste stream: F039		U161
ETHYL BENZENE 100-41-4		Included in waste stream: F039		
(1-METHYLETHYL)BENZE NE				U055

Component	CAWAST
BARIUM SULFATE (TOTAL DUST) 7727-43-7	Toxic
XYLENE 1330-20-7	Toxic Ignitable

ETHYL BENZENE 100-41-4	Toxic Ignitable
(1-METHYLETHYL)BENZENE	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no.	1263
Proper Shipping Name	paint
Hazard Class	3
Packing Group	III
Emergency Response Guide Number	1285

IATA

UN/ID no.	1263
Proper Shipping Name	paint
Hazard Class	3
Packing Group	III
ERG Code	366

Additional information

Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Does not comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component

HAPS Data

XYLENE

METHYL ISOBUTYL KETONE

ETHYL BENZENE

BENZENE, 1,4-DIMETHYL

BENZENE, 1,3-DIMETHYL

BENZENE, 1,2-DIMETHYL

(1-METHYLETHYL)BENZENE

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST) - 7727-43-7	1.0
XYLENE - 1330-20-7	1.0
METHYL ISOBUTYL KETONE - 108-10-1	1.0
1,2,4-TRIMETHYLBENZENE - 95-63-6	1.0
ETHYL BENZENE - 100-41-4	0.1
BENZENE, 1,4-DIMETHYL - 106-42-3	1.0
BENZENE, 1,3-DIMETHYL - 108-38-3	1.0
BENZENE, 1,2-DIMETHYL - 95-47-6	1.0
(1-METHYLETHYL)BENZENE -	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3				X
BENZENE, 1,3-DIMETHYL 108-38-3				X
BENZENE, 1,2-DIMETHYL 95-47-6				X

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,4-DIMETHYL 106-42-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
BENZENE, 1,3-DIMETHYL 108-38-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE, 1,2-DIMETHYL 95-47-6	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
(1-METHYLETHYL)BENZENE	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

United States of America

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental
ETHYL BENZENE - 100-41-4	Carcinogen
(1-METHYLETHYL)BENZENE -	Carcinogen

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
TALC (RESPIRABLE DUST) 14807-96-6	X	X	X
BARIUM SULFATE (TOTAL DUST) 7727-43-7	X	X	X
XYLENE 1330-20-7	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE, 1,4-DIMETHYL 106-42-3	X	X	X
1,3,5-TRIMETHYLBENZENE 108-67-8		X	
BENZENE, 1,3-DIMETHYL 108-38-3	X	X	X
BENZENE, 1,2-DIMETHYL 95-47-6	X	X	X
(1-METHYLETHYL)BENZENE	X	X	X

16. OTHER INFORMATION**NFPA**

Health 2

Flammability 3

Instability 1

Physical hazard *

HMIS (Hazardous

Health 2*

Flammability 3

Reactivity 1

Material Information**System)**

Prepared By

Tnemec Regulatory Dept: 816-474-3400

Revision Date

26-Jun-2015

Revision Summary

9 4 5 7 10 8 11 14

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS