



# Material Safety Data Sheet

Print Date 20-May-2011

Revision Date 20-May-2011

Revision Number 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Common name</b>	SERIES 114 PART A
<b>Product code</b>	F114-11WHA
<b>Trade name</b>	HBTNEMETUFCOAT WHITE
<b>Product Class</b>	ACRYLIC PAINT
<b>Manufacturer</b>	Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
<b>Emergency telephone</b>	800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

#### WARNING!

COMBUSTIBLE LIQUID AND VAPOR.  
HARMFUL IF INHALED.  
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.  
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.  
MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

#### Potential health effects

**Principle Routes of Exposure** Eye contact, Inhalation, Skin contact.

#### Acute effects

<b>Eyes</b>	Moderately irritating to the eyes.
<b>Skin</b>	Irritating to skin.
<b>Inhalation</b>	Irritating to respiratory system.
<b>Ingestion</b>	May be harmful if swallowed.

#### Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** Central nervous system. Gastrointestinal tract. Kidney disorders. Liver disorders. Skin disorders. Respiratory disorders.

**Interactive effects** Use of alcoholic beverages may enhance toxic effects.

**Potential environmental effects** See Section 12 for additional Ecological Information

**Target Organ Effects** Blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, Kidney, Liver, Lungs, Respiratory system, Skin

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous Components

Component	CAS-No	Weight %
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - 30
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	2807-30-9	5 - 10
AMORPHOUS SILICA	7631-86-9	1 - 5
ALUMINUM OXIDES	1344-28-1	1 - 5
TRIETHYLAMINE	121-44-8	1 - 5
XYLENE	1330-20-7	1 - 5
FULLER'S EARTH (TOTAL DUST)	8031-18-3	1 - 5

### 4. FIRST AID MEASURES

<b>Eye contact:</b>	Rinse thoroughly with plenty of water for at least 15 minutes.
<b>Skin contact:</b>	Wash off immediately with soap and plenty of water.
<b>Ingestion:</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Inhalation:</b>	Move to fresh air. Oxygen or artificial respiration if needed.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable properties</b>	Combustible material.
<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO <sub>2</sub> ) - Foam - Dry chemical
<b>Hazardous decomposition products</b>	Oxides of carbon, hydrocarbons. formaldehyde.
<b>Specific hazards arising from the chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.
<b>Protective equipment and precautions for firefighters</b>	Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
<b>Methods for cleaning up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Other information</b>	Not applicable

7. HANDLING AND STORAGE

**Handling**

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Storage**

Close container after each use. Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
TITANIUM DIOXIDE (TOTAL DUST)	: 10 mg/m <sup>3</sup> TWA	: 10 mg/m <sup>3</sup> TWA (total dust); 15 mg/m <sup>3</sup> TWA (total dust)	TWA: 10 mg/m <sup>3</sup> TWAEV (total dust, containing no asbestos and less than 1% crystalline silica)	TWA: 10 mg/m <sup>3</sup> TWA (total dust)	: 10 mg/m <sup>3</sup> TWA (as Ti); 20 mg/m <sup>3</sup> STEL (as Ti)
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)				TWA: 25 ppm TWA; 110 mg/m <sup>3</sup> TWA Skin	
ALUMINUM OXIDES	TWA: 1 mg/m <sup>3</sup>	: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	TWA: 10 mg/m <sup>3</sup> TWAEV (total dust, containing no asbestos and less than 1% crystalline silica, as Al)	TWA: 10 mg/m <sup>3</sup>	: 10 mg/m <sup>3</sup> TWA
TRIETHYLAMINE	: 1 ppm TWA Skin : 3 ppm STEL	: 10 ppm TWA; 40 mg/m <sup>3</sup> TWA : 15 ppm STEL; 60 mg/m <sup>3</sup> STEL : 25 ppm TWA; 100 mg/m <sup>3</sup> TWA	TWA: 5 ppm TWAEV; 20.5 mg/m <sup>3</sup> TWAEV STEL: 15 ppm STEV; 61.5 mg/m <sup>3</sup> STEV Skin	TWA: 1 ppm TWA STEL: 3 ppm STEL Skin	: 25 ppm TWA; 100 mg/m <sup>3</sup> TWA : 40 ppm STEL; 160 mg/m <sup>3</sup> STEL
XYLENE	: 100 ppm TWA : 150 ppm STEL	: 100 ppm TWA; 435 mg/m <sup>3</sup> TWA : 150 ppm STEL; 655 mg/m <sup>3</sup> STEL	TWA: 100 ppm TWAEV; 434 mg/m <sup>3</sup> TWAEV STEL: 150 ppm STEV; 651 mg/m <sup>3</sup> STEV	TWA: 100 ppm TWA STEL: 150 ppm STEL	: 100 ppm TWA; 435 mg/m <sup>3</sup> TWA : 150 ppm STEL; 655 mg/m <sup>3</sup> STEL

**Engineering measures**

Ensure adequate ventilation, especially in confined areas

**Personal Protective Equipment**

**Skin protection**

Lightweight protective clothing, Apron, Impervious gloves

**Eye/face protection**

Safety glasses with side-shields

**Respiratory protection**

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

**Flash point**

88°C / 190.0°F

**Boiling range**

85 - 154°C / 185.0 - 310.0°F

**Upper explosion limit**

No information available

9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Lower explosion limit</b>	No information available
<b>Evaporation rate</b>	No information available
<b>Vapor pressure</b>	No information available
<b>Vapor density</b>	No information available
<b>Specific Gravity</b>	1.27581 g/cm <sup>3</sup>
<b>Density</b>	10.61664 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	2.039 lbs/gal
<b>Volatile by weight</b>	46.0560 %
<b>Volatile by volume</b>	60.9242 %

10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable.	<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Incompatible products</b>	Strong oxidizing agents. Acids.	<b>Possibility of hazardous reactions</b>	None under normal processing

11. TOXICOLOGICAL INFORMATION

**Acute toxicity**

**Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
WATER	90 mL/kg ( Rat )		
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg ( Rat )		
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	3089 mg/kg ( Rat )	960 µL/kg ( Rabbit )	
AMORPHOUS SILICA	5000 mg/kg ( Rat )	2000 mg/kg ( Rabbit )	2.2 mg/L ( Rat ) 1 h
ALUMINUM OXIDES	5000 mg/kg ( Rat )		
TRIETHYLAMINE	460 mg/kg ( Rat )	416 mg/kg ( Rabbit ) 570 µL/kg ( Rabbit )	0.42 mg/L ( Rat ) 1 h 3496 ppm ( Rat ) 1 h
XYLENE	4300 mg/kg ( Rat )	1700 mg/kg ( Rabbit )	5000 ppm ( Rat ) 4 h 47635 mg/L ( Rat ) 4 h

<b>Irritation</b>	No information available
<b>Corrosivity</b>	No information available
<b>Sensitization</b>	No information available

**Chronic toxicity**

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	

<b>Mutagenicity</b>	No information available
<b>Reproductive effects</b>	No information available
<b>Developmental effects</b>	No information available
<b>Teratogenicity</b>	No information available
<b>Target Organ Effects</b>	Blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, Kidney, Liver, Lungs, Respiratory system, Skin.
<b>Endocrine Disruptor Information</b>	No information available

12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
AMORPHOUS SILICA	EC50 = 440 mg/L 72 h	LC50= 5000 mg/L Brachydanio rerio 96 h		EC50 = 7600 mg/L 48 h
TRIETHYLAMINE		LC50= 43.7 mg/L Pimephales promelas 96 h	EC50 = 95 mg/L 17 h EC50 = 127 mg/L 2 h	EC50 = 200 mg/L 48 h
XYLENE		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661-4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5-17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1-16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711-9.591 mg/L Lepomis macrochirus 96 h LC50 23.53-29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26-40.75 mg/L Poecilia reticulata 96 h	EC50 = 0.0084 mg/L 24 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

**Waste disposal methods**

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

**DOT**

Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

**Proper shipping name**

PAINT,WATER BASE FREEZABLE

15. REGULATORY INFORMATION

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Complies
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Complies
AICS	Complies

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):  
Component



**WHMIS Classification**

B3 Combustible liquid  
D2B Toxic materials



Component	NPRI
ALUMINUM OXIDES	Part 1, Group 1 Substance (fibrous form)
TRIETHYLAMINE	Part 1, Group 1 Substance
XYLENE	Part 1, Group 1 Substance; Part 5 Substance

**Legend**

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date 20-May-2011

Revision Note No information available

HMIS (Hazardous Material Information System)      Health 2      Flammability 2      Reactivity 1

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Material Safety Data Sheet

Print Date 19-May-2011

Revision Date 19-May-2011

Revision Number 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Common name</b>	SERIES 113 PART B
<b>Product code</b>	B113-0113B
<b>Trade name</b>	113/114 TNEME-TUFCOAT CONVERT
<b>Product Class</b>	EPOXY PAINT
<b>Manufacturer</b>	Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
<b>Emergency telephone</b>	800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

#### DANGER!

COMBUSTIBLE LIQUID AND VAPOR.  
HARMFUL OR FATAL IF SWALLOWED.  
HARMFUL IF INHALED.  
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT.  
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.  
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.  
MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

#### Potential health effects

**Principle Routes of Exposure** Eye contact, Inhalation, Skin contact.

#### Acute effects

<b>Eyes</b>	Moderately irritating to the eyes.
<b>Skin</b>	Irritating to skin. May cause sensitization by skin contact.
<b>Inhalation</b>	Irritating to respiratory system.
<b>Ingestion</b>	May be harmful if swallowed.

#### Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** No information available

**Interactive effects** Use of alcoholic beverages may enhance toxic effects.

**Potential environmental effects** See Section 12 for additional Ecological Information

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Hazardous Components

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
EPOXY RESIN (LER)	25085-99-8	60 - 100
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	2807-30-9	10 - 30

### 4. FIRST AID MEASURES

<b>Eye contact:</b>	Rinse thoroughly with plenty of water for at least 15 minutes.
<b>Skin contact:</b>	Wash off immediately with soap and plenty of water.
<b>Ingestion:</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Inhalation:</b>	Move to fresh air. Oxygen or artificial respiration if needed.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable properties</b>	Combustible material.
<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO <sub>2</sub> ) - Foam - Dry chemical
<b>Hazardous decomposition products</b>	Oxides of carbon, hydrocarbons. Aldehydes.

#### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

#### Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
<b>Methods for cleaning up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Other information</b>	Not applicable

### 7. HANDLING AND STORAGE

#### Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Storage**

Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)				TWA: 25 ppm TWA; 110 mg/m <sup>3</sup> TWA Skin	

**Engineering measures**

Ensure adequate ventilation, especially in confined areas

**Personal Protective Equipment**

**Skin protection**

Lightweight protective clothing, Apron, Impervious gloves

**Eye/face protection**

If splashes are likely to occur, wear Goggles.

**Respiratory protection**

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Flash point</b>	57°C / 135.0°F
<b>Method</b>	Pensky Martens - Closed Cup
<b>Boiling range</b>	149 - 154°C / 301.0 - 310.0°F
<b>Upper explosion limit</b>	No information available
<b>Lower explosion limit</b>	No information available
<b>Evaporation rate</b>	No information available
<b>Vapor pressure</b>	No information available
<b>Vapor density</b>	No information available
<b>Specific Gravity</b>	1.08771 g/cm <sup>3</sup>
<b>Density</b>	9.05139 lbs/gal
<b>Volatile organic compounds (VOC) content</b>	2.219 lbs/gal
<b>Volatile by weight</b>	24.5180 %
<b>Volatile by volume</b>	29.2000 %

**10. STABILITY AND REACTIVITY**

<b>Chemical stability</b>	Stable.	<b>Conditions to avoid</b>	Heat, flames and sparks. Amines.
<b>Incompatible products</b>	Strong oxidizing agents. Bases. Acids. Amines.	<b>Possibility of hazardous reactions</b>	None under normal processing

**11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

## 11. TOXICOLOGICAL INFORMATION

### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	3089 mg/kg ( Rat )	960 µL/kg ( Rabbit )	

**Irritation** No information available  
**Corrosivity** No information available  
**Sensitization** No information available

### Chronic toxicity

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen

**Mutagenicity** No information available  
**Reproductive effects** No information available  
**Developmental effects** No information available  
**Teratogenicity** No information available  
**Target Organ Effects** No information available  
**Endocrine Disruptor Information** No information available

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
EPOXY RESIN (LER)	Group III Chemical		

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

## 13. DISPOSAL CONSIDERATIONS

**Waste disposal methods** Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Contaminated packaging** Empty containers should be taken for local recycling, recovery or waste disposal

## 14. TRANSPORT INFORMATION

**DOT** Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

**Proper shipping name** PAINT IN OIL

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA** Complies  
**DSL/NDL** Complies  
**EINECS/ELINCS** Does not Comply

CHINA Complies  
 ENCS Does not Comply  
 KECL Complies  
 PICCS Complies  
 AICS Complies

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component  
 ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)

**United States of America Federal Regulations**

**SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)	2807-30-9	10 - 30	1.0

**SARA 311/312 Hazardous Categorization**

Chronic Health Hazard no  
 Acute Health Hazard yes  
 Fire Hazard yes  
 Sudden Release of Pressure Hazard no  
 Reactive Hazard no

**CERCLA**

**United States of America State Regulations**

**California Prop. 65**

This product contains the following Proposition 65 chemicals:

**State Right-to-Know**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ETHYLENE GLYCOL MONOPROPYL ETHER (SKIN)		X	X	X	

**Other international regulations**

**Canada**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**WHMIS Classification**

B3 Combustible liquid  
 D2A Very toxic materials



**Legend**

NPRI - National Pollutant Release Inventory

