



# Material Safety Data Sheet

Preparation Date: 09-Apr-2010

Revision Date: 09-Apr-2010

Revision Number: 0

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Code** 1254-1202A  
**Trade Name** EPOXOBLOCK WB OFF-WHITE  
**Contact Manufacturer** TNE MEC Company, Inc.  
123 West 23rd Avenue  
North Kansas City, MO 64116-3064  
816-474-3400  
**Emergency Telephone Number** 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

#### DANGER!

CAUSES SKIN AND EYE BURNS.  
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT.  
MAY CAUSE SENSITIZATION BY SKIN CONTACT.

#### Potential Health Effects

**Principle Routes of Exposure** Skin contact, Inhalation.

**Acute Effects**

**Eyes** Irritating to eyes. Causes burns.

**Skin** Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact. Causes burns.

**Inhalation** May cause irritation of respiratory tract. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### Chronic Effects

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)  
NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** Central nervous system. Kidney disorders. Liver disorders. Skin disorders.

**Interactions with Other Chemicals** Use of alcoholic beverages may enhance toxic effects.

**Potential Environmental Effects** See Section 12 for additional Ecological information

**Target Organ Effects** Blood, Central nervous system, Central Vascular System, Eyes, Kidney, Liver, Lungs, Nasal Cavities, Prostate, Respiratory system, Skin

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous Components

Component	CAS-No	Weight %
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - 30
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	12.7009
BARIUM SULFATE (TOTAL DUST)	7727-43-7	5 - 10
AMORPHOUS CALCIUM ALUMINOSILICATE	65997-17-3	5 - 10
AMORPHOUS SILICA	7631-86-9	1 - 5
ALUMINUM OXIDES	1344-28-1	1 - 5
MODIFIED ALIPHATIC AMINE	1477-55-0	1 - 5

### 4. FIRST AID MEASURES

<b>Eye Contact</b>	Flush immediately with large amounts of clean water under low pressure for at least 15 minutes. Consult a physician.
<b>Skin Contact</b>	Wash affected area with soap and water. Remove contaminated clothing. Dispose of or launder accordingly. Consult a physician if skin irritation persists.
<b>Ingestion</b>	Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center IMMEDIATELY. Treat symptomatically.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	No information available
<b>Suitable Extinguishing Media</b>	Foam, carbon dioxide, and dry chemical.
<b>Hazardous Decomposition Products</b>	Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ). Hydrocarbons.
<b>Specific Hazards Arising from the Chemical</b>	Keep product and empty container away from heat and sources of ignition
<b>Protective Equipment and Precautions for Firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove all sources of ignition. Use personal protective equipment.
<b>Environmental Precautions</b>	Prevent further leakage or spillage if safe to do so
<b>Methods for Cleaning Up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Other Information</b>	Not applicable

## 7. HANDLING AND STORAGE

### Handling

Handle in accordance with good industrial hygiene and safety practice. Store in dry area. Keep closures tight and upright to prevent leakage. Do not store in high temperature areas or near fire or open flame. Refer to product data sheet for recommended storage temperatures.

### Storage

Keep containers tightly closed in a cool, well-ventilated place

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
TITANIUM DIOXIDE (TOTAL DUST)	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
BARIUM SULFATE (TOTAL DUST)	TWA: 0.5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup> TWA: 10 ppm TWA: 5 ppm	TWA: 10 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>
AMORPHOUS CALCIUM ALUMINOSILICATE	TWA: 1 fiber/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup> TWA: 0.05 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup> TWA: 0.01 mg/m <sup>3</sup> TWA: 0.002 mg/m <sup>3</sup>	Ceiling: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 1 fibre/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup> TWA: 0.05 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup> TWA: 0.02 mg/m <sup>3</sup> TWA: 0.025 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 1 fibres/cm <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> TWA: 0.01 mg/m <sup>3</sup> TWA: 0.002 mg/m <sup>3</sup> TWA: 0.05 mg/m <sup>3</sup> STEL: 0.6 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 0.15 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 0.002 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
ALUMINUM OXIDES	TWA: 1 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
MODIFIED ALIPHATIC AMINE	Skin Ceiling: 0.1 mg/m <sup>3</sup>	Skin Ceiling: 0.1 mg/m <sup>3</sup>	Ceiling: 0.1 mg/m <sup>3</sup> Skin	CEV: 0.1 mg/m <sup>3</sup> Skin	Peak: 0.1 mg/m <sup>3</sup>

### Engineering Measures

Ensure adequate ventilation, especially in confined areas

### Personal Protective Equipment

#### Skin Protection

Wear protective gloves/clothing.

#### Eye/face Protection

Tightly fitting safety goggles

#### Respiratory Protection

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

#### General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Flash Point

Not applicable

#### Boiling Point/Range

100 - -18°C / 212.0 - .0°F

#### Upper Exposure Limits

No information available

#### Lower Exposure Limits

No information available

#### Evaporation Rate

No information available

#### Vapour Pressure

No information available

#### Vapour Density

No information available

#### Specific Gravity

1.78915

#### Density

14.88843

#### VOC Content (lbs/gal)

.000

#### % Volatile by Weight

29.6010

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**% Volatile by Volume** 52.9069

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable.	<b>Conditions to Avoid</b>	Heat, flames and sparks
<b>Incompatible Products</b>	Acids. Bases. Strong oxidizing agents. Reducing agents.	<b>Possibility of Hazardous Reactions</b>	None under normal processing

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg ( Rat )		
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg ( Rat )		
AMORPHOUS SILICA	5000 mg/kg ( Rat )	2000 mg/kg ( Rabbit )	2.2 mg/L ( Rat ) 1 h
ALUMINUM OXIDES	5000 mg/kg ( Rat )		
MODIFIED ALIPHATIC AMINE	930 mg/kg ( Rat )	2000 mg/kg ( Rabbit )	700 ppm ( Rat ) 1 h

<b>Irritation</b>	No information available
<b>Corrosivity</b>	No information available
<b>Sensitization</b>	No information available

### Chronic Toxicity

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	
AMORPHOUS CALCIUM ALUMINOSILICATE		Group 1 Group 2A			

<b>Mutagenic Effects</b>	No information available
<b>Reproductive Effects</b>	No information available
<b>Developmental Effects</b>	No information available
<b>Teratogenicity</b>	No information available
<b>Target Organ Effects</b>	Blood, Central nervous system, Central Vascular System, Eyes, Kidney, Liver, Lungs, Nasal Cavities, Prostate, Respiratory system, Skin.
<b>Endocrine Disruptor Information</b>	No information available

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
AMORPHOUS CALCIUM ALUMINOSILICATE		LC50 5.6 - 7.4 µg/L Pimephales promelas 96 h LC50 9.4 - 9.7 µg/L Pimephales promelas 96 h LC50 24.2 - 48.4 µg/L Lepomis macrochirus 96 h		EC50 = 0.9 µg/L 48 h LC50 = 5 µg/L 96 h LC50 1.4 - 2.3 µg/L 96 h
AMORPHOUS SILICA	EC50 = 440 mg/L 72 h	LC50= 5000 mg/L Brachydanio rerio 96 h		EC50 = 7600 mg/L 48 h

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** In accordance with local and national regulations

**Contaminated Packaging** Empty containers should be taken for local recycling, recovery or waste disposal

### 14. TRANSPORT INFORMATION

**DOT** Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

**Proper Shipping Name** PAINT, WATER BASE FREEZABLE

### 15. REGULATORY INFORMATION

#### International Inventories

**TSCA** Complies  
**DSL/NDL** Does not Comply

**EINECS/ELINCS** Does not Comply  
**CHINA** Does not Comply  
**ENCS** Does not Comply  
**KECL** Does not Comply  
**PICCS** Does not Comply  
**AICS** Does not Comply

#### **Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

#### U.S. Federal Regulations

#### SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST)	7727-43-7	5 - 10	1.0
ALUMINUM OXIDES	1344-28-1	1 - 5	1.0

#### SARA 311/312 Hazardous Categorization

**Chronic Health Hazard** No  
**Acute Health Hazard** No  
**Fire Hazard** No  
**Sudden Release of Pressure Hazard** No  
**Reactive Hazard** No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
AMORPHOUS CALCIUM ALUMINOSILICATE		X		

**CERCLA****U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen
AMORPHOUS CALCIUM ALUMINOSILICATE	65997-17-3	Carcinogen

**State Right-to-Know**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
TITANIUM DIOXIDE (TOTAL DUST)	X	X	X		X
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
BARIUM SULFATE (TOTAL DUST)	X	X	X		X
AMORPHOUS CALCIUM ALUMINOSILICATE	X	X	X	X	X
AMORPHOUS SILICA	X		X		
ALUMINUM OXIDES	X	X	X		X
MODIFIED ALIPHATIC AMINE	X	X	X		X

**Other International Regulations****Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class**

Non-controlled

Component	NPRI
ALUMINUM OXIDES	Part 1, Group 1 Substance (fibrous form)

<b>16. OTHER INFORMATION</b>
------------------------------

Revision Date: 09-Apr-2010

Revision Summary: No information available


HMIS: Health 3                      Flammability 1                      Reactivity 1

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**



# Material Safety Data Sheet

Preparation Date: 09-Apr-2010

Revision Date: 09-Apr-2010

Revision Number: 0

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Code** 1254-1254B  
**Trade Name** EPOXOBLOCK WB CONVERTER  
**Contact Manufacturer** TNEMEC Company, Inc.  
123 West 23rd Avenue  
North Kansas City, MO 64116-3064  
816-474-3400  
**Emergency Telephone Number** 800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

#### CAUTION

MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT.  
MAY CAUSE SENSITIZATION BY SKIN CONTACT.  
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.  
MAY CAUSE EYE INJURY.

#### Potential Health Effects

**Principle Routes of Exposure** Skin contact, Inhalation.

#### Acute Effects

##### Eyes

Irritating to eyes. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible tissue (skin, eye, respiratory tract) damage due to chemical (caustic) burns, including third degree burns. May cause eye injury.

##### Skin

May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible tissue (skin, eye, respiratory tract) damage due to chemical (caustic) burns, including third degree burns.

##### Inhalation

Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible tissue (skin, eye, respiratory tract) damage due to chemical (caustic) burns, including third degree burns.

##### Ingestion

May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea..

#### Chronic Effects

Avoid repeated exposure Repeated contact may cause allergic reactions in very susceptible persons Prolonged exposure may cause chronic effects NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

<b>Aggravated Medical Conditions</b>	Skin disorders. Allergies.
<b>Interactions with Other Chemicals</b>	No information available
<b>Potential Environmental Effects</b>	See Section 12 for additional Ecological information

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous Components

Component	CAS-No	Weight %
CALCIUM ALUMINATE CEMENT	65997-16-2	30 - 60
BISPHENOL A TYPE EPOXY RESIN	25085-99-8	30 - 60

### 4. FIRST AID MEASURES

<b>Eye Contact</b>	Flush immediately with large amounts of clean water under low pressure for at least 15 minutes. Consult a physician.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
<b>Ingestion</b>	Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center IMMEDIATELY. Treat symptomatically.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	No information available
<b>Suitable Extinguishing Media</b>	Foam, carbon dioxide, and dry chemical.
<b>Hazardous Decomposition Products</b>	Oxides of carbon, hydrocarbons. Aldehydes.

#### Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Ensure adequate ventilation
<b>Environmental Precautions</b>	Prevent further leakage or spillage if safe to do so
<b>Methods for Cleaning Up</b>	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Other Information</b>	Not applicable

## 7. HANDLING AND STORAGE

**Handling**

Handle in accordance with good industrial hygiene and safety practice.

**Storage**

Keep containers tightly closed in a cool, well-ventilated place

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas

**Personal Protective Equipment****Skin Protection**

Wear protective gloves/clothing.

**Eye/face Protection**

Tightly fitting safety goggles

**Respiratory Protection**

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Flash Point</b>	102°C / 215.0°F
<b>Boiling Point/Range</b>	No information available
<b>Upper Exposure Limits</b>	No information available
<b>Lower Exposure Limits</b>	No information available
<b>Evaporation Rate</b>	No information available
<b>Vapour Pressure</b>	No information available
<b>Vapour Density</b>	No information available
<b>Specific Gravity</b>	1.72531
<b>Density</b>	14.35715
<b>VOC Content (lbs/gal)</b>	.000
<b>% Volatile by Weight</b>	.0000
<b>% Volatile by Volume</b>	.0000

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable.	<b>Conditions to Avoid</b>	Heat, flames and sparks. Amines.
<b>Incompatible Products</b>	Strong oxidizing agents. Acids. Bases. Amines.	<b>Possibility of Hazardous Reactions</b>	None under normal processing

## 11. TOXICOLOGICAL INFORMATION

**Acute Toxicity****Component Information**

<b>Irritation</b>	No information available
<b>Corrosivity</b>	No information available

## 11. TOXICOLOGICAL INFORMATION

**Sensitization** No information available

### Chronic Toxicity

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen

**Mutagenic Effects** No information available

**Reproductive Effects** No information available

**Developmental Effects** No information available

**Teratogenicity** No information available

**Target Organ Effects** No information available

**Endocrine Disruptor Information** No information available

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
BISPHENOL A TYPE EPOXY RESIN	Group III Chemical		

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** In accordance with local and national regulations

**Contaminated Packaging** Empty containers should be taken for local recycling, recovery or waste disposal

## 14. TRANSPORT INFORMATION

**DOT** Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

**Proper Shipping Name** PAINT IN OIL

## 15. REGULATORY INFORMATION

### International Inventories

**TSCA** Complies  
**DSL/NDL** Does not Comply

**EINECS/ELINCS** Does not Comply  
**CHINA** Does not Comply  
**ENCS** Does not Comply  
**KECL** Does not Comply  
**PICCS** Does not Comply  
**AICS** Does not Comply

### U.S. Federal Regulations

**SARA 313**

**SARA 311/312 Hazardous Categorization**

Chronic Health Hazard	No
Acute Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

## CERCLA

### U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

#### State Right-to-Know

### Other International Regulations

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### WHMIS Hazard Class

Non-controlled

## 16. OTHER INFORMATION

Revision Date: 09-Apr-2010

Revision Summary: No information available

HMIS Health 2 Flammability 1 Reactivity 1

#### Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**