



Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code 0156-WHITE
Trade Name ENVIRO-CRETE WHITE BASE
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

HARMFUL IF INHALED.
HARMFUL IF SWALLOWED
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes Irritating to eyes.
Skin Irritating to skin.
Inhalation Irritating to respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Ingestion May be harmful if swallowed.

Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Skin disorders.

Interactions with Other Chemicals No information available

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Eyes, Lungs, Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
-----------	--------	----------

3. COMPOSITION/INFORMATION ON INGREDIENTS

STRONTIUM SULPHATE	7759-02-6	10 - 30
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	5 - 10
ZINC COMPOUNDS	1314-13-2	1 - 5
ALUMINUM SILICATE (TOTAL DUST)	1332-58-7	1 - 5
CALCIUM CARBONATE	471-34-1	1 - 5
ALUMINUM OXIDES	1344-28-1	1 - 5
BARIUM SULFATE (TOTAL DUST)	7727-43-7	0.1 - 1
FERRIC OXIDE	1309-37-1	0.1 - 1
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.2342

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	No information available.
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous Decomposition Products	Oxides of carbon, hydrocarbons. Oxides of nitrogen. Oxides of sulphur. Hydrogen chloride.
Specific Hazards Arising from the Chemical	Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.
Protective Equipment and Precautions for Firefighters	Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
TITANIUM DIOXIDE (TOTAL DUST)	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³
ZINC COMPOUNDS	TWA: 2 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³ STEL: 10 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 2 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³ STEL: 10 mg/m ³
ALUMINUM SILICATE (TOTAL DUST)	TWA: 2 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³ TWA: 15 mg/m ³	TWA: 5 mg/m ³	TWA: 2 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³
CALCIUM CARBONATE			TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³
ALUMINUM OXIDES	TWA: 1 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
BARIUM SULFATE (TOTAL DUST)	TWA: 10 mg/m ³ TWA: 0.5 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³ TWA: 15 mg/m ³	TWA: 10 ppm TWA: 5 ppm TWA: 0.5 mg/m ³	TWA: 10 mg/m ³	TWA: 0.5 mg/m ³
FERRIC OXIDE	TWA: 1 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³	TWA: 1 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 1 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³ STEL: 2 mg/m ³
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

Safety glasses with side-shields

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point

Not applicable

Boiling Point/Range

100°C / 212.0.0°F

Upper Exposure Limits

No information available

Lower Exposure Limits

No information available

Evaporation Rate

No information available

Vapour Pressure

No information available

Vapour Density

No information available

Specific Gravity

1.41299

Density

11.75818

9. PHYSICAL AND CHEMICAL PROPERTIES

VOC Content (lbs/gal)	.408
% Volatile by Weight	34.4710
% Volatile by Volume	49.0675

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks.
Incompatible Products	Strong oxidizing agents. Bases. Acids. Alkalines. Amines. Reducing agents.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg (Rat)		
ZINC COMPOUNDS	5000 mg/kg (Rat)		
CALCIUM CARBONATE	6450 mg/kg (Rat)		
ALUMINUM OXIDES	5000 mg/kg (Rat)		
FERRIC OXIDE	10000 mg/kg (Rat)		
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg (Rat)		

Irritation	No information available
Corrosivity	No information available
Sensitization	No information available

Chronic Toxicity

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	

Mutagenic Effects	No information available
Reproductive Effects	No information available
Developmental Effects	No information available
Teratogenicity	No information available
Target Organ Effects	Eyes, Lungs, Respiratory system, Skin.
Endocrine Disruptor Information	No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name PAINT, WATER BASE FREEZABLE

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDL Does not Comply

EINECS/ELINCS Does not Comply
CHINA Does not Comply
ENCS Does not Comply
KECL Does not Comply
PICCS Does not Comply
AICS Does not Comply

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
ZINC COMPOUNDS	1314-13-2	1 - 5	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard No
Acute Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC COMPOUNDS		X		

CERCLA

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
TITANIUM DIOXIDE (TOTAL DUST)	X	X	X		X
ZINC COMPOUNDS	X	X	X		X
ALUMINUM SILICATE (TOTAL DUST)	X	X	X		X
CALCIUM CARBONATE	X	X	X		X
ALUMINUM OXIDES	X	X	X		X
BARIUM SULFATE (TOTAL DUST)	X	X	X		X
FERRIC OXIDE	X	X	X		X
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X

Other International Regulations**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials



Component	NPRI
ALUMINUM OXIDES	Part 1, Group 1 Substance (fibrous form)

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 29-Dec-2009

Revision Summary: No information available

HMIS Health 0 Flammability 0 Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS