



# Material Safety Data Sheet

Print Date 28-May-2011

Revision Date 27-May-2011

Revision Number 2

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Common name</b>	SERIES 156
<b>Product code</b>	0156-W6673
<b>Trade name</b>	ENVIRO-CRETE WHITE SOLITUDE
<b>Product Class</b>	STYRENATED ACRYLIC
<b>Manufacturer</b>	Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
<b>Emergency telephone</b>	800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

#### WARNING!

HARMFUL IF INHALED.  
HARMFUL IF SWALLOWED.  
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.  
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

#### Potential health effects

**Principle Routes of Exposure** Eye contact, Inhalation, Skin contact.

#### Acute effects

<b>Eyes</b>	Irritating to eyes.
<b>Skin</b>	Irritating to skin.
<b>Inhalation</b>	Irritating to respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
<b>Ingestion</b>	May be harmful if swallowed.

#### Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** Skin disorders. Respiratory disorders.

**Interactive effects** No information available

**Potential environmental effects** See Section 12 for additional Ecological Information

**Target Organ Effects** Eyes, Lungs, Respiratory system, Skin

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Hazardous Components

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
CELESTITE		10 - 30
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	5 - 10
ZINC COMPOUNDS	1314-13-2	1 - 5
ALUMINUM SILICATE (TOTAL DUST)	1332-58-7	1 - 5
BARIUM SULFATE (TOTAL DUST)	7727-43-7	1 - 5
GLASS OXIDE	65997-17-3	1 - 5
CARBONIC ACID CALCIUM SALT		1 - 5
ALUMINUM OXIDES	1344-28-1	1 - 5
MINERAL OIL MIST		1 - 5
BARIUM SULFATE (TOTAL DUST)	7727-43-7	0.1 - 1
FERRIC SESQUIOXIDE		0.1 - 1
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.1 - 1

### 4. FIRST AID MEASURES

<b>Eye contact:</b>	Rinse thoroughly with plenty of water for at least 15 minutes.
<b>Skin contact:</b>	Wash off immediately with soap and plenty of water.
<b>Ingestion:</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Inhalation:</b>	Move to fresh air. Oxygen or artificial respiration if needed.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable properties</b>	No information available.
<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO <sub>2</sub> ) - Foam - Dry chemical
<b>Hazardous decomposition products</b>	Oxides of carbon, hydrocarbons. Oxides of nitrogen. Oxides of sulphur. Hydrogen chloride.
<b>Specific hazards arising from the chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.
<b>Protective equipment and precautions for firefighters</b>	Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
<b>Methods for cleaning up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Other information Not applicable

## 7. HANDLING AND STORAGE

### Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

### Storage

Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
TITANIUM DIOXIDE (TOTAL DUST)	: 10 mg/m <sup>3</sup> TWA	: 10 mg/m <sup>3</sup> TWA (total dust); 15 mg/m <sup>3</sup> TWA (total dust)	TWA: 10 mg/m <sup>3</sup> TWAEV (total dust, containing no asbestos and less than 1% crystalline silica)	TWA: 10 mg/m <sup>3</sup> TWA (total dust)	: 10 mg/m <sup>3</sup> TWA (as Ti); 20 mg/m <sup>3</sup> STEL (as Ti)
ZINC COMPOUNDS	: 2 mg/m <sup>3</sup> TWA (respirable fraction); 10 mg/m <sup>3</sup> STEL (respirable fraction)	: 5 mg/m <sup>3</sup> TWA (fume); 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction); 10 mg/m <sup>3</sup> STEL (fume); 5 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	TWA: 5 mg/m <sup>3</sup> TWAEV (fume); 10 mg/m <sup>3</sup> TWAEV (total dust, containing no asbestos and less than 1% crystalline silica) STEL: 10 mg/m <sup>3</sup> STEV (fume)	TWA: 2 mg/m <sup>3</sup> TWA (respirable) STEL: 10 mg/m <sup>3</sup> STEL (respirable)	: 5 mg/m <sup>3</sup> TWA (fume); 10 mg/m <sup>3</sup> TWA (dust); 10 mg/m <sup>3</sup> STEL (fume)
ALUMINUM SILICATE (TOTAL DUST)	: 2 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	TWA: 5 mg/m <sup>3</sup> TWAEV (respirable dust, containing no asbestos and less than 1% crystalline silica)	TWA: 2 mg/m <sup>3</sup> TWA (containing no Asbestos and <1% Crystalline silica, respirable)	: 10 mg/m <sup>3</sup> TWA : 20 mg/m <sup>3</sup> STEL
BARIUM SULFATE (TOTAL DUST)	: 10 mg/m <sup>3</sup> TWA : 0.5 mg/m <sup>3</sup> TWA (as Ba)	: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	TWA: 10 ppm TWAEV (total dust, containing no asbestos and less than 1% crystalline silica); 5 ppm TWAEV (respirable dust, containing no asbestos and less than 1% crystalline silica) TWA: 0.5 mg/m <sup>3</sup> TWAEV (as Ba)	TWA: 10 mg/m <sup>3</sup> TWA (total dust) TWA: 0.5 mg/m <sup>3</sup> TWA (as Ba)	TWA: 0.5 mg/m <sup>3</sup>
GLASS OXIDE	: 1 fiber/cm <sup>3</sup> TWA (respirable fibers: length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination, listed under Synthetic vitreous fibers); 5 mg/m <sup>3</sup> TWA (inhalable fraction, listed under Synthetic vitreous fibers)		TWA: 10 mg/m <sup>3</sup> TWAEV (total dust, respirable, containing no asbestos and less than 1% crystalline silica, listed under Fibres - Artificial vitreous mineral fibres)	TWA: 1 fibre/cm <sup>3</sup> TWA (length>5 microns, aspect ratio≥ 3.1, respirable); 5 mg/m <sup>3</sup> TWA (inhalable)	

CARBONIC ACID CALCIUM SALT			TWA: 10 mg/m <sup>3</sup> TWA EV (total dust) TWA: 10 mg/m <sup>3</sup> TWA EV (Limestone, total dust, containing no asbestos and less than 1% crystalline silica)	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
ALUMINUM OXIDES	TWA: 1 mg/m <sup>3</sup>	: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	TWA: 10 mg/m <sup>3</sup> TWA EV (total dust, containing no asbestos and less than 1% crystalline silica, as Al)	TWA: 10 mg/m <sup>3</sup>	: 10 mg/m <sup>3</sup> TWA
BARIUM SULFATE (TOTAL DUST)	: 10 mg/m <sup>3</sup> TWA : 0.5 mg/m <sup>3</sup> TWA (as Ba)	: 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)	TWA: 10 ppm TWA EV (total dust, containing no asbestos and less than 1% crystalline silica); 5 ppm TWA EV (respirable dust, containing no asbestos and less than 1% crystalline silica) TWA: 0.5 mg/m <sup>3</sup> TWA EV (as Ba)	TWA: 10 mg/m <sup>3</sup> TWA (total dust) TWA: 0.5 mg/m <sup>3</sup> TWA (as Ba)	TWA: 0.5 mg/m <sup>3</sup>
FERRIC SESQUIOXIDE	: 5 mg/m <sup>3</sup> TWA (respirable fraction)	: 10 mg/m <sup>3</sup> TWA (fume)	TWA: 5 mg/m <sup>3</sup> TWA EV (dust and fume, as Fe)	TWA: 5 mg/m <sup>3</sup> TWA (respirable)	: 5 mg/m <sup>3</sup> TWA : 10 mg/m <sup>3</sup> STEL (as Fe)
CRYSTALLINE SILICA (QUARTZ)	: 0.025 mg/m <sup>3</sup> TWA (respirable fraction)	: 0.1 mg/m <sup>3</sup> TWA (respirable dust)	TWA: 0.1 mg/m <sup>3</sup> TWA EV (respirable dust)	TWA: 0.10 mg/m <sup>3</sup> TWA (designated substance regulation, respirable)	: 0.1 mg/m <sup>3</sup> TWA (respirable fraction)

**Engineering measures**

Ensure adequate ventilation, especially in confined areas

**Personal Protective Equipment****Skin protection**

Lightweight protective clothing, Apron, Impervious gloves

**Eye/face protection**

Safety glasses with side-shields

**Respiratory protection**

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General hygiene considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point	Not applicable
Boiling range	100 - 100°C / 212.0 - 212.0°F
Upper explosion limit	No information available
Lower explosion limit	No information available
Evaporation rate	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	1.43572 g/cm <sup>3</sup>
Density	11.94738 lbs/gal
Volatile organic compounds (VOC) content	.407 lbs/gal
Volatile by weight	33.9260 %
Volatile by volume	49.0679 %

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable.	<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Incompatible products</b>	Strong oxidizing agents. Bases. Acids. Alkalines. Amines. Reducing agents.	<b>Possibility of hazardous reactions</b>	None under normal processing

## 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
WATER	90 mL/kg ( Rat )		
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg ( Rat )		
ZINC COMPOUNDS	5000 mg/kg ( Rat )		
CARBONIC ACID CALCIUM SALT	6450 mg/kg ( Rat )		
ALUMINUM OXIDES	5000 mg/kg ( Rat )		
FERRIC SESQUIOXIDE	10000 mg/kg ( Rat )		
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg ( Rat )		

<b>Irritation</b>	No information available
<b>Corrosivity</b>	No information available
<b>Sensitization</b>	No information available

### Chronic toxicity

#### Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	

<b>Mutagenicity</b>	No information available
<b>Reproductive effects</b>	No information available
<b>Developmental effects</b>	No information available
<b>Teratogenicity</b>	No information available
<b>Target Organ Effects</b>	Eyes, Lungs, Respiratory system, Skin.
<b>Endocrine Disruptor Information</b>	No information available

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

## 13. DISPOSAL CONSIDERATIONS

### 13. DISPOSAL CONSIDERATIONS

<b>Waste disposal methods</b>	Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Contaminated packaging</b>	Empty containers should be taken for local recycling, recovery or waste disposal

### 14. TRANSPORT INFORMATION

<b>DOT</b>	Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.
<b>Proper shipping name</b>	PAINT,WATER BASE FREEZABLE

### 15. REGULATORY INFORMATION

#### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Does not Comply
<b>CHINA</b>	Complies
<b>ENCS</b>	Does not Comply
<b>KECL</b>	Does not Comply
<b>PICCS</b>	Does not Comply
<b>AICS</b>	Complies

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):  
United States of America Federal Regulations

#### SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
ZINC COMPOUNDS	1314-13-2	1 - 5	1.0
BARIUM SULFATE (TOTAL DUST)	7727-43-7	1 - 5	1.0
ALUMINUM OXIDES	1344-28-1	1 - 5	1.0 % de minimis concentration (fibrous forms)
BARIUM SULFATE (TOTAL DUST)	7727-43-7	0.1 - 1	1.0

#### SARA 311/312 Hazardous Categorization

<b>Chronic Health Hazard</b>	no
<b>Acute Health Hazard</b>	yes
<b>Fire Hazard</b>	yes
<b>Sudden Release of Pressure Hazard</b>	no
<b>Reactive Hazard</b>	no

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC COMPOUNDS		X		

#### CERCLA

#### United States of America State Regulations

**California Prop. 65**

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen

**State Right-to-Know**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
TITANIUM DIOXIDE (TOTAL DUST)	X	X	X		X
ZINC COMPOUNDS	X	X	X		X
ALUMINUM SILICATE (TOTAL DUST)	X	X	X		X
BARIUM SULFATE (TOTAL DUST)	X	X	X		X
CARBONIC ACID CALCIUM SALT	X	X	X		X
ALUMINUM OXIDES	X	X	X		X
BARIUM SULFATE (TOTAL DUST)	X	X	X		X
FERRIC SESQUIOXIDE	X	X	X		X
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X

**Other international regulations****Canada**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**WHMIS Classification**

D2B Toxic materials



Component	NPRI
ALUMINUM OXIDES	Part 1, Group 1 Substance (fibrous form)

**Legend**

NPRI - National Pollutant Release Inventory

## 16. OTHER INFORMATION

Revision Date 27-May-2011

Revision Note No information available

HMIS (Hazardous Material Information System)

Health 3\*

Flammability 1

Reactivity 1

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**