



# Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Code** F157-11WH  
**Trade Name** ENVIRO-CRETETX WHITE  
**Contact Manufacturer** Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372  
**Emergency Telephone Number** 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

#### WARNING!

HARMFUL IF INHALED.  
HARMFUL IF SWALLOWED  
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.  
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

#### Potential Health Effects

**Principle Routes of Exposure** Eye contact, Inhalation, Skin contact.

#### Acute Effects

**Eyes** Irritating to eyes.  
**Skin** Irritating to skin.  
**Inhalation** Irritating to respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.  
**Ingestion** May be harmful if swallowed.

#### Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** Skin disorders.

**Interactions with Other Chemicals** No information available

**Potential Environmental Effects** See Section 12 for additional Ecological information

**Target Organ Effects** Eyes, Lungs, Respiratory system, Skin

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous Components

Component	CAS-No	Weight %
-----------	--------	----------

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CRYSTALLINE SILICA (QUARTZ)	14808-60-7	21.5368
STRONTIUM SULPHATE	7759-02-6	10 - 30
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	5 - 10
ZINC COMPOUNDS	1314-13-2	1 - 5
ALUMINUM SILICATE (TOTAL DUST)	1332-58-7	1 - 5
SILICON DIOXIDE/ALUMINUM OXIDE	66402-68-4	1 - 5
ALUMINUM OXIDES	1344-28-1	1 - 5
AMORPHOUS SILICA	7631-86-9	1 - 5
BARIUM SULFATE (TOTAL DUST)	7727-43-7	0.1 - 1
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.2487
FERRIC OXIDE	1309-37-1	0.1 - 1

### 4. FIRST AID MEASURES

<b>Eye Contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water.
<b>Ingestion</b>	If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Inhalation</b>	Move to fresh air. Oxygen or artificial respiration if needed.

### 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	No information available.
<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO <sub>2</sub> ) - Foam - Dry chemical
<b>Hazardous Decomposition Products</b>	Oxides of carbon, hydrocarbons. Oxides of nitrogen. Oxides of sulphur. Hydrogen chloride.
<b>Specific Hazards Arising from the Chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.
<b>Protective Equipment and Precautions for Firefighters</b>	Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
<b>Environmental Precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
<b>Methods for Cleaning Up</b>	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
<b>Other Information</b>	Not applicable

7. HANDLING AND STORAGE

**Handling**

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

**Storage**

Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
TITANIUM DIOXIDE (TOTAL DUST)	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
ZINC COMPOUNDS	TWA: 2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
ALUMINUM SILICATE (TOTAL DUST)	TWA: 2 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
SILICON DIOXIDE/ALUMINUM OXIDE	TWA: 5 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup>		TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 0.5 fibres/cm <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 0.2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
ALUMINUM OXIDES	TWA: 1 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
BARIUM SULFATE (TOTAL DUST)	TWA: 10 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> TWA: 15 mg/m <sup>3</sup>	TWA: 10 ppm TWA: 5 ppm TWA: 0.5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
FERRIC OXIDE	TWA: 1 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> STEL: 2 mg/m <sup>3</sup>

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas

**Personal Protective Equipment**

**Skin Protection**

Lightweight protective clothing, Apron, Impervious gloves

**Eye/face Protection**

Safety glasses with side-shields

**Respiratory Protection**

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

**General Hygiene Considerations**

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

**Flash Point**

Not applicable

**Boiling Point/Range**

100°C / 212.0°F

**Upper Exposure Limits**

No information available

**Lower Exposure Limits**

No information available

**Evaporation Rate**

No information available

**Vapour Pressure**

No information available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Vapour Density	No information available
Specific Gravity	1.57339
Density	13.09295
VOC Content (lbs/gal)	.378
% Volatile by Weight	27.1720
% Volatile by Volume	43.1575

## 10. STABILITY AND REACTIVITY

<b>Chemical stability</b>	Stable.	<b>Conditions to Avoid</b>	Heat, flames and sparks.
<b>Incompatible Products</b>	Strong oxidizing agents. Bases. Acids. Alkalines. Amines. Reducing agents.	<b>Possibility of Hazardous Reactions</b>	None under normal processing

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg ( Rat )		
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg ( Rat )		
ZINC COMPOUNDS	5000 mg/kg ( Rat )		
ALUMINUM OXIDES	5000 mg/kg ( Rat )		
AMORPHOUS SILICA	5000 mg/kg ( Rat )	2000 mg/kg ( Rabbit )	2.2 mg/L ( Rat ) 1 h
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg ( Rat )		
FERRIC OXIDE	10000 mg/kg ( Rat )		

<b>Irritation</b>	No information available
<b>Corrosivity</b>	No information available
<b>Sensitization</b>	No information available

### Chronic Toxicity

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	

<b>Mutagenic Effects</b>	No information available
<b>Reproductive Effects</b>	No information available
<b>Developmental Effects</b>	No information available
<b>Teratogenicity</b>	No information available
<b>Target Organ Effects</b>	Eyes, Lungs, Respiratory system, Skin.
<b>Endocrine Disruptor Information</b>	No information available

## 12. ECOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
AMORPHOUS SILICA	EC50 = 440 mg/L 72 h	LC50= 5000 mg/L Brachydanio rerio 96 h		EC50 = 7600 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging

Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper Shipping Name PAINT, WATER BASE FREEZABLE

15. REGULATORY INFORMATION

International Inventories

TSCA Complies  
 DSL/NDL Does not Comply

EINECS/ELINCS Does not Comply  
 CHINA Does not Comply  
 ENCS Does not Comply  
 KECL Does not Comply  
 PICCS Does not Comply  
 AICS Does not Comply

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
ZINC COMPOUNDS	1314-13-2	1 - 5	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard No  
 Acute Health Hazard Yes  
 Fire Hazard Yes  
 Sudden Release of Pressure Hazard No  
 Reactive Hazard No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC COMPOUNDS		X		
SILICON DIOXIDE/ALUMINUM OXIDE		X		

**CERCLA**

**U.S. State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen

**State Right-to-Know**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
TITANIUM DIOXIDE (TOTAL DUST)	X	X	X		X
ZINC COMPOUNDS	X	X	X		X
ALUMINUM SILICATE (TOTAL DUST)	X	X	X		X
SILICON DIOXIDE/ALUMINUM OXIDE		X	X		X
ALUMINUM OXIDES	X	X	X		X
AMORPHOUS SILICA	X		X		
BARIUM SULFATE (TOTAL DUST)	X	X	X		X
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
FERRIC OXIDE	X	X	X		X

**Other International Regulations**

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class**

D2B Toxic materials



Component	NPRI
ALUMINUM OXIDES	Part 1, Group 1 Substance (fibrous form)

**Legend**

NPRI - National Pollutant Release Inventory

**16. OTHER INFORMATION**

Revision Date: 29-Dec-2009

Revision Summary                      No information available

HMIS                                      Health 0                                      Flammability 0                                      Reactivity 1

**Disclaimer**

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

**End of MSDS**