



Material Safety Data Sheet

Preparation Date: 04-Jan-2010

Revision Date: 29-Dec-2009

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code F394-0394
Trade Name PERIMIPRIME GREENISH GREY
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

DANGER!

HARMFUL IF INHALED.
MAY CAUSE LUNG INJURY.
MAY CAUSE ALLERGIC RESPIRATORY REACTION; EFFECTS MAY BE PERMANENT.
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT.
HARMFUL OR FATAL IF SWALLOWED.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.
FLAMMABLE LIQUID AND VAPOR.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes

Moderately irritating to the eyes. Risk of serious damage to eyes.

Skin

Irritating to skin. May cause sensitization by skin contact.

Inhalation

May cause allergic respiratory reaction. Inhalation of metallic zinc dust may result in symptoms known as metal fume fever. Symptoms include chills, fever, muscular pain, nausea and vomiting.

Ingestion

May be harmful if swallowed.

Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Gastrointestinal tract. Liver disorders. Skin disorders.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Blood, Central nervous system, Central Vascular System, Gastrointestinal tract, Eyes, Liver, Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
IRON OXIDE FUME	1309-37-1	30 - 60
ZINC (TOTAL DUST)	7440-66-6	10 - 30
DIPHENYLMETHANE DIISOCYANATE (MDI) POLYMER		5 - 10
AROMATIC HYDROCARBON MIXTURE	64742-95-6	6.1669
1,2,4-TRIMETHYLBENZENE	95-63-6	4.5775
TALC (RESPIRABLE DUST)	14807-96-6	1 - 5
C.I. PIGMENT BROWN 24	68186-90-3	1 - 5
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	101-68-8	2.0663
1,3,5-TRIMETHYLBENZENE	108-67-8	1.1444
ACETONE	67-64-1	0.472
XYLENE	1330-20-7	0.2631

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Flammable.
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous Decomposition Products	Oxides of carbon, hydrocarbons. Oxides of nitrogen. Hydrogen cyanide. Oxides of sulphur. Zinc oxide fume.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods for Cleaning Up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Other Information Not applicable

7. HANDLING AND STORAGE

Handling

Use only with adequate ventilation. Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Close container after each use. Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
IRON OXIDE FUME	TWA: 1 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³	TWA: 1 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 1 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³ STEL: 2 mg/m ³
1,2,4-TRIMETHYLBENZENE	TWA: 25 ppm		TWA: 25 ppm TWA: 123 mg/m ³	TWA: 25 ppm TWA: 123 mg/m ³	TWA: 125 mg/m ³ TWA: 25 ppm STEL: 170 mg/m ³ STEL: 35 ppm
TALC (RESPIRABLE DUST)	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 3 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
C.I. PIGMENT BROWN 24	TWA: 0.5 mg/m ³		TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	TWA: 0.005 ppm	Ceiling: 0.2 mg/m ³ Ceiling: 0.02 ppm	TWA: 0.051 mg/m ³ TWA: 0.005 ppm	TWA: 0.2 µmol/m ³ TWA: 0.005 ppm CEV: 0.02 ppm CEV: 0.8 µmol/m ³	TWA: 0.2 mg/m ³ TWA: 0.005 ppm TWA: 0.051 mg/m ³ TWA: 0.02 ppm
1,3,5-TRIMETHYLBENZENE	TWA: 25 ppm		TWA: 25 ppm TWA: 123 mg/m ³	TWA: 25 ppm TWA: 123 mg/m ³	TWA: 125 mg/m ³ TWA: 25 ppm STEL: 170 mg/m ³ STEL: 35 ppm
ACETONE	TWA: 500 ppm STEL: 750 ppm	TWA: 1800 mg/m ³ TWA: 750 ppm STEL: 2400 mg/m ³ STEL: 1000 ppm TWA: 2400 mg/m ³ TWA: 1000 ppm	TWA: 500 ppm TWA: 1190 mg/m ³ STEL: 2380 mg/m ³ STEL: 1000 ppm	TWA: 500 ppm STEL: 750 ppm	TWA: 2400 mg/m ³ TWA: 1000 ppm STEL: 3000 mg/m ³ STEL: 1260 ppm
XYLENE	TWA: 100 ppm STEL: 150 ppm	TWA: 435 mg/m ³ TWA: 100 ppm STEL: 150 ppm STEL: 655 mg/m ³	TWA: 434 mg/m ³ TWA: 100 ppm STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 650 mg/m ³	TWA: 435 mg/m ³ TWA: 100 ppm STEL: 150 ppm STEL: 655 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

Safety glasses with side-shields

Respiratory Protection

INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (TC 19C NIOSH/MSHA) is recommended. A vapor-particulate respirator (TC 23C NIOSH/MSHA) may be appropriate where air monitoring demonstrates vapors are less than ten times the applicable exposure limits and the isocyanate concentration is less than its applicable exposure limit. The use of an air-supplied respirator is mandatory whenever the airborne concentration of isocyanate monomer is unknown.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	29°C / 85.0°F
Boiling Point/Range	No information available.0.0
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	2.54738
Density	21.19804
VOC Content (lbs/gal)	2.764
% Volatile by Weight	13.3100
% Volatile by Volume	38.9347

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks. Amines.
Incompatible Products	Strong oxidizing agents. Bases. Acids. Alkalines. Amines. Water, alcohols, amines, strong bases, metal components, surface active materials. Water. Product may release hydrogen.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
IRON OXIDE FUME	10000 mg/kg (Rat)		
AROMATIC HYDROCARBON MIXTURE	8400 mg/kg (Rat)	2000 mg/kg (Rabbit)	5.2 mg/L (Rat) 4 h 3400 ppm (Rat) 4 h

11. TOXICOLOGICAL INFORMATION

1,2,4-TRIMETHYLBENZENE	3400 mg/kg (Rat)	3160 mg/kg (Rabbit)	18 g/m ³ (Rat) 4 h
C.I. PIGMENT BROWN 24	10000 mg/kg (Rat)		
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	9200 mg/kg (Rat)		
1,3,5-TRIMETHYLBENZENE	5000 mg/kg (Rat)		24 g/m ³ (Rat) 4 h
ACETONE	5800 mg/kg (Rat)		
XYLENE	4300 mg/kg (Rat)	1700 mg/kg (Rabbit)	47635 mg/L (Rat) 4 h 5000 ppm (Rat) 4 h

Irritation No information available
Corrosivity No information available
Sensitization No information available

Chronic Toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Mutagenic Effects No information available
Reproductive Effects No information available
Developmental Effects No information available
Teratogenicity No information available
Target Organ Effects Blood, Central nervous system, Central Vascular System, Gastrointestinal tract, Eyes, Liver, Respiratory system, Skin.
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
ZINC (TOTAL DUST)	EC50 = 30 µg/L 96 h	LC50= 6.4 mg/L Pimephales promelas 96 h		EC50 = 5 µg/L 72 h
AROMATIC HYDROCARBON MIXTURE		LC50= 9.22 mg/L Oncorhynchus mykiss 96 h		EC50 = 6.14 mg/L 48 h
1,2,4-TRIMETHYLBENZENE		LC50= 7.72 mg/L Pimephales promelas 96 h		EC50 = 6.14 mg/L 48 h
TALC (RESPIRABLE DUST)		LC50> 100 g/L Brachydanio rerio 96 h		
C.I. PIGMENT BROWN 24		LC50> 10000 mg/L Leuciscus idus 96 h		
1,3,5-TRIMETHYLBENZENE		LC50= 7.72 mg/L Pimephales promelas 96 h LC50= 3.48 mg/L Pimephales promelas 96 h		EC50 = 50 mg/L 24 h
ACETONE		LC50= 5540 mg/L Oncorhynchus mykiss 96 h LC50= 6210 mg/L Pimephales promelas 96 h LC50= 8300 mg/L Lepomis macrochirus 96 h	EC50 = 14500 mg/L 15 min	EC50 = 0.0039 mg/L 48 h EC50 = 12700 mg/L 48 h EC50 = 12600 mg/L 48 h
XYLENE		LC50= 13.4 mg/L Pimephales promelas 96 h LC50= 8.05 mg/L Oncorhynchus mykiss 96 h LC50= 16.1 mg/L Lepomis macrochirus 96 h LC50= 26.7 mg/L Pimephales promelas 96 h	EC50 = 0.0084 mg/L 24 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name UN1263,PAINT,3,PGIII,ERG 128

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Does not Comply
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Does not Comply
AICS	Does not Comply

Component
XYLENE

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
ZINC (TOTAL DUST)	7440-66-6	10 - 30	1.0
1,2,4-TRIMETHYLBENZENE	95-63-6	4.5775	1.0
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	101-68-8	2.0663	1.0
XYLENE	1330-20-7	0.2631	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	Yes
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC (TOTAL DUST)		X	X	
C.I. PIGMENT BROWN 24		X		
XYLENE	100 lb			X

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
ZINC (TOTAL DUST)	1000 lb	
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	5000 lb	
ACETONE	5000 lb	
XYLENE	100 lb	

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
IRON OXIDE FUME	X	X	X		X
ZINC (TOTAL DUST)	X	X	X		X
1,2,4-TRIMETHYLBENZENE	X	X	X	X	X
TALC (RESPIRABLE DUST)	X	X	X		X
C.I. PIGMENT BROWN 24		X	X	X	X
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	X	X	X	X	X
1,3,5-TRIMETHYLBENZENE	X	X	X	X	X
ACETONE	X	X	X		X
XYLENE	X	X	X	X	X

Other International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid
D2A Very toxic materials



Component	NPRI
ZINC (TOTAL DUST)	Part 1, Group 1 Substance
AROMATIC HYDROCARBON MIXTURE	Part 5 Substance
1,2,4-TRIMETHYLBENZENE	Part 1, Group 1 Substance; Part 5 Substance
DIPHENYLMETHANE DIISOCYANATE (MDI) REACTIVE MONOMER	Part 1, Group 1 Substance
XYLENE	Part 1, Group 1 Substance; Part 5 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 29-Dec-2009

Revision Summary No information available

HMIS Health 0 Flammability 0 Reactivity 2

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS