



Material Safety Data Sheet

Preparation Date: 30-Dec-2009

Revision Date: 29-Dec-2009

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code F044-0600
Trade Name UV SHIELD
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

DANGER!

COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL IF INHALED.
HARMFUL OR FATAL IF SWALLOWED.
CAUSES SKIN AND EYE BURNS.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes Causes burns.
Skin Causes burns.
Inhalation Irritating to respiratory system.
Ingestion May be harmful if swallowed.

Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Gastrointestinal tract. Kidney disorders. Liver disorders. Skin disorders.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Blood, Central nervous system, Gastrointestinal tract, Eyes, Kidney, Liver, Peripheral Nervous System (PNS), Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
METHYL N-AMYL KETONE	110-43-0	40.1649
AMINE STABILIZER	79720-19-7	10 - 30
XYLENE	1330-20-7	13.2368

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Combustible material.
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical

Hazardous Decomposition Products Oxides of carbon, hydrocarbons. Oxides of nitrogen.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
METHYL N-AMYL KETONE	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³	TWA: 50 ppm TWA: 233 mg/m ³	TWA: 25 ppm TWA: 115 mg/m ³	TWA: 235 mg/m ³ TWA: 50 ppm STEL: 465 mg/m ³ STEL: 100 ppm
XYLENE	TWA: 100 ppm STEL: 150 ppm	TWA: 435 mg/m ³ TWA: 100 ppm STEL: 150 ppm STEL: 655 mg/m ³	TWA: 434 mg/m ³ TWA: 100 ppm STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 650 mg/m ³	TWA: 435 mg/m ³ TWA: 100 ppm STEL: 150 ppm STEL: 655 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

Goggles. If splashes are likely to occur, wear face-shield.

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	39°C / 102.0°F
Boiling Point/Range	138 - 154°C / 280.0 - 309.0°F
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	.91309
Density	7.59827
VOC Content (lbs/gal)	4.057
% Volatile by Weight	53.4020
% Volatile by Volume	58.7527

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks.
Incompatible Products	Strong oxidizing agents. Acids.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

11. TOXICOLOGICAL INFORMATION

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL N-AMYL KETONE	1670 mg/kg (Rat)	12600 µL/kg (Rabbit)	
XYLENE	4300 mg/kg (Rat)	1700 mg/kg (Rabbit)	47635 mg/L (Rat) 4 h 5000 ppm (Rat) 4 h

Irritation No information available
Corrosivity No information available
Sensitization No information available

Chronic Toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Mutagenic Effects No information available
Reproductive Effects No information available
Developmental Effects No information available
Teratogenicity No information available
Target Organ Effects Blood, Central nervous system, Gastrointestinal tract, Eyes, Kidney, Liver, Peripheral Nervous System (PNS), Respiratory system, Skin.
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

(Bad file name or number)

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
METHYL N-AMYL KETONE		LC50= 131.0 mg/L Pimephales promelas 96 h		
XYLENE		LC50= 13.4 mg/L Pimephales promelas 96 h LC50= 8.05 mg/L Oncorhynchus mykiss 96 h LC50= 16.1 mg/L Lepomis macrochirus 96 h LC50= 26.7 mg/L Pimephales promelas 96 h	EC50 = 0.0084 mg/L 24 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name PAINT & RELATED MATERIAL-(NMFC 149980 SUB2)

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Does not Comply
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Does not Comply
AICS	Does not Comply

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Component
XYLENE

U.S. Federal Regulations**SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values
XYLENE	1330-20-7	13.2368	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE	100 lb			X

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
XYLENE	100 lb	

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL N-AMYL KETONE	X	X	X		X
XYLENE	X	X	X	X	X

Other International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class
 B3 Combustible liquid
 D2B Toxic materials
 E Corrosive material



Component	NPRI
XYLENE	Part 1, Group 1 Substance; Part 5 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 29-Dec-2009

Revision Summary No information available

HMIS Health 0 Flammability 0 Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS