



Material Safety Data Sheet

Print Date 08-Jun-2011

Revision Date 08-Jun-2011

Revision Number 2

1. PRODUCT AND COMPANY IDENTIFICATION

Common name	SERIES 61 PART A
Product code	F061-5001A
Trade name	TNEME-LINER GRAY
Product Class	AMINE ADDUCT PAINT
Manufacturer	Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency telephone	800-535-5053 (INFOTRAC) - TNEMEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

FLAMMABLE LIQUID AND VAPOR.
HARMFUL IF INHALED.
CAUSES SKIN AND EYE BURNS.
HARMFUL OR FATAL IF SWALLOWED.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT.
MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

Potential health effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute effects

Eyes

Causes burns.

Skin

Causes burns. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Harmful in contact with skin.

Inhalation

Irritating to respiratory system.

Ingestion

May be harmful if swallowed.

Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Gastrointestinal tract. Kidney disorders. Liver disorders. Skin disorders. Respiratory disorders.

Interactive effects Use of alcoholic beverages may enhance toxic effects.

Potential environmental effects See Section 12 for additional Ecological Information

Target Organ Effects

Liver, Kidney, Respiratory system, Eyes, Skin, Central nervous system, Blood, Gastrointestinal tract, Central Vascular System (CVS), Lungs

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
BARIUM SULFATE (TOTAL DUST)	7727-43-7	30 - 60
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	10 - 30
TALC (RESPIRABLE DUST)	14807-96-6	10 - 30
BENZYL ALCOHOL	100-51-6	10 - 30
XYLENE	1330-20-7	5 - 10
AMORPHOUS SILICA	7631-86-9	1 - 5
ALUMINUM OXIDES	1344-28-1	1 - 5
ETHYL BENZENE	100-41-4	1 - 5
IRON OXIDE FUME	1309-37-1	0.1 - 1

4. FIRST AID MEASURES

Eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin contact:	Wash off immediately with soap and plenty of water.
Ingestion:	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation:	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable properties	Flammable.
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous decomposition products	Oxides of carbon, hydrocarbons. Oxides of nitrogen. Aldehydes. Nitric acid, nitrosamine.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Other information Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
BARIUM SULFATE (TOTAL DUST)	: 10 mg/m ³ TWA : 0.5 mg/m ³ TWA (as Ba)	: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction) : 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	TWA: 10 ppm TWAEV (total dust, containing no asbestos and less than 1% crystalline silica); 5 ppm TWAEV (respirable dust, containing no asbestos and less than 1% crystalline silica) TWA: 0.5 mg/m ³ TWAEV (as Ba)	TWA: 10 mg/m ³ TWA (total dust) TWA: 0.5 mg/m ³ TWA (as Ba)	TWA: 0.5 mg/m ³
TITANIUM DIOXIDE (TOTAL DUST)	: 10 mg/m ³ TWA	: 10 mg/m ³ TWA (total dust) : 15 mg/m ³ TWA (total dust)	TWA: 10 mg/m ³ TWAEV (total dust, containing no asbestos and less than 1% crystalline silica)	TWA: 10 mg/m ³ TWA (total dust)	: 10 mg/m ³ TWA (as Ti) : 20 mg/m ³ STEL (as Ti)
TALC (RESPIRABLE DUST)	: 2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	: 2 mg/m ³ TWA (<1% Crystalline silica, containing no Asbestos, respirable dust)	TWA: 3 mg/m ³ TWAEV (respirable dust)	TWA: 2 mg/m ³ TWA (containing no Asbestos and <1% Crystalline silica, respirable)	: 2 mg/m ³ TWA (respirable fraction)
XYLENE	: 100 ppm TWA : 150 ppm STEL	: 100 ppm TWA; 435 mg/m ³ TWA : 150 ppm STEL; 655 mg/m ³ STEL	TWA: 100 ppm TWAEV; 434 mg/m ³ TWAEV STEL: 150 ppm STEV; 651 mg/m ³ STEV	TWA: 100 ppm TWA STEL: 150 ppm STEL	: 100 ppm TWA; 435 mg/m ³ TWA : 150 ppm STEL; 655 mg/m ³ STEL
ALUMINUM OXIDES	TWA: 1 mg/m ³	: 10 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction) : 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	TWA: 10 mg/m ³ TWAEV (total dust, containing no asbestos and less than 1% crystalline silica, as Al)	TWA: 10 mg/m ³	: 10 mg/m ³ TWA
ETHYL BENZENE	: 100 ppm TWA : 125 ppm STEL	: 100 ppm TWA; 435 mg/m ³ TWA : 125 ppm STEL; 545 mg/m ³ STEL	TWA: 100 ppm TWAEV; 434 mg/m ³ TWAEV STEL: 125 ppm STEV; 543 mg/m ³ STEV	TWA: 100 ppm TWA STEL: 125 ppm STEL	: 100 ppm TWA; 435 mg/m ³ TWA : 125 ppm STEL; 545 mg/m ³ STEL
IRON OXIDE FUME	: 5 mg/m ³ TWA (respirable fraction)	: 10 mg/m ³ TWA (fume)	TWA: 5 mg/m ³ TWAEV (dust and fume, as Fe)	TWA: 5 mg/m ³ TWA (respirable)	: 5 mg/m ³ TWA : 10 mg/m ³ STEL (as Fe)

Engineering measures Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin protection Lightweight protective clothing, Apron, Impervious gloves
Eye/face protection Goggles. If splashes are likely to occur, wear face-shield.
Respiratory protection **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.
General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point 27°C / 81.0°F
Boiling range 116 - 142°C / 241.0 - 288.0°F
Upper explosion limit No information available
Lower explosion limit No information available
Evaporation rate No information available
Vapor pressure No information available
Vapor density No information available
Specific Gravity 1.92818 g/cm3
Density 16.04533 lbs/gal
Volatile organic compounds (VOC) content 1.467 lbs/gal
Volatile by weight 9.1410 %
Volatile by volume 19.8141 %

10. STABILITY AND REACTIVITY

Chemical stability Stable. **Conditions to avoid** Heat, flames and sparks. Epoxy constituents. Reacts with air to form peroxides.
Incompatible products Strong oxidizing agents. Bases. **Possibility of hazardous reactions** None under normal processing
 Acids. Metals . Hypochlorites.
 Peroxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg (Rat)		
BENZYL ALCOHOL	1230 mg/kg (Rat)	2000 mg/kg (Rabbit)	8.8 mg/L (Rat) 4 h
XYLENE	4300 mg/kg (Rat)	1700 mg/kg (Rabbit)	5000 ppm (Rat) 4 h 47635 mg/L (Rat) 4 h
AMORPHOUS SILICA	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	2.2 mg/L (Rat) 1 h
ALUMINUM OXIDES	5000 mg/kg (Rat)		
ETHYL BENZENE	3500 mg/kg (Rat)	15354 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h
IRON OXIDE FUME	10000 mg/kg (Rat)		

Irritation No information available

Corrosivity No information available
Sensitization No information available

Chronic toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA	Mexico
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	
ETHYL BENZENE	A3	Group 2B		X	

Mutagenicity No information available
Reproductive effects No information available
Developmental effects No information available
Teratogenicity No information available
Target Organ Effects Liver, Kidney, Respiratory system, Eyes, Skin, Central nervous system, Blood, Gastrointestinal tract, Central Vascular System (CVS), Lungs.
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
TALC (RESPIRABLE DUST)		LC50> 100 g/L Brachydanio rerio 96 h		
BENZYL ALCOHOL	EC50 = 35 mg/L 3 h	LC50= 10 mg/L Lepomis macrochirus 96 h LC50= 460 mg/L Pimephales promelas 96 h	EC50 = 63.7 mg/L 5 min EC50 = 63.7 mg/L 15 min EC50 = 71.4 mg/L 30 min EC50 = 50 mg/L 5 min	EC50 = 23 mg/L 48 h
XYLENE		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661-4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5-17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1-16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711-9.591 mg/L Lepomis macrochirus 96 h LC50 23.53-29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26-40.75 mg/L Poecilia reticulata 96 h	EC50 = 0.0084 mg/L 24 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
AMORPHOUS SILICA	EC50 = 440 mg/L 72 h	LC50= 5000 mg/L Brachydanio rerio 96 h		EC50 = 7600 mg/L 48 h
ETHYL BENZENE	EC50 = 4.6 mg/L 72 h EC50 > 438 mg/L 96 h EC50 2.6 - 11.3 mg/L 72 h EC50 1.7 - 7.6 mg/L 96 h	LC50 11.0-18.0 mg/L Oncorhynchus mykiss 96 h LC50= 4.2 mg/L Oncorhynchus mykiss 96 h LC50 7.55-11 mg/L Pimephales promelas 96 h LC50= 32 mg/L Lepomis macrochirus 96 h LC50 9.1-15.6 mg/L Pimephales promelas 96 h LC50= 9.6 mg/L Poecilia reticulata 96 h	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 1.8 - 2.4 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste disposal methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. STORAGE AND DISPOSAL.

Contaminated packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper shipping name UN1263,PAINT,3,PGIII,ERG 128

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Complies
ENCS	Does not Comply
KECL	Complies
PICCS	Does not Comply
AICS	Does not Comply

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component
 XYLENE
 ETHYL BENZENE

United States of America Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
BARIUM SULFATE (TOTAL DUST)	7727-43-7	30 - 60	1.0
XYLENE	1330-20-7	5 - 10	1.0 % de minimis concentration
ALUMINUM OXIDES	1344-28-1	1 - 5	1.0 % de minimis concentration (fibrous forms)
ETHYL BENZENE	100-41-4	1 - 5	0.1 % de minimis concentration

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	yes
Acute Health Hazard	yes
Fire Hazard	yes
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE	100 lb RQ			X
ETHYL BENZENE	1000 lb RQ	X	X	X

CERCLA

United States of America State Regulations

California Prop. 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
ETHYL BENZENE	100-41-4	Carcinogen

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
BARIUM SULFATE (TOTAL DUST)	X	X	X		X
TITANIUM DIOXIDE (TOTAL DUST)	X	X	X		X
TALC (RESPIRABLE DUST)	X	X	X		X
BENZYL ALCOHOL	X		X		
XYLENE	X	X	X	X	X
AMORPHOUS SILICA	X		X		
ALUMINUM OXIDES	X	X	X		X
ETHYL BENZENE	X	X	X	X	X
IRON OXIDE FUME	X	X	X		X

Other international regulations

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

WHMIS Classification

- B2 Flammable liquid
- D2A Very toxic materials
- E Corrosive material



Component	NPRI
XYLENE	Part 1, Group 1 Substance; Part 5 Substance
ALUMINUM OXIDES	Part 1, Group 1 Substance (fibrous form)
ETHYL BENZENE	Part 1, Group 1 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date

08-Jun-2011

Revision Note

No information available

HMIS (Hazardous Material Information System)

Health 2

Flammability 3


Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS



Material Safety Data Sheet

Print Date 08-Jun-2011

Revision Date 08-Jun-2011

Revision Number 2

1. PRODUCT AND COMPANY IDENTIFICATION

Common name	SERIES 61 PART B
Product code	F061-0061B
Trade name	TNEME-LINER CONVERTER
Product Class	EPOXY PAINT
Manufacturer	Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency telephone	800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

DANGER!

FLAMMABLE LIQUID AND VAPOR.
HARMFUL IF INHALED.
MAY CAUSE ALLERGIC SKIN REACTION; EFFECTS MAY BE PERMANENT.
HARMFUL OR FATAL IF SWALLOWED.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential health effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute effects

Eyes	Moderately irritating to the eyes.
Skin	Irritating to skin. May cause sensitization by skin contact.
Inhalation	Irritating to respiratory system.
Ingestion	May be harmful if swallowed.

Chronic effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Gastrointestinal tract. Kidney disorders. Liver disorders. Skin disorders. Respiratory disorders.

Interactive effects Use of alcoholic beverages may enhance toxic effects.

Potential environmental effects See Section 12 for additional Ecological Information

Target Organ Effects Blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, Kidney, Liver, Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
EPOXY RESIN (LER)	25085-99-8	60 - 100
TALC (RESPIRABLE DUST)	14807-96-6	10 - 30
XYLENE	1330-20-7	5 - 10
ETHYL BENZENE	100-41-4	1 - 5

4. FIRST AID MEASURES

Eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin contact:	Wash off immediately with soap and plenty of water.
Ingestion:	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation:	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable properties	Flammable.
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous decomposition products	Oxides of carbon, hydrocarbons. Aldehydes.
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.
Protective equipment and precautions for firefighters	Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for cleaning up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
TALC (RESPIRABLE DUST)	: 2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	: 2 mg/m ³ TWA (<1% Crystalline silica, containing no Asbestos, respirable dust)	TWA: 3 mg/m ³ TWAEV (respirable dust)	TWA: 2 mg/m ³ TWA (containing no Asbestos and <1% Crystalline silica, respirable)	: 2 mg/m ³ TWA (respirable fraction)
XYLENE	: 100 ppm TWA : 150 ppm STEL	: 100 ppm TWA; 435 mg/m ³ TWA : 150 ppm STEL; 655 mg/m ³ STEL	TWA: 100 ppm TWAEV; 434 mg/m ³ TWAEV STEL: 150 ppm STEV; 651 mg/m ³ STEV	TWA: 100 ppm TWA STEL: 150 ppm STEL	: 100 ppm TWA; 435 mg/m ³ TWA : 150 ppm STEL; 655 mg/m ³ STEL
ETHYL BENZENE	: 100 ppm TWA : 125 ppm STEL	: 100 ppm TWA; 435 mg/m ³ TWA : 125 ppm STEL; 545 mg/m ³ STEL	TWA: 100 ppm TWAEV; 434 mg/m ³ TWAEV STEL: 125 ppm STEV; 543 mg/m ³ STEV	TWA: 100 ppm TWA STEL: 125 ppm STEL	: 100 ppm TWA; 435 mg/m ³ TWA : 125 ppm STEL; 545 mg/m ³ STEL

Engineering measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face protection

If splashes are likely to occur, wear Goggles.

Respiratory protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash point	27°C / 81.0°F
Boiling range	135 - 142°C / 275.0 - 288.0°F
Upper explosion limit	No information available
Lower explosion limit	No information available
Evaporation rate	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	1.25701 g/cm ³
Density	10.46022 lbs/gal
Volatile organic compounds (VOC) content	1.285 lbs/gal

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile by weight	12.2770 %
Volatile by volume	17.7180 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to avoid	Heat, flames and sparks. Amines.
Incompatible products	Strong oxidizing agents. Bases. Acids. Amines.	Possibility of hazardous reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
XYLENE	4300 mg/kg (Rat)	1700 mg/kg (Rabbit)	5000 ppm (Rat) 4 h 47635 mg/L (Rat) 4 h
ETHYL BENZENE	3500 mg/kg (Rat)	15354 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h

Irritation	No information available
Corrosivity	No information available
Sensitization	No information available

Chronic toxicity

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
ETHYL BENZENE	A3	Group 2B		X	

Mutagenicity	No information available
Reproductive effects	No information available
Developmental effects	No information available
Teratogenicity	No information available
Target Organ Effects	Blood, Central nervous system, Central Vascular System (CVS), Gastrointestinal tract, Eyes, Kidney, Liver, Respiratory system, Skin.
Endocrine Disruptor Information	No information available

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
EPOXY RESIN (LER)	Group III Chemical		

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
TALC (RESPIRABLE DUST)		LC50> 100 g/L Brachydanio rerio 96 h		

Component	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia
XYLENE		LC50= 13.4 mg/L Pimephales promelas 96 h LC50 2.661-4.093 mg/L Oncorhynchus mykiss 96 h LC50 13.5-17.3 mg/L Oncorhynchus mykiss 96 h LC50 13.1-16.5 mg/L Lepomis macrochirus 96 h LC50= 19 mg/L Lepomis macrochirus 96 h LC50 7.711-9.591 mg/L Lepomis macrochirus 96 h LC50 23.53-29.97 mg/L Pimephales promelas 96 h LC50= 780 mg/L Cyprinus carpio 96 h LC50> 780 mg/L Cyprinus carpio 96 h LC50 30.26-40.75 mg/L Poecilia reticulata 96 h	EC50 = 0.0084 mg/L 24 h	EC50 = 3.82 mg/L 48 h LC50 = 0.6 mg/L 48 h
ETHYL BENZENE	EC50 = 4.6 mg/L 72 h EC50 > 438 mg/L 96 h EC50 2.6 - 11.3 mg/L 72 h EC50 1.7 - 7.6 mg/L 96 h	LC50 11.0-18.0 mg/L Oncorhynchus mykiss 96 h LC50= 4.2 mg/L Oncorhynchus mykiss 96 h LC50 7.55-11 mg/L Pimephales promelas 96 h LC50= 32 mg/L Lepomis macrochirus 96 h LC50 9.1-15.6 mg/L Pimephales promelas 96 h LC50= 9.6 mg/L Poecilia reticulata 96 h	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 1.8 - 2.4 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste disposal methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.

Proper shipping name UN1263,PAINT,3,PGIII,ERG 128

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Complies
ENCS	Does not Comply
KECL	Complies
PICCS	Complies
AICS	Complies

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component
XYLENE

ETHYL BENZENE

United States of America Federal RegulationsSARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
XYLENE	1330-20-7	5 - 10	1.0 % de minimis concentration
ETHYL BENZENE	100-41-4	1 - 5	0.1 % de minimis concentration

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	yes
Acute Health Hazard	yes
Fire Hazard	yes
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE	100 lb RQ			X
ETHYL BENZENE	1000 lb RQ	X	X	X

CERCLAUnited States of America State RegulationsCalifornia Prop. 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
ETHYL BENZENE	100-41-4	Carcinogen

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
TALC (RESPIRABLE DUST)	X	X	X		X
XYLENE	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X

Other international regulationsCanada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

WHMIS Classification

B2 Flammable liquid
D2A Very toxic materials



Component	NPRI
XYLENE	Part 1, Group 1 Substance; Part 5 Substance
ETHYL BENZENE	Part 1, Group 1 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date 08-Jun-2011

Revision Note No information available

HMIS (Hazardous Material Information System) Health 2 Flammability 3 Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS