

Material Safety Data Sheet

Preparation Date: 08-Mar-2010

Revision Date: 08-Mar-2010

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code S252-00GRA
Trade Name MP VINYL ESTER GRAY
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

DANGER!

FLAMMABLE LIQUID AND VAPOR.
HARMFUL IF INHALED.
HARMFUL OR FATAL IF SWALLOWED.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.
MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes Moderately irritating to the eyes.
Skin Irritating to skin.
Inhalation Irritating to respiratory system.
Ingestion May be harmful if swallowed.

Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Kidney disorders. Liver disorders. Skin disorders.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Central nervous system, Eyes, Kidney, Liver, Lungs, Reproductive System, Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
STYRENE	100-42-5	31.3761
TITANIUM DIOXIDE (TOTAL DUST)	13463-67-7	1 - 5

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Flammable.
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous Decomposition Products	Oxides of carbon, hydrocarbons.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. VAPORS MAY CAUSE FLASH FIRE. Use only in an area containing flame proof equipment. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
STYRENE	TWA: 20 ppm STEL: 40 ppm	TWA: 50 ppm TWA: 215 mg/m ³ STEL: 100 ppm STEL: 425 mg/m ³ TWA: 100 ppm Ceiling: 200 ppm	TWA: 50 ppm TWA: 213 mg/m ³ STEL: 426 mg/m ³ STEL: 100 ppm Skin	TWA: 35 ppm STEL: 100 ppm	TWA: 215 mg/m ³ TWA: 50 ppm STEL: 425 mg/m ³ STEL: 100 ppm
TITANIUM DIOXIDE (TOTAL DUST)	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 15 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 20 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment**Skin Protection**

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

If splashes are likely to occur, wear Goggles.

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	21°C / 70.0°F
Boiling Point/Range	145 - 146°C / 293.0 - 295.0°F
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	1.11620
Density	9.28842
VOC Content (lbs/gal)	.017
% Volatile by Weight	.1860
% Volatile by Volume	.2363

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks.
Incompatible Products	Strong oxidizing agents. Acids.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
STYRENE	1000 mg/kg (Rat)		11.8 mg/L (Rat) 4 h
TITANIUM DIOXIDE (TOTAL DUST)	10000 mg/kg (Rat)		

Irritation	No information available
Corrosivity	No information available
Sensitization	No information available

Chronic Toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
STYRENE		Group 2B		X	
TITANIUM DIOXIDE (TOTAL DUST)		Group 2B		X	

Mutagenic Effects	No information available
Reproductive Effects	No information available
Developmental Effects	No information available
Teratogenicity	No information available
Target Organ Effects	Central nervous system, Eyes, Kidney, Liver, Lungs, Reproductive System, Respiratory system, Skin.

Endocrine Disruptor Information No information available

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
STYRENE	Group I Chemical	High Exposure Concern	

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
STYRENE	EC50 = 1.4 mg/L 72 h EC50 = 0.72 mg/L 96 h	LC50= 4.02 mg/L Pimephales promelas 96 h LC50= 25.05 mg/L Lepomis macrochirus 96 h LC50= 29 mg/L Pimephales promelas 96 h	EC50 = 5.4 mg/L 5 min	EC50 = 4.7 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNE MEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name UN1263,PAINT,3,PGIII,ERG 128

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Does not Comply
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Does not Comply
AICS	Does not Comply

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
STYRENE	100-42-5	31.3761	0.1

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
STYRENE	1000 lb			X

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
STYRENE	1000 lb	

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
STYRENE	X	X	X	X	X
TITANIUM DIOXIDE (TOTAL DUST)	X	X	X		X

Other International Regulations**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid

D2A Very toxic materials



Component	NPRI
STYRENE	Part 1, Group 1 Substance; Part 5 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 08-Mar-2010

Revision Summary: No information available

HMIS Health 2 Flammability 3 Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS



Material Safety Data Sheet

Preparation Date: 08-Mar-2010

Revision Date: 08-Mar-2010

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code S252-0252B
Trade Name MP VINYL ESTER VINYL ESTER PAR
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL OR FATAL IF SWALLOWED.
HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.
OXIDIZING

Potential Health Effects

Principle Routes of Exposure Eye contact, Skin contact, Inhalation.

Acute Effects

Eyes Severe irritation.
Skin Irritating to skin.
Inhalation Irritating to respiratory system.
Ingestion May be harmful if swallowed.

Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Skin disorders. Gastrointestinal tract. Kidney disorders. Liver disorders.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin, Gastrointestinal tract, Kidney, Liver

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
-----------	--------	----------

3. COMPOSITION/INFORMATION ON INGREDIENTS

METHYL ETHYL KETONE PEROXIDE	1338-23-4	38
DIMETHYL PHTHALATE	131-11-3	34
PROPRIETARY DILUENT		10 - 30
HYDROGEN PEROXIDE	7722-84-1	0.5

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Combustible material.
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous Decomposition Products	Oxides of carbon, hydrocarbons. Oxides of nitrogen.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Close container after each use. Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
METHYL ETHYL KETONE PEROXIDE	Ceiling: 0.2 ppm	Ceiling: 0.7 ppm 5 mg/m ³	Ceiling: 0.2 ppm Ceiling: 1.5 mg/m ³		Peak: 0.2 ppm Peak: 1.5 mg/m ³
DIMETHYL PHTHALATE	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³
HYDROGEN PEROXIDE	TWA: 1 ppm	TWA: 1.4 mg/m ³ TWA: 1 ppm	TWA: 1.4 mg/m ³ TWA: 1 ppm	TWA: 1.4 mg/m ³ TWA: 1 ppm	TWA: 1 ppm TWA: 1.5 mg/m ³ STEL: 2 ppm STEL: 3 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment**Skin Protection**

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

Goggles. If splashes are likely to occur, wear face-shield.

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene

Handle in accordance with good industrial hygiene and safety practice.

Considerations

Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	79°C / 175.0°F
Boiling Point/Range	No information available
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	1.07299
Density	8.92889
VOC Content (lbs/gal)	8.929
% Volatile by Weight	100.0000
% Volatile by Volume	100.0000

10. STABILITY AND REACTIVITY

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks.
Incompatible Products	Strong oxidizing agents. Acids. Alkalines. Promoters, accelerators, reducing agents, strong acids, and other reactive chemicals. Contamination of ANY foreign substance, exposure to heat, and direct sunlight.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ETHYL KETONE PEROXIDE	470 mg/kg (Rat)		200 ppm (Rat) 4 h
DIMETHYL PHTHALATE	6800 mg/kg (Rat)	4800 mg/kg (Rat) 20 mL/kg (Rabbit)	
HYDROGEN PEROXIDE	801 mg/kg (Rat)	4060 mg/kg (Rat) 2000 mg/kg (Rabbit)	2 mg/L (Rat) 4 h

Irritation	No information available
Corrosivity	No information available
Sensitization	No information available

Chronic Toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
HYDROGEN PEROXIDE	A3				A3

Mutagenic Effects	No information available
Reproductive Effects	No information available
Developmental Effects	No information available
Teratogenicity	No information available
Target Organ Effects	Central nervous system, Eyes, Respiratory system, Skin, Gastrointestinal tract, Kidney, Liver.
Endocrine Disruptor Information	No information available

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
DIMETHYL PHTHALATE	Group III Chemical		

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
DIMETHYL PHTHALATE	EC50 = 39.8 mg/L 96 h EC50 = 26.1 mg/L 96 h EC50 = 204 mg/L 72 h	LC50= 121 mg/L Pimephales promelas 96 h LC50= 49.5 mg/L Lepomis macrochirus 96 h LC50= 39 mg/L Pimephales promelas 96 h LC50= 35 mg/L Pimephales promelas 96 h LC50 100 - 220 mg/L Leuciscus idus 96 h	EC50 = 16.0 mg/L 5 min EC50 = 18.0 mg/L 15 min EC50 = 18.0 mg/L 30 min EC50 = 4100 mg/L 30 min EC50 > 2000 mg/L 17 h	EC50 = 33 mg/L 48 h
HYDROGEN PEROXIDE	EC50 = 2.5 mg/L 72 h	LC50= 16.4 mg/L Pimephales promelas 96 h		EC50 = 7.7 mg/L 24 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNE MEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name UN3109, ORGANIC PEROXIDE, TYPE F, LIQUID, (CUMYL HYDROPEROXIDE <90%), 5.2(8), PGII, ERG 145

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Does not Comply
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Does not Comply
AICS	Does not Comply

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Component
 DIMETHYL PHTHALATE

U.S. Federal Regulations

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values
DIMETHYL PHTHALATE	131-11-3	34	1.0

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No

Reactive Hazard

No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
DIMETHYL PHTHALATE			X	

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
METHYL ETHYL KETONE PEROXIDE	10 lb	
DIMETHYL PHTHALATE	5000 lb	
HYDROGEN PEROXIDE		1000 lb

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL ETHYL KETONE PEROXIDE	X	X	X		X
DIMETHYL PHTHALATE	X	X	X	X	X
HYDROGEN PEROXIDE	X	X	X		X

Other International Regulations**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B3 Combustible liquid
 C Oxidizing materials
 D2B Toxic materials
 E Corrosive material



Component	NPRI
DIMETHYL PHTHALATE	Part 1, Group 1 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 08-Mar-2010

Revision Summary: No information available

HMIS

Health 3

Flammability 2


Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS



Material Safety Data Sheet

Preparation Date: 04-Mar-2010

Revision Date: 04-Mar-2010

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code S211-0214
Trade Name FUMED SILICA S C MORTAR
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

HARMFUL BY INHALATION.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes May cause slight irritation.
Skin Irritating to skin.
Inhalation Irritating to respiratory system. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Ingestion May be harmful if swallowed.

Chronic Effects

Cancer hazard. Contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Kidney disorders. Liver disorders. Skin disorders.

Interactions with Other Chemicals No information available. Use of alcoholic beverages may enhance toxic effects.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Blood, Central nervous system, Central Vascular System, Eyes, Kidney, Liver, Lungs, Nasal Cavities, Prostate, Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	56.0747
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	37.3831
GLASS OXIDE	65997-17-3	1 - 5

3. COMPOSITION/INFORMATION ON INGREDIENTS

AMORPHOUS SILICA	7631-86-9	1 - 5
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.2336

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	No information available.
Suitable Extinguishing Media	Foam, carbon dioxide, and dry chemical.
Hazardous Decomposition Products	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	Shovel or sweep up.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Tightly fitting safety goggles. Wear protective gloves/clothing. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³

CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³
GLASS OXIDE	TWA: 1 fiber/cm ³ TWA: 5 mg/m ³ TWA: 0.5 mg/m ³ TWA: 0.05 mg/m ³ TWA: 0.2 mg/m ³ TWA: 0.1 mg/m ³ TWA: 0.02 mg/m ³ TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³	Ceiling: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 1 fibre/cm ³ TWA: 5 mg/m ³ TWA: 0.2 mg/m ³ TWA: 0.05 mg/m ³ TWA: 0.5 mg/m ³ TWA: 0.02 mg/m ³ TWA: 0.025 mg/m ³ TWA: 0.1 mg/m ³ STEL: 10 mg/m ³	TWA: 1 fibres/cm ³ TWA: 0.2 mg/m ³ TWA: 5 mg/m ³ TWA: 0.1 mg/m ³ TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³ TWA: 0.05 mg/m ³ STEL: 0.6 mg/m ³ STEL: 10 mg/m ³	TWA: 0.15 mg/m ³ TWA: 0.5 mg/m ³ TWA: 0.1 mg/m ³ TWA: 0.2 mg/m ³ TWA: 5 mg/m ³ TWA: 0.01 mg/m ³ TWA: 0.002 mg/m ³ STEL: 10 mg/m ³
CRYSTALLINE SILICA (QUARTZ)	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

Tightly fitting safety goggles

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	Not applicable
Boiling Point/Range	No information available
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	2.35477
Density	19.59522
VOC Content (lbs/gal)	.000
% Volatile by Weight	.0000
% Volatile by Volume	.0000

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks
Incompatible Products	No information available. Strong oxidizing agents. Acids. Reducing agents.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

11. TOXICOLOGICAL INFORMATION

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg (Rat)		
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg (Rat)		
AMORPHOUS SILICA	5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	2.2 mg/L (Rat) 1 h
CRYSTALLINE SILICA (QUARTZ)	500 mg/kg (Rat)		

Irritation No information available
Corrosivity No information available
Sensitization No information available

Chronic Toxicity

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	ACGIH	IARC	NTP	OSHA	Mexico
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	
GLASS OXIDE		Group 1 Group 2A			
CRYSTALLINE SILICA (QUARTZ)	A2	Group 1	Known	X	

Mutagenic Effects No information available
Reproductive Effects No information available
Developmental Effects No information available
Teratogenicity No information available
Target Organ Effects Blood, Central nervous system, Central Vascular System, Eyes, Kidney, Liver, Lungs, Nasal Cavities, Prostate, Respiratory system, Skin.
Endocrine Disruptor Information No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
GLASS OXIDE		LC50 5.6 - 7.4 µg/L Pimephales promelas 96 h LC50 9.4 - 9.7 µg/L Pimephales promelas 96 h LC50 24.2 - 48.4 µg/L Lepomis macrochirus 96 h		EC50 = 0.9 µg/L 48 h LC50 = 5 µg/L 96 h LC50 1.4 - 2.3 µg/L 96 h
AMORPHOUS SILICA	EC50 = 440 mg/L 72 h	LC50= 5000 mg/L Brachydanio rerio 96 h		EC50 = 7600 mg/L 48 h

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name SILCA,N.O.I.-20-P.C.F.,GREATER (ITEM 176370,Sub 3)

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
CHINA	Complies
ENCS	Does not Comply
KECL	Complies
PICCS	Does not Comply
AICS	Complies

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

U.S. Federal Regulations

SARA 313

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
GLASS OXIDE		X		

CERCLA

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen
GLASS OXIDE	65997-17-3	Carcinogen
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	Carcinogen

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X
GLASS OXIDE	X	X	X	X	X

AMORPHOUS SILICA	X		X		
CRYSTALLINE SILICA (QUARTZ)	X	X	X		X

Other International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class
D2A Very toxic materials



Legend
NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 04-Mar-2010

Revision Summary No information available

HMIS **Health** 1 **Flammability** 0 **Reactivity** 0

Disclaimer
For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS