



# ADHESION PROMOTER SERIES 44-900

## PRODUCT PROFILE

**GENERIC DESCRIPTION** Adhesion Promoter  
**COMMON USAGE** An additive package to promote the adhesion and corrosion protection of Series 35 and 115 to selected substrates and primers.

## TECHNICAL DATA

**VOLUME SOLIDS** 6.0 ± 0.1%  
**VOLITILE ORGANIC COMPOUNDS** 0 lbs/gallon (0 grams/litre)  
**PACKAGING** 32 ounce plastic container  
**NET WEIGHT PER GALLON** 8.42 ± 0.10 lbs (3.82 ± .11 kg)  
**STORAGE TEMPERATURE** Minimum 40°F (4°C) Maximum 110°F (43°C)  
 Protect from freezing.  
**SHELF LIFE** 12 months at recommended storage temperature.  
**FLASH POINT - SETA** >200°F (95°C)  
**HEALTH & SAFETY** Paint products contain chemical ingredients which are considered hazardous. Read container label warning and Material Safety Data Sheet for important health and safety information prior to the use of this product.  
**Keep out of the reach of children.**

## APPLICATION

**MIXING** Shake container before addition to insure complete incorporation. Add measured amount of 44-900 to paint and mix well under low agitation. **DO NOT BOX OR SHAKE.** Recommended levels are:

Series	5 Gallon	1 Gallon	Quart
35	25 ounces	5 ounces	1.2 ounces
115	25 ounces	5 ounces	1.2 ounces

WARRANTY & LIMITATION OF SELLER'S LIABILITY: Tnemec Company, Inc. warrants only that its coatings represented herein meet the formulation standards of Tnemec Company, Inc. THE WARRANTY DESCRIBED IN THE ABOVE PARAGRAPH SHALL BE IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES THAT EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The buyer's sole and exclusive remedy against Tnemec Company, Inc. shall be for replacement of the product in the event a defective condition of the product should be found to exist and the exclusive remedy shall not have failed its essential purpose as long as Tnemec is willing to provide comparable replacement product to the buyer. NO OTHER REMEDY (INCLUDING, BUT NOT LIMITED TO, INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR LOST PROFITS, LOST SALES, INJURY TO PERSON OR PROPERTY, ENVIRONMENTAL INJURIES OR ANY OTHER INCIDENTAL OR CONSEQUENTIAL LOSS) SHALL BE AVAILABLE TO THE BUYER. Technical and application information herein is provided for the purpose of establishing a general profile of the coating and proper coating application procedures. Test performance results were obtained in a controlled environment and Tnemec Company makes no claim that these tests or any other tests, accurately represent all environments. As application, environmental and design factors can vary significantly, due care should be exercised in the selection and use of the coating.

